Matte Black Professional Gaffers Tape

Rolls per Case (1.89 in / 48mm): 24

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd | 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

–

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a

particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

Premium Grade 7-Day Stucco Duct Tape

CL-W6045 is a premium grade, 7-day cloth, stucco duct tape designed for stucco applications. Used to protect vinyl windows, profiles, and door frames, the stucco duct tape has superior holding power and leaves limited residue if removed within seven days.

APPLICATIONS FOR THE TAPE

The most common applications for the 7-day stucco duct tape include:

- protects door frames, vinyl windows, and profiles during outdoor stucco application
- used for one-coat stucco processes

FEATURES OF THE TAPE

Features of the 7-day stucco duct tape include:

- strong holding power and durability (prevents lifting)
- doesn’t leave residue (if removed within 7 days)
- conforms to uneven surfaces
- can tear the tape by hand (leaving a clean, straight edge)
- easy to apply (doesn’t curl or splinter)

TAPE ADHESIVE

The tape has a high-performance rubber adhesive.

WEATHER RESISTANCE

The 7-day stucco duct tape is weather resistant:

- can be used indoors and outdoors
- outstanding UV resistance (lasting up to 7 days)

TAPE SIZES

The 7-day stucco duct tape is available in the following size:

- 2 inches by 60 yards / 48 mm by 55 m

TAPE COLORS

The 7-day stucco duct tape is available in blue.

WHO USES THE TAPE

The tape is most commonly used by:

- stucco contractors
- painting contractors

ECHOtape PART NUMBER

The part number for this tape is CL-W6045.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd | 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

–

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a

particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

Premium Grade 60 Day Stucco Duct Tape Gray

CL-W6059 is a premium grade, gray 60-day cloth stucco duct tape that was developed for stucco professionals. Designed to protect window frames and door frames during outdoor masking applications, the tape is strong and durable and will peel off without leaving residue.

APPLICATIONS FOR THE TAPE

The most common applications for the 60-day stucco duct tape include:

- protects vinyl windows, profiles, and doorframes during outdoor stucco applications
- recommended by Milgard for use with their vinyl and fiberglass windows
- used in 2-step and 3-step stucco processes (scratch, brown, and finish) where the protective barrier is used throughout the entire stucco application

FEATURES OF THE TAPE

Features of the 60-day stucco duct tape include:

- superior holding power and durability in hot temperatures
- limited residue when removed within 60 days of application
- sticks well to smooth surfaces (such as steel and plastic)
- sticks well to rough or textured surfaces (such as wood)
- conforms to uneven surfaces
- can tear the tape by hand (leaving a clean, straight edge)
- easy to apply (doesn’t curl or splinter)

TAPE ADHESIVE

The tape has a high-performance rubber adhesive.

WEATHER RESISTANCE

The 60-day stucco duct tape is weather resistant:

- can be used indoors and outdoors
- outstanding UV resistance
- holds up in hot temperatures

TAPE SIZES

The 60-day stucco duct tape is available in the following sizes:

- 2 inches by 60 yards / 48 mm by 55 m

TAPE COLORS

The 60-day stucco duct tape is available in gray.

WHO USES THE TAPE

The tape is most commonly used by:

- stucco contractors
- painting contractors

ECHOtape PART NUMBER

The part number for this tape is CL-W6059.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords

- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd | 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

Industrial Strength Utility Grade Duct Tape

CL-W6064 is an industrial-strength duct tape that’s no ordinary duct tape! Made with an advanced adhesive technology, the duct tape provides superior holding power, yet is easy to tear and apply. This heavy-duty duct tape sticks well to smooth and rough surfaces, and it can be used for holding, seaming, repairing, and bundling.

Applications For the Tape

The most common applications for the industrial duct tape include:

- temporary holding and bonding
- general purpose use and repair
- hanging and patching polyethylene sheeting
- duct work
- bundling
- color coding
- applications in manufacturing and industrial environments

Features Of the Tape

Features of the industrial duct tape include:

- aggressive adhesive
- superior holding power
- sticks well to a wide variety of smooth and rough surfaces
- conforms to uneven surfaces
- can tear the tape by hand (leaving a clean, straight edge)
- unwinds smoothly (making it easier to apply)
- tape lays flat (no twisting or curling)

Tape Adhesive

The tape has a high-performance rubber adhesive.

Tape Sizes

The industrial duct tape is available in the following size:

- 2 inches by 60 yards / 48 mm by 55 m

Tape Colors

The industrial duct tape is available in silver, black, yellow, red, blue, green, and white.

Who Uses the Tape

The tape is most commonly used by:

- construction professionals
- HVAC contractors
- contractors

ECHOtape Part Number

The part number for this tape is CL-W6064.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd | 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber

THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

–

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for

Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

Premium Grade 60-Day Stucco Duct Tape [Red]

CL-W6089 is a premium grade, red cloth duct tape that’s designed to protect and mask windows, profiles, and door frames during outdoor stucco applications. Strong and durable, this 60-day stucco duct tape has a high-tack rubber adhesive that holds up well in hot temperatures, high winds, and moist conditions. Easy to apply, the tape leaves limited residue if removed within 60 days.

APPLICATIONS FOR THE TAPE
The most common applications for the 60-day stucco duct tape include:

- protects vinyl windows, profiles, and doorframes during outdoor stucco applications
- used in 2-step and 3-step stucco processes (scratch,

brown, and finish) where the protective barrier is left in place throughout the entire stucco application

FEATURES OF THE TAPE

Features of the 60-day stucco duct tape include:

- superior holding power in hot temperatures, high winds, and moist conditions
- limited residue when removed within 60 days of application
- conforms to uneven surfaces
- can tear the tape by hand (leaving a clean, straight edge)
- easy to apply (doesn’t curl or splinter)

TAPE ADHESIVE

The tape has a high-performance rubber adhesive.

WEATHER RESISTANCE

The 60-day stucco duct tape is weather resistant:

- holds well in high temperatures
- holds well in high winds
- holds well in moist conditions
- outstanding UV resistance (lasting up to 60 days)

TAPE SIZES

The 60-day stucco duct tape is available in the following sizes:

- 2 inches by 60 yards / 48 mm by 55 m

TAPE COLORS
The 60-day stucco duct tape is available in red.

WHO USES THE TAPE
The tape is most commonly used by:

- stucco contractors
- painting contractors

ECHOtape PART NUMBER
The part number for this tape is CL-W6089.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant

- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd | 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

–

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are

warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

Double Sided Removable Carpet Tape

DC-W18FF is an extremely effective double-sided, removable carpet tape, with a strong adhesive that won’t leave behind residue. The carpet tape is ideal for professionals who manage trade shows, conventions, and other large events that require carpeting and other types of temporary flooring to be quickly laid down and then easily removed.

And these aren’t the only uses for this unique removable tape!

It can also be used for construction and industrial mounting applications (for holding vapor barrier film, for mounting film for construction processes, for printing plates in industrial print packaging, and more).

APPLICATIONS FOR THE TAPE

The most common applications for the double-sided, removable carpet tape include:

- laying down carpet and other types of temporary flooring
- holding vapor barrier film In place when encapsulating crawl spaces
- mounting film when creating clean rooms or containment rooms
- mounting film for demolition and remediation processes
- mounting printing plates for industrial print packaging applications

FEATURES OF THE TAPE

Features of the double-sided, removable carpet tape include:

- aggressive adhesive on the liner side of the tape
- especially suited for adhesion to carpet
- adhesive on the exposed side of the tape leaves no residue when removed
- easy release poly liner
- fast to apply and easy to use

TAPE ADHESIVE

The tape has a rubber adhesive.

WEATHER RESISTANCE

The double-sided, removable carpet tape is designed for indoor use.

TAPE SIZES

The double-sided, removable carpet tape is available in the following sizes:

- 2 inches by 36 yards / 48 mm x 33 m
- 2.75 inches by 36 yards / 72 mm x 33 m

TAPE COLORS

The double-sided, removable carpet tape is available in beige.

WHO USES THE TAPE

The tape is most commonly used by:

- trade show contractors
- convention contractors
- event organizers
- construction contractors
- printers who specialize in industrial print packaging

ECHOtape PART NUMBER

The part number for this tape is DC-W188F.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts,

trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd | 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.