

# Strong Double Sided Tape For Temporary Hold

DC-K048A is an extremely strong, double-sided tape that's designed to mount or bond items temporarily. The tape sticks very well to smooth surfaces (such as steel and paper), but also can be used on wood, fabric, and other porous and textured surfaces. When you need your temporary hold to hold up, this double-sided tape will do the trick!

## APPLICATIONS FOR THE TAPE

The most common applications for the temporary double-sided tape include:

- temporarily hold down steel or metal components
- temporarily hold down wooden components
- temporarily hold small carpets in place
- mount posters or photographs on walls

## FEATURES OF THE TAPE

Features of the temporary double-sided tape include:

- excellent holding power from the onset
- removes cleanly from most hard and smooth surfaces
- easy to remove the paper liner
- can tear the tape by hand
- designed to work at room temperature, the tape can also perform for medium heat applications

## TAPE ADHESIVE



---

The tape has a high-performance rubber adhesive.

### **TAPE SIZES**

The temporary double-sided tape is available in the following size:

- 1 inch by 36 yards / 24 mm by 33 m

### **TAPE COLORS**

The temporary double-sided tape is available in beige.

### **WHO USES THE TAPE**

The tape is most commonly used by:

- manufacturers
- printers
- woodworkers
- interior decorators and designers

### **ECHOtape PART NUMBER**

The part number for this tape is DC-K048A.

## **Applications**

- Use to temporarily hold down steel or metal components in manufacturing or printing applications
- Use to temporarily hold down wooden components in woodworking applications
- Use to mount posters or photographs on walls
- Use to temporarily hold small carpets in place



---

## Features & Benefits

- Hand tearable making it very easy to apply and use
- Excellent holding power from the onset helps speed up application
- Easy to remove paper liner
- Removes cleanly from most hard and smooth surfaces

## Technical Data

<b>SIZES</b>	.94 in x 36 yd   24 mm x 33m
<b>CARRIER</b>	Crepe Paper
<b>ADHESIVE</b>	Rubber
<b>TOTAL THICKNESS</b>	6 mils
<b>RELEASE LINER</b>	Crepe Paper
<b>TENSILE</b>	23 lbs/in
<b>ADHESION</b>	47 oz/in
<b>APPLICATION TEMPERATURE</b>	50°F to 110°F (10°C to 43°C)
<b>SERVICE TEMPERATURE</b>	32°F to 180°F (0°C to 82°C)
<b>ELONGATION</b>	8.5%
<b>COLOR</b>	Beige

## Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape



---

should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

# **Clear Double Sided Tape for Permanent Mounting and Bonding**

DC-M012P is an extremely strong and aggressive, double-sided tape that's designed to mount or bond items permanently. Thanks to its high-performance acrylic adhesive, this double-sided tape can be used for difficult bonding applications where other tapes might fail. The clear tape sticks well to a variety of surfaces, including plexiglass, rubber, plastic, metal, and steel.

## **APPLICATIONS FOR THE TAPE**

The most common applications for the permanent double-sided tape include:

- permanent bonding of steel, metal, plastic, rubber, and plexiglass
- mounting small to medium, lightweight indoor and outdoor signs
- mounting nameplates
- mounting decorative trims
- mounting plastic profiles
- joining or splicing various types of polyester films
- difficult bonding applications where other tapes might not adhere properly

## **FEATURES OF THE TAPE**



---

Features of the permanent double-sided tape include:

- strong hold from the onset
- easily conforms to most surfaces
- superior adhesion to polyester films
- easy-to-remove red paper liner makes it quick to apply the tape
- acrylic adhesive provides maximum performance indoors and outdoors

#### **TAPE ADHESIVE**

The tape has a high-performance acrylic adhesive.

#### **WEATHER RESISTANCE**

The permanent double-sided tape can be used indoors and outdoors.

#### **TAPE SIZES**

The permanent double-sided tape is available in the following size:

- 1 inch by 36 yards / 24 mm by 33 m

#### **TAPE COLORS**

The permanent double-sided tape is available in clear (transparent).

#### **WHO USES THE TAPE**

The tape is most commonly used by:

- sign companies
- plexiglass installers



- insulation companies
- contractors who use polyester film
- interior decorators and designers

### **ECHOtape PART NUMBER**

The part number for this tape is DC-M012P.

### **Applications**

- Use to temporarily hold down steel or metal components in manufacturing or printing applications
- Use to temporarily hold down wooden components in woodworking applications
- Use to mount posters or photographs on walls
- Use to temporarily hold small carpets in place

### **Features & Benefits**

- Hand tearable making it very easy to apply and use
- Excellent holding power from the onset helps speed up application
- Easy to remove paper liner
- Removes cleanly from most hard and smooth surfaces

### **Technical Data**

<b>SIZES</b>	.94 in x 36 yd   24 mm x 33m
<b>CARRIER</b>	Crepe Paper
<b>ADHESIVE</b>	Rubber

<b>TOTAL THICKNESS</b>	6 mils
<b>RELEASE LINER</b>	Crepe Paper
<b>TENSILE</b>	23 lbs/in
<b>ADHESION</b>	47 oz/in
<b>APPLICATION TEMPERATURE</b>	50°F to 110°F (10°C to 43°C)
<b>SERVICE TEMPERATURE</b>	32°F to 180°F (0°C to 82°C)
<b>ELONGATION</b>	8.5%
<b>COLOR</b>	Beige

## Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or



otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

---

## **Clear Double Sided Polyester Tape for General Purpose Mounting & Bonding**

DC-M158A is the perfect permanent double-sided tape for everyday applications around the office, warehouse, workshop, or classroom. The aggressive, acrylic adhesive bonds to virtually any surface, and on hard surfaces, you can reposition the tape within 60 seconds of application. Designed for lightweight mounting and bonding, the double-sided tape can be applied to textiles, foils, films, papers, plastic, metal, and more!

### **APPLICATIONS FOR THE TAPE**



---

The most common applications for the permanent double-sided tape include:

- permanent bonding of papers, films, foils, textiles, leather, plastic, and metal
- general assembly of decorative parts
- temporary bonding to keep items in place prior to fastening them
- bonding textiles and leather prior to sewing

### **FEATURES OF THE TAPE**

Features of the permanent double-sided tape include:

- fast-grabbing adhesive sticks well from the onset
- can reposition the tape within 60 seconds (but only on hard surfaces)
- adheres well to a variety of surfaces
- polyester carrier is flexible and conforms to many surfaces
- can tear the tape by hand
- performs well across a broad range of temperatures

### **TAPE ADHESIVE**

The tape has an aggressive, high-tack acrylic adhesive.

### **WEATHER RESISTANCE**

The permanent double-sided tape performs well across a wide range of temperatures.

### **TAPE SIZES**

The permanent double-sided tape is available in the following sizes:

- 1 inch by 55 yards / 24 mm by 50 m
- 2 inches by 55 yards / 48 mm by 50 m

### **TAPE COLORS**

The permanent double-sided tape is available in clear (transparent).

### **WHO USES THE TAPE**

The tape is most commonly used in:

- offices
- warehouses
- workshops
- classrooms
- sewing workrooms

### **ECHOtape PART NUMBER**

The part number for this tape is DC-M158A.

### **Applications**

- Use to temporarily hold down steel or metal components in manufacturing or printing applications
- Use to temporarily hold down wooden components in woodworking applications
- Use to mount posters or photographs on walls
- Use to temporarily hold small carpets in place



---

## Features & Benefits

- Hand tearable making it very easy to apply and use
- Excellent holding power from the onset helps speed up application
- Easy to remove paper liner
- Removes cleanly from most hard and smooth surfaces

## Technical Data

<b>SIZES</b>	.94 in x 36 yd   24 mm x 33m
<b>CARRIER</b>	Crepe Paper
<b>ADHESIVE</b>	Rubber
<b>TOTAL THICKNESS</b>	6 mils
<b>RELEASE LINER</b>	Crepe Paper
<b>TENSILE</b>	23 lbs/in
<b>ADHESION</b>	47 oz/in
<b>APPLICATION TEMPERATURE</b>	50°F to 110°F (10°C to 43°C)
<b>SERVICE TEMPERATURE</b>	32°F to 180°F (0°C to 82°C)
<b>ELONGATION</b>	8.5%
<b>COLOR</b>	Beige

## Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and



---

free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

---

# **All Weather/Cold Weather**

# Double Sided Polyester Tape

DC-M194A is a high-performance, double-sided polyester film tape, designed specifically to work well in cold weather temperatures. Often used in commercial construction and metal building insulation applications, the double-sided PET tape is also versatile enough for a broad range of environmental conditions.

## APPLICATIONS FOR THE TAPE

The most common applications for the double-sided polyester tape (PET tape) include:

- mounting insulation
- creating lap seals on laminated insulation, reflective insulation, and jacketing insulation
- permanently bonding foams, plastics, metals, and composite materials
- mounting smooth surface substrates in cold temperatures (such as freezers)

## FEATURES OF THE TAPE

Features of the double-sided polyester tape (PET tape) include:

- superior holding power
- bonds well to a variety of surfaces
- specially formulated as a cold weather adhesive tape
- polyester (PET) carrier allows for UV resistance



- can tear the tape by hand
- can apply the tape by hand or with a machine

## **TAPE ADHESIVE**

The double-sided polyester film tape (PET tape) tape is coated with a specially engineered acrylic adhesive that's designed to work exceptionally well in cold temperatures.

## **WEATHER RESISTANCE**

The PET tape is an all-weather and cold temperature tape:

- specifically designed for extremely cold weather
- can be used indoors and outdoors
- UV resistant

## **TAPE SIZES**

The polyester film tape (PET tape) is available in the following sizes:

- 1 inch by 60 yards / 24 mm by 55 m
- 1.5 inches by 60 yards / 36 mm by 55 m
- 2 inches by 60 yards / 48 mm by 55 m

## **TAPE COLORS**

The high-performance, polyester film tape (PET tape) is transparent.

## **WHO USES THE TAPE**

The tape is most commonly used by:



- metal building insulation contractors
- commercial construction contractors

## ECHOtape PART NUMBER

The part number for this tape is DC-M194A.

## Applications

- Use to temporarily hold down steel or metal components in manufacturing or printing applications
- Use to temporarily hold down wooden components in woodworking applications
- Use to mount posters or photographs on walls
- Use to temporarily hold small carpets in place

## Features & Benefits

- Hand tearable making it very easy to apply and use
- Excellent holding power from the onset helps speed up application
- Easy to remove paper liner
- Removes cleanly from most hard and smooth surfaces

## Technical Data

<b>SIZES</b>	.94 in x 36 yd   24 mm x 33m
<b>CARRIER</b>	Crepe Paper
<b>ADHESIVE</b>	Rubber
<b>TOTAL THICKNESS</b>	6 mils



---

<b>RELEASE LINER</b>	Crepe Paper
<b>TENSILE</b>	23 lbs/in
<b>ADHESION</b>	47 oz/in
<b>APPLICATION TEMPERATURE</b>	50°F to 110°F (10°C to 43°C)
<b>SERVICE TEMPERATURE</b>	32°F to 180°F (0°C to 82°C)
<b>ELONGATION</b>	8.5%
<b>COLOR</b>	Beige

## Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes

no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

---

## **General Purpose Clear Double Sided Tape for Mounting Bonding (Paper)**

DC-T274A is a general-purpose, double-sided tape that can be used for everyday applications around the office, warehouse, workshop, or classroom. Able to stick to almost any surface, this fast-grabbing, clear tape works well for lightweight mounting and bonding applications to textiles, foils, films, papers, plastic, metal, and more.

### **APPLICATIONS FOR THE TAPE**

The most common applications for the double-sided tape include:

- permanent bonding of papers, films, foils, textiles,

- leather, plastic, and metal
- general assembly of decorative parts
- temporary bonding to keep items in place prior to fastening them
- bonding textiles and leather prior to sewing

## **FEATURES OF THE TAPE**

Features of the double-sided tape include:

- fast-grabbing adhesive sticks well from the onset
- adheres well to a variety of surfaces
- flexible enough to conform to many surfaces
- can tear the tape by hand
- easy to remove the paper liner

## **TAPE ADHESIVE**

The tape has an aggressive, high-tack acrylic adhesive.

## **TAPE SIZES**

The double-sided tape is available in the following sizes:

- 1/2 inch by 55 yards / 12 mm by 50 m
- 3/4 inch by 55 yards / 18 mm by 50 m
- 1 inch by 55 yards / 24 mm by 50 m
- 2 inches by 55 yards / 48 mm by 50 m

## **TAPE COLORS**

The double-sided tape is available in frosted clear.

## **WHO USES THE TAPE**

The tape is most commonly used in:

- offices
- warehouses
- workshops
- classrooms
- sewing workrooms

### **ECHOtape PART NUMBER**

The part number for this tape is DC-T274A.

### **Applications**

- Use to temporarily hold down steel or metal components in manufacturing or printing applications
- Use to temporarily hold down wooden components in woodworking applications
- Use to mount posters or photographs on walls
- Use to temporarily hold small carpets in place

### **Features & Benefits**

- Hand tearable making it very easy to apply and use
- Excellent holding power from the onset helps speed up application
- Easy to remove paper liner
- Removes cleanly from most hard and smooth surfaces

### **Technical Data**

<b>SIZES</b>	.94 in x 36 yd   24 mm x 33m
<b>CARRIER</b>	Crepe Paper

<b>ADHESIVE</b>	Rubber
<b>TOTAL THICKNESS</b>	6 mils
<b>RELEASE LINER</b>	Crepe Paper
<b>TENSILE</b>	23 lbs/in
<b>ADHESION</b>	47 oz/in
<b>APPLICATION TEMPERATURE</b>	50°F to 110°F (10°C to 43°C)
<b>SERVICE TEMPERATURE</b>	32°F to 180°F (0°C to 82°C)
<b>ELONGATION</b>	8.5%
<b>COLOR</b>	Beige

## Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a

particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

---

## **White Double Sided Tape for Permanent Mounting & Bonding**

DC-U032A is an extremely aggressive and strong double-sided mounting tape that is designed for permanent bonding and will stick to just about any surface.

### **APPLICATIONS FOR THE TAPE**

The most common applications for the permanent, double-sided mounting tape include:

- permanent bonding of metal, plastic, rubber, plexiglass, and wood
- mounting small to medium, lightweight indoor and outdoor

signs

- mounting name plates
- mounting decorative trim
- bonding applications where other tapes might not adhere properly

## **FEATURES OF THE TAPE**

Features of the permanent, double-sided mounting tape include:

- superior holding power (from the onset)
- sticks well to smooth surfaces (such as steel and plastic)
- adheres to rough and textured surfaces (such as wood)
- conforms to most surfaces
- easy to apply (the tape can be easily removed from its liner)
- designed to work at room temperature, the tape can also perform for medium heat applications

## **TAPE ADHESIVE**

The tape has an acrylic adhesive.

## **WEATHER RESISTANCE**

The permanent, double-sided mounting tape is weather resistant:

- can be used indoors and outdoors
- resistant to extreme weather and other environmental conditions



---

## TAPE SIZES

The permanent, double-sided mounting tape is available in the following sizes:

- 1/2 inch by 54.6 yards / 12 mm by 50 m
- 3/4 inch by 54.6 yards / 18 mm by 50 m
- 1 inch by 54.6 yards / 24 mm by 50 m
- 2 inches by 54.6 yards / 48 mm by 50 m

## TAPE COLORS

The permanent, double-sided mounting tape is available in white.

## WHO USES THE TAPE

The tape is most commonly used by:

- construction professionals
- flooring contractors
- insulation contractors
- handymen
- sign makers
- interior decorators and designers

## ECHOtape PART NUMBER

The part number for this tape is DC-U032A.

## Applications

- Use to temporarily hold down steel or metal components in manufacturing or printing applications





- Use to temporarily hold down wooden components in woodworking applications
- Use to mount posters or photographs on walls
- Use to temporarily hold small carpets in place

## Features & Benefits

- Hand tearable making it very easy to apply and use
- Excellent holding power from the onset helps speed up application
- Easy to remove paper liner
- Removes cleanly from most hard and smooth surfaces

## Technical Data

<b>SIZES</b>	.94 in x 36 yd   24 mm x 33m
<b>CARRIER</b>	Crepe Paper
<b>ADHESIVE</b>	Rubber
<b>TOTAL THICKNESS</b>	6 mils
<b>RELEASE LINER</b>	Crepe Paper
<b>TENSILE</b>	23 lbs/in
<b>ADHESION</b>	47 oz/in
<b>APPLICATION TEMPERATURE</b>	50°F to 110°F (10°C to 43°C)
<b>SERVICE TEMPERATURE</b>	32°F to 180°F (0°C to 82°C)
<b>ELONGATION</b>	8.5%
<b>COLOR</b>	Beige

## **Storage & Usage Conditions**

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

# Clear Double Sided Tape for Permanent Mounting & Bonding

DC-U101A is double-sided UPVC tape that incorporates a high-tack and high-peel acrylic adhesive system. This unique UPVC tape is often used for product assembly, difficult bonding and splicing applications, and lamination on a variety of materials (including EPDM rubber, plastic, glass, and urethane foams).

## APPLICATIONS FOR THE TAPE

The most common applications for the double-sided UPVC tape include:

- product assembly
- difficult bonding and splicing applications
- lamination to EPDM rubber, plastic, glass, and urethane foams

## FEATURES OF THE TAPE

Features of the double-sided UPVC tape include:

- exceptionally high-tack and high-peel
- high-adhesive mass helps fill gaps
- UPVC film allows conformability
- adheres well to ether foams and ester foams
- bonds well to rough surfaces and porous surfaces

- excellent resistance to environmental extremes
- water resistant

### **TAPE ADHESIVE**

The tape incorporates an exceptionally high-tack and high-peel acrylic adhesive system.

### **WEATHER RESISTANCE**

The double-sided UPVC tape is weather resistant:

- excellent resistance to environmental extremes
- water resistant
- to achieve best results, recommended application temperature is 65 degrees Fahrenheit / 18 degrees Celsius

### **TAPE SIZES**

The double-sided UPVC tape is available in the following sizes:

- 1/2 inch by 60 yards / 12 mm by 55 m
- 1 inch by 60 yards / 24 mm by 55 m
- 2 inches by 60 yards / 48 mm by 50 m

### **TAPE COLORS**

The double-sided UPVC tape is available in clear (transparent).

### **WHO USES THE TAPE**

The tape is most commonly used in:

- product assembly

- bonding and splicing
- manufacturing
- industrial environments
- construction and building
- electronics

### **ECHOtape PART NUMBER**

The part number for this tape is DC-U101A.

### **Applications**

- Use to temporarily hold down steel or metal components in manufacturing or printing applications
- Use to temporarily hold down wooden components in woodworking applications
- Use to mount posters or photographs on walls
- Use to temporarily hold small carpets in place

### **Features & Benefits**

- Hand tearable making it very easy to apply and use
- Excellent holding power from the onset helps speed up application
- Easy to remove paper liner
- Removes cleanly from most hard and smooth surfaces

### **Technical Data**

<b>SIZES</b>	.94 in x 36 yd   24 mm x 33m
<b>CARRIER</b>	Crepe Paper

<b>ADHESIVE</b>	Rubber
<b>TOTAL THICKNESS</b>	6 mils
<b>RELEASE LINER</b>	Crepe Paper
<b>TENSILE</b>	23 lbs/in
<b>ADHESION</b>	47 oz/in
<b>APPLICATION TEMPERATURE</b>	50°F to 110°F (10°C to 43°C)
<b>SERVICE TEMPERATURE</b>	32°F to 180°F (0°C to 82°C)
<b>ELONGATION</b>	8.5%
<b>COLOR</b>	Beige

## Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a

particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

---

## **Double Sided Removable Carpet Tape**

DC-W18FF is an extremely effective double-sided, removable carpet tape, with a strong adhesive that won't leave behind residue. The carpet tape is ideal for professionals who manage trade shows, conventions, and other large events that require carpeting and other types of temporary flooring to be quickly laid down and then easily removed.

And these aren't the only uses for this unique removable tape! It can also be used for construction and industrial mounting applications (for holding vapor barrier film, for mounting film for construction processes, for printing plates in

industrial print packaging, and more).

## **APPLICATIONS FOR THE TAPE**

The most common applications for the double-sided, removable carpet tape include:

- laying down carpet and other types of temporary flooring
- holding vapor barrier film in place when encapsulating crawl spaces
- mounting film when creating clean rooms or containment rooms
- mounting film for demolition and remediation processes
- mounting printing plates for industrial print packaging applications

## **FEATURES OF THE TAPE**

Features of the double-sided, removable carpet tape include:

- aggressive adhesive on the liner side of the tape
- especially suited for adhesion to carpet
- adhesive on the exposed side of the tape leaves no residue when removed
- easy release poly liner
- fast to apply and easy to use

## **TAPE ADHESIVE**

The tape has a rubber adhesive.

## **WEATHER RESISTANCE**

The double-sided, removable carpet tape is designed for indoor



use.

## **TAPE SIZES**

The double-sided, removable carpet tape is available in the following sizes:

- 2 inches by 36 yards / 48 mm x 33 m
- 2.75 inches by 36 yards / 72 mm x 33 m

## **TAPE COLORS**

The double-sided, removable carpet tape is available in beige.

## **WHO USES THE TAPE**

The tape is most commonly used by:

- trade show contractors
- convention contractors
- event organizers
- construction contractors
- printers who specialize in industrial print packaging

## **ECHOtape PART NUMBER**

The part number for this tape is DC-W188F.

## **Applications**

- Use to temporarily hold down steel or metal components in manufacturing or printing applications
- Use to temporarily hold down wooden components in woodworking applications



- Use to mount posters or photographs on walls
- Use to temporarily hold small carpets in place

## Features & Benefits

- Hand tearable making it very easy to apply and use
- Excellent holding power from the onset helps speed up application
- Easy to remove paper liner
- Removes cleanly from most hard and smooth surfaces

## Technical Data

<b>SIZES</b>	.94 in x 36 yd   24 mm x 33m
<b>CARRIER</b>	Crepe Paper
<b>ADHESIVE</b>	Rubber
<b>TOTAL THICKNESS</b>	6 mils
<b>RELEASE LINER</b>	Crepe Paper
<b>TENSILE</b>	23 lbs/in
<b>ADHESION</b>	47 oz/in
<b>APPLICATION TEMPERATURE</b>	50°F to 110°F (10°C to 43°C)
<b>SERVICE TEMPERATURE</b>	32°F to 180°F (0°C to 82°C)
<b>ELONGATION</b>	8.5%
<b>COLOR</b>	Beige

## **Storage & Usage Conditions**

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

# Double Sided Foam Glazing Tape

GL-N0708 and GL-N0716 are double-sided, foam glazing tapes that are designed for window glazing applications. Available in 1/8 inch and 1/16 inch thicknesses, the tape is coated on each side with a high-tack acrylic adhesive that's quick to set and continues to strengthen over time. Made with a soft and flexible polyethylene foam, the double-sided glazing tape adapts to a variety of textured surfaces.

## APPLICATIONS FOR THE TAPE

The most common applications for the double-sided, foam glazing tape include:

- window glazing applications on aluminum window framing
- window glazing applications on PVC window framing
- bonding and mounting lightweight plastic
- bonding and mounting lightweight metal

## FEATURES OF THE TAPE

Features of the double-sided, foam glazing tape include:

- seals well against water, dust, and light
- resistant to weather, temperature, UV, and oxidation
- flexible and soft, which makes it easy to adjust to a

- variety of textured surfaces
- sticks well from the onset
- acrylic adhesive continues to strengthen over time
- easy release poly liner
- AAMA certified (which makes it suitable for glazing applications)

## **TAPE ADHESIVE**

The tape has an acrylic adhesive.

## **WEATHER RESISTANCE**

The double-sided, foam glazing tape has excellent weather resistance, UV resistance, temperature resistance, and oxidation resistance.

## **TAPE SIZES**

The double-sided foam glazing tape is available in the following sizes:

- 1/8 inch thick: 3/8 inch by 75 feet / 10 mm x 23 m
- 1/16 inch thick: 1/3 inch by 150 feet / 9 mm x 46 m
- 1/16 inch thick: 3/8 inch by 150 feet / 10 mm x 46 m
- 1/16 inch thick: 1/2 inch by 150 feet / 12 mm x 46 m

## **TAPE COLORS**

The double-sided, foam glazing tape is available in black and white.

## **WHO USES THE TAPE**

The tape is most commonly used by:

- window contractors
- glass companies

## ECHOtape PART NUMBER

The part numbers for this tape are GL-N0708 (1/8 inch thickness) and GL-N0716 (1/16 inch thickness).

## Applications

- Use to temporarily hold down steel or metal components in manufacturing or printing applications
- Use to temporarily hold down wooden components in woodworking applications
- Use to mount posters or photographs on walls
- Use to temporarily hold small carpets in place

## Features & Benefits

- Hand tearable making it very easy to apply and use
- Excellent holding power from the onset helps speed up application
- Easy to remove paper liner
- Removes cleanly from most hard and smooth surfaces

## Technical Data

SIZES	.94 in x 36 yd   24 mm x 33m
CARRIER	Crepe Paper
ADHESIVE	Rubber

---

<b>TOTAL THICKNESS</b>	6 mils
<b>RELEASE LINER</b>	Crepe Paper
<b>TENSILE</b>	23 lbs/in
<b>ADHESION</b>	47 oz/in
<b>APPLICATION TEMPERATURE</b>	50°F to 110°F (10°C to 43°C)
<b>SERVICE TEMPERATURE</b>	32°F to 180°F (0°C to 82°C)
<b>ELONGATION</b>	8.5%
<b>COLOR</b>	Beige

## Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or

otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

---

## **High Performance Indoor/Outdoor Double Sided Acrylic Foam Tape**

UB-F3504 is a gray, heavy-duty, double-sided foam tape that's designed for demanding jobs! This double-sided tape has a high-performance, acrylic adhesive that's been engineered for permanent mounting and bonding to metal, plastics, and woods (including rough, textured, and painted surfaces). The double-sided foam tape is so strong that it's often used as an alternative to traditional fasteners. Designed for indoor and outdoor use, the tape offers outstanding resistance to hot temperatures, cold temperatures, and extreme weather fluctuations.



## **APPLICATIONS FOR THE TAPE**

The most common applications for the double-sided foam tape include:

- attaching automotive exterior trim parts
- attaching automotive side body moldings, claddings, roof ditch moldings, wheel flares, and tailgate appliques
- mounting muntin / SDL bars on wooden, metal, and vinyl doors
- mounting indoor signage (the tape can be used in place of a fastener)
- mounting outdoor signage (the tape can be used in place of a fastener)

## **FEATURES OF THE TAPE**

Features of the double-sided foam tape include:

- adheres well to metal, wood, and plastics (including hard-to-stick plastics)
- adheres well to rough, textured, or painted surfaces
- strong enough to support heavier loads than typical double-sided tapes
- excellent temperature resistance
- highly flexible (sticks well to curved surfaces)
- easily adapts to a variety of surfaces
- good shock absorption properties

## **TAPE ADHESIVE**

The tape has a high-performance acrylic adhesive.

## **WEATHER RESISTANCE**

The double-sided foam tape is weather resistant:

- can be used indoors and outdoors
- resistant to heat and cold
- resistant to extreme weather fluctuations

## **TAPE SIZES**

The double-sided foam tape is available in the following sizes:

- 1/3 inch by 36 yards / 9 mm x 33 m
- 1/2 inch by 36 yards / 12 mm x 33 m
- 3/4 inch by 36 yards / 18 mm x 33 m
- 1 inch by 36 yards / 24 mm x 33 m

## **TAPE COLORS**

The double-sided foam tape is available in gray (with an easy-release red polyethylene film).

## **WHO USES THE TAPE**

The tape is most commonly used by:

- auto repair shops
- auto body shops
- sign companies
- carpenters
- window and door installation specialists
- glass companies and glaziers
- general contractors

- handymen

## **ECHOtape PART NUMBER**

The part number for this tape is UB-F3504.

## **Applications**

- Use to temporarily hold down steel or metal components in manufacturing or printing applications
- Use to temporarily hold down wooden components in woodworking applications
- Use to mount posters or photographs on walls
- Use to temporarily hold small carpets in place

## **Features & Benefits**

- Hand tearable making it very easy to apply and use
- Excellent holding power from the onset helps speed up application
- Easy to remove paper liner
- Removes cleanly from most hard and smooth surfaces

## **Technical Data**

<b>SIZES</b>	.94 in x 36 yd   24 mm x 33m
<b>CARRIER</b>	Crepe Paper
<b>ADHESIVE</b>	Rubber
<b>TOTAL THICKNESS</b>	6 mils

RELEASE LINER	Crepe Paper
TENSILE	23 lbs/in
ADHESION	47 oz/in
APPLICATION TEMPERATURE	50°F to 110°F (10°C to 43°C)
SERVICE TEMPERATURE	32°F to 180°F (0°C to 82°C)
ELONGATION	8.5%
COLOR	Beige

## Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes

no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

---

## **High Performance Indoor/Outdoor Double Sided Acrylic Foam Tape**

UB-F3557 is a clear, heavy-duty, double-sided foam tape that's designed for demanding jobs! This double-sided tape has a high-performance, acrylic adhesive that's been engineered for permanent mounting and bonding to metal, plastics, and woods (including rough, textured, and painted surfaces). The double-sided foam tape is so strong that it's often used as an alternative to traditional fasteners. Designed for indoor and outdoor use, the tape offers outstanding resistance to hot temperatures, cold temperatures, and extreme weather fluctuations.

## **APPLICATIONS FOR THE TAPE**

The most common applications for the double-sided foam tape include:

- attaching automotive exterior trim parts
- attaching automotive side body moldings, claddings, roof ditch moldings, wheel flares, and tailgate appliques
- mounting muntin / SDL bars on wooden, metal, and vinyl doors
- mounting indoor signage (the tape can be used in place of a fastener)
- mounting outdoor signage (the tape can be used in place of a fastener)

## **FEATURES OF THE TAPE**

Features of the double-sided foam tape include:

- adheres well to metal, wood, and plastics (including hard-to-stick plastics)
- adheres well to rough, textured, or painted surfaces
- strong enough to support heavier loads than typical double-sided tapes
- excellent temperature resistance
- highly flexible (sticks well to curved surfaces)
- easily adapts to a variety of surfaces
- good shock absorption properties

## **TAPE ADHESIVE**

The tape has a high-performance acrylic adhesive.

## **WEATHER RESISTANCE**

The double-sided foam tape is weather resistant:

- can be used indoors and outdoors
- resistant to heat and cold
- resistant to extreme weather fluctuations

## **TAPE SIZES**

The double-sided foam tape is available in the following sizes:

- 1/2 inch by 36 yards / 12 mm x 33 m
- 1 inch by 36 yards / 24 mm x 33 m

## **TAPE COLORS**

The double-sided foam tape is available in clear (with an easy-release red polyethylene film).

## **WHO USES THE TAPE**

The tape is most commonly used by:

- auto repair shops
- auto body shops
- sign companies
- carpenters
- window and door installation specialists
- glass companies and glaziers
- general contractors
- handymen



---

## ECHOtape PART NUMBER

The part number for this tape is UB-F3557.

## Applications

- Use to temporarily hold down steel or metal components in manufacturing or printing applications
- Use to temporarily hold down wooden components in woodworking applications
- Use to mount posters or photographs on walls
- Use to temporarily hold small carpets in place

## Features & Benefits

- Hand tearable making it very easy to apply and use
- Excellent holding power from the onset helps speed up application
- Easy to remove paper liner
- Removes cleanly from most hard and smooth surfaces

## Technical Data

<b>SIZES</b>	.94 in x 36 yd   24 mm x 33m
<b>CARRIER</b>	Crepe Paper
<b>ADHESIVE</b>	Rubber
<b>TOTAL THICKNESS</b>	6 mils
<b>RELEASE LINER</b>	Crepe Paper
<b>TENSILE</b>	23 lbs/in



---

<b>ADHESION</b>	47 oz/in
<b>APPLICATION TEMPERATURE</b>	50°F to 110°F (10°C to 43°C)
<b>SERVICE TEMPERATURE</b>	32°F to 180°F (0°C to 82°C)
<b>ELONGATION</b>	8.5%
<b>COLOR</b>	Beige

## Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for

Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.