



All Weather/Cold Weather Double Sided Polyester Tape

DC-M194A is a high-performance, double-sided polyester film tape, designed specifically to work well in cold weather temperatures. Often used in commercial construction and metal building insulation applications, the double-sided PET tape is also versatile enough for a broad range of environmental conditions.

APPLICATIONS FOR THE TAPE

The most common applications for the double-sided polyester tape (PET tape) include:

- mounting insulation
- creating lap seals on laminated insulation, reflective insulation, and jacketing insulation
- permanently bonding foams, plastics, metals, and composite materials
- mounting smooth surface substrates in cold temperatures (such as freezers)

FEATURES OF THE TAPE

Features of the double-sided polyester tape (PET tape) include:

- superior holding power
- bonds well to a variety of surfaces
- specially formulated as a cold weather adhesive tape
- polyester (PET) carrier allows for UV resistance



-
- can tear the tape by hand
 - can apply the tape by hand or with a machine

TAPE ADHESIVE

The double-sided polyester film tape (PET tape) tape is coated with a specially engineered acrylic adhesive that's designed to work exceptionally well in cold temperatures.

WEATHER RESISTANCE

The PET tape is an all-weather and cold temperature tape:

- specifically designed for extremely cold weather
- can be used indoors and outdoors
- UV resistant

TAPE SIZES

The polyester film tape (PET tape) is available in the following sizes:

- 1 inch by 60 yards / 24 mm by 55 m
- 1.5 inches by 60 yards / 36 mm by 55 m
- 2 inches by 60 yards / 48 mm by 55 m

TAPE COLORS

The high performance, polyester film tape (PET tape) is transparent.

WHO USES THE TAPE

The tape is most commonly used by:

- metal building insulation contractors
- commercial construction contractors



ECH0tape PART NUMBER

The part number for this tape is DC-M194A.

Applications

- Use for lap seals on laminated, reflective and pipe jacketing insulation
- Use to mount smooth surface substrates in freezers
- Use for permanently bonding foams, plastics, metals and composite materials.
- Use for insulation mounting

Features & Benefits

- Hand tearable
- Hand or machine applied
- Excellent holding power
- Specially formulated cold weather adhesive
- Bonds well to a variety of surfaces
- PET carrier allows for UV resistance
- Performs well under a broad range of environmental conditions

Technical Data



SIZES	1.41 in x 60 yd. 36 mm x 55 m 1.41 in x 180 yd. 36 mm x 165 m 1.41 in x 360 yd. 36 mm x 330 m
Carrier	Polyester Film
Adhesive	Acrylic
Release Liner	Siliconized Paper
Total Thickness	3.6 mils
Tensile	7.7 lbs/in
Adhesion	40 oz/in
Application Temperature Range	-4°F to 176°F (-20°C to 90°C)
Service Temperature Range	-40°F to 176°F (-40°C to 80°C)
Elongation	75%
Color	Transparent

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—



The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

Single Sided Thermal Break Tape (1/4" and 1/8" thick)

F0-V2344 and F0-V2348 are single-sided thermal break tapes, designed to reduce thermal bridging on outer and inner framing in metal buildings. Available in 1/4 inch and 1/8 inch thicknesses, the tape has excellent holding power and high-load capability.



APPLICATIONS FOR THE TAPE

The most common applications for the single-sided thermal break tape include:

- create a vapor seal where large gaps occur
- create a lap joint seal on corrugated metal building panels or prefabricated wall panels
- create a flash break on building purlins and girt flanges
- maintain a seal in high movement joints

FEATURES OF THE TAPE

Features of the single-sided thermal break tape include:

- adheres strongly to smooth and rough surfaces (including corrugated metal)
- easy to apply
- sticks quickly (which speeds up application)
- conforms well to irregular surfaces
- easy to die-cut for custom sizing
- the paper release liner protects the adhesive from contaminants when cutting the tape to specific lengths

TAPE ADHESIVE

The tape has an acrylic adhesive.

TAPE SIZES

The single-sided thermal break tape is available in the following sizes:

- 2 inches by 50 feet (1/4 inch thick)
- 3 inches by 50 feet (1/4 inch thick)



-
- 2 inches by 75 feet (1/8 inch thick)
 - 3 inches by 75 feet (1/8 inch thick)

TAPE COLORS

The single-sided thermal break tape is available in gray.

WHO USES THE TAPE

The tape is most commonly used by:

- construction professionals
- building contractors
- insulation contractors
- metal building specialists

ECHOtape PART NUMBER

The part numbers for this tape are F0-V2344 (1/4 inch thickness) and F0-V2348 (1/8 inch thickness).

Applications

- Use for lap seals on laminated, reflective and pipe jacketing insulation
- Use to mount smooth surface substrates in freezers
- Use for permanently bonding foams, plastics, metals and composite materials.
- Use for insulation mounting

Features & Benefits

- Hand tearable
- Hand or machine applied



- Excellent holding power
- Specially formulated cold weather adhesive
- Bonds well to a variety of surfaces
- PET carrier allows for UV resistance
- Performs well under a broad range of environmental conditions

Technical Data

SIZES	1.41 in x 60 yd. 36 mm x 55 m 1.41 in x 180 yd. 36 mm x 165 m 1.41 in x 360 yd. 36 mm x 330 m
Carrier	Polyester Film
Adhesive	Acrylic
Release Liner	Siliconized Paper
Total Thickness	3.6 mils
Tensile	7.7 lbs/in
Adhesion	40 oz/in
Application Temperature Range	-4°F to 176°F (-20°C to 90°C)
Service Temperature Range	-40°F to 176°F (-40°C to 80°C)
Elongation	75%
Color	Transparent



Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.



All Weather Lamtec WMP®-VR Facing Tape

FS-G7731 is an all-weather, facing tape primarily used to seal and seam Lamtec WMP-VR faced insulation that's used in metal buildings. Easy to apply and quick to stick, the Lamtec WMP-VR facing tape delivers a strong bond, even at cold temperatures.

APPLICATIONS FOR THE TAPE

The Lamtec WMP-VR facing tape is used to:

- seam and join Lamtec WMP-VR faced insulation
- repair tears on Lamtec WMP-VR faced insulation

FEATURES OF THE TAPE

Features of the Lamtec WMP-VR facing tape include:

- quick to stick
- creates a strong bond
- performs well across a broad range of temperatures (including cold temperatures)
- excellent vapor barrier
- low WVTR (water vapor transmission rate)
- paper liner is easy to remove
- can be cut to specific lengths for use in tight areas

TAPE ADHESIVE

The Lamtec WMP-VR facing tape has a cold-weather, acrylic adhesive.



WEATHER RESISTANCE

The Lamtec WMP-VR tape is weather resistant:

- works well in cold weather – bonds well at low temperature
- excellent vapor barrier
- low WVTR (water vapor transmission rate)

TAPE SIZES

The Lamtec WMP-VR facing tape is available in the following size:

- 2.75 inches by 50 yards / 72 mm x 46 m

TAPE COLORS

The Lamtec WMP-VR facing tape is available in white and black.

WHO USES THE TAPE

The tape is most commonly used by:

- metal building insulation contractors

ECH0tape PART NUMBER

The part number for this tape is FS-G7731.

Note that Lamtec and WMP are registered trademarks of Lamtec Corporation.

Applications

- Use for lap seals on laminated, reflective and pipe jacketing insulation



-
- Use to mount smooth surface substrates in freezers
 - Use for permanently bonding foams, plastics, metals and composite materials.
 - Use for insulation mounting

Features & Benefits

- Hand tearable
- Hand or machine applied
- Excellent holding power
- Specially formulated cold weather adhesive
- Bonds well to a variety of surfaces
- PET carrier allows for UV resistance
- Performs well under a broad range of environmental conditions

Technical Data

SIZES	1.41 in x 60 yd. 36 mm x 55 m 1.41 in x 180 yd. 36 mm x 165 m 1.41 in x 360 yd. 36 mm x 330 m
Carrier	Polyester Film
Adhesive	Acrylic
Release Liner	Siliconized Paper
Total Thickness	3.6 mils
Tensile	7.7 lbs/in



Adhesion	40 oz/in
Application Temperature Range	-4°F to 176°F (-20°C to 90°C)
Service Temperature Range	-40°F to 176°F (-40°C to 80°C)
Elongation	75%
Color	Transparent

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not



otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

All Weather Lamtec WMP®-VR-R Plus Facing Tape

FS-G7732 is an adhesive tape used primarily to seal and seam Lamtec® WMP-VR-R Plus faced Insulation used in metal buildings. It is coated with a high performance cold weather acrylic adhesive offering a superior quick stick, it also provides a strong bond and great performance at low temperatures. The paper release liner protects the adhesive from contaminants when you need to cut the tape to specific lengths for use in tight areas ensuring a strong bond once applied.

Lamtec and WMP are registered trademarks of Lamtec Corporation.

Applications

- Use for lap seals on laminated, reflective and pipe jacketing insulation
- Use to mount smooth surface substrates in freezers
- Use for permanently bonding foams, plastics, metals and



composite materials.

- Use for insulation mounting

Features & Benefits

- Hand tearable
- Hand or machine applied
- Excellent holding power
- Specially formulated cold weather adhesive
- Bonds well to a variety of surfaces
- PET carrier allows for UV resistance
- Performs well under a broad range of environmental conditions

Technical Data

SIZES	1.41 in x 60 yd. 36 mm x 55 m 1.41 in x 180 yd. 36 mm x 165 m 1.41 in x 360 yd. 36 mm x 330 m
Carrier	Polyester Film
Adhesive	Acrylic
Release Liner	Siliconized Paper
Total Thickness	3.6 mils
Tensile	7.7 lbs/in
Adhesion	40 oz/in



Application Temperature Range	-4°F to 176°F (-20°C to 90°C)
Service Temperature Range	-40°F to 176°F (-40°C to 80°C)
Elongation	75%
Color	Transparent

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct,



indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

All Weather Lamtec WMP 10 Metal Facing Tape

FS-G7735 is an adhesive tape used primarily to seal and seam Lamtec® WMP®-10 faced Insulation used in metal buildings. It is coated with a high performance cold weather acrylic adhesive offering a superior quick stick, it also provides a strong bond and great performance at low temperatures. The paper release liner protects the adhesive from contaminants when you need to cut the tape to specific lengths for use in tight areas ensuring a strong bond once applied.

Applications

- Use for lap seals on laminated, reflective and pipe jacketing insulation
- Use to mount smooth surface substrates in freezers
- Use for permanently bonding foams, plastics, metals and composite materials.
- Use for insulation mounting



Features & Benefits

- Hand tearable
- Hand or machine applied
- Excellent holding power
- Specially formulated cold weather adhesive
- Bonds well to a variety of surfaces
- PET carrier allows for UV resistance
- Performs well under a broad range of environmental conditions

Technical Data

SIZES	1.41 in x 60 yd. 36 mm x 55 m 1.41 in x 180 yd. 36 mm x 165 m 1.41 in x 360 yd. 36 mm x 330 m
Carrier	Polyester Film
Adhesive	Acrylic
Release Liner	Siliconized Paper
Total Thickness	3.6 mils
Tensile	7.7 lbs/in
Adhesion	40 oz/in
Application Temperature Range	-4°F to 176°F (-20°C to 90°C)
Service Temperature Range	-40°F to 176°F (-40°C to 80°C)
Elongation	75%



Color	Transparent
-------	-------------

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.



All Weather Lamtec WMP®-50 Metal Facing Tape

FS-G7736 is an adhesive tape used primarily to seal and seam Lamtec® WMP-50 faced Insulation used in metal buildings. It is coated with a high performance cold weather acrylic adhesive offering a superior quick stick, it also provides a strong bond and great performance at low temperatures. The paper release liner protects the adhesive from contaminants when you need to cut the tape to specific lengths for use in tight areas ensuring a strong bond once applied.

Lamtec and WMP are registered trademarks of Lamtec Corporation.

Applications

- Use for lap seals on laminated, reflective and pipe jacketing insulation
- Use to mount smooth surface substrates in freezers
- Use for permanently bonding foams, plastics, metals and composite materials.
- Use for insulation mounting

Features & Benefits

- Hand tearable



- Hand or machine applied
- Excellent holding power
- Specially formulated cold weather adhesive
- Bonds well to a variety of surfaces
- PET carrier allows for UV resistance
- Performs well under a broad range of environmental conditions

Technical Data

SIZES	1.41 in x 60 yd. 36 mm x 55 m 1.41 in x 180 yd. 36 mm x 165 m 1.41 in x 360 yd. 36 mm x 330 m
Carrier	Polyester Film
Adhesive	Acrylic
Release Liner	Siliconized Paper
Total Thickness	3.6 mils
Tensile	7.7 lbs/in
Adhesion	40 oz/in
Application Temperature Range	-4°F to 176°F (-20°C to 90°C)
Service Temperature Range	-40°F to 176°F (-40°C to 80°C)
Elongation	75%
Color	Transparent



Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.



All Weather EHP VR-R Plus Facing Tape

FS-G7739 is an adhesive tape used primarily to seal and seam EHP VR-R Plus faced Insulation used in metal buildings. It is coated with a high performance cold weather acrylic adhesive offering a superior quick stick, it also provides a strong bond and great performance at low temperatures. The paper release liner protects the adhesive from contaminants when you need to cut the tape to specific lengths for use in tight areas ensuring a strong bond once applied.

Applications

- Use for lap seals on laminated, reflective and pipe jacketing insulation
- Use to mount smooth surface substrates in freezers
- Use for permanently bonding foams, plastics, metals and composite materials.
- Use for insulation mounting

Features & Benefits

- Hand tearable
- Hand or machine applied
- Excellent holding power
- Specially formulated cold weather adhesive
- Bonds well to a variety of surfaces
- PET carrier allows for UV resistance



- Performs well under a broad range of environmental conditions

Technical Data

SIZES	1.41 in x 60 yd. 36 mm x 55 m 1.41 in x 180 yd. 36 mm x 165 m 1.41 in x 360 yd. 36 mm x 330 m
Carrier	Polyester Film
Adhesive	Acrylic
Release Liner	Siliconized Paper
Total Thickness	3.6 mils
Tensile	7.7 lbs/in
Adhesion	40 oz/in
Application Temperature Range	-4°F to 176°F (-20°C to 90°C)
Service Temperature Range	-40°F to 176°F (-40°C to 80°C)
Elongation	75%
Color	Transparent

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape



works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

All Weather ASJ Kraft



Insulation Facing Tape

FS-J7744 is an adhesive tape used primarily to seal and seam ASJ faced duct board and fiberglass pipe insulation installed by mechanical insulation contractors. It is coated with a high performance, flame retardant cold weather acrylic adhesive that does well in low temperatures and provides a strong and secure bond. The paper liner protects the adhesive from contaminants when you need to cut the tape to specific lengths ensuring a strong bond once applied. This tape is UL 723 Classified and mold resistant.

Applications

- Use for lap seals on laminated, reflective and pipe jacketing insulation
- Use to mount smooth surface substrates in freezers
- Use for permanently bonding foams, plastics, metals and composite materials.
- Use for insulation mounting

Features & Benefits

- Hand tearable
- Hand or machine applied
- Excellent holding power
- Specially formulated cold weather adhesive
- Bonds well to a variety of surfaces
- PET carrier allows for UV resistance
- Performs well under a broad range of environmental



conditions

Technical Data

SIZES	1.41 in x 60 yd. 36 mm x 55 m 1.41 in x 180 yd. 36 mm x 165 m 1.41 in x 360 yd. 36 mm x 330 m
Carrier	Polyester Film
Adhesive	Acrylic
Release Liner	Siliconized Paper
Total Thickness	3.6 mils
Tensile	7.7 lbs/in
Adhesion	40 oz/in
Application Temperature Range	-4°F to 176°F (-20°C to 90°C)
Service Temperature Range	-40°F to 176°F (-40°C to 80°C)
Elongation	75%
Color	Transparent

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and



free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

All Weather ASJ Poly



Insulation Facing Tape

FS-J7754 is an adhesive tape used primarily to seal and seam ASJ faced duct board and fiberglass pipe insulation installed by mechanical insulation contractors. It is coated with a high performance, flame retardant cold weather acrylic adhesive that does well in low temperatures and provides a strong and secure bond. The paper liner protects the adhesive from contaminants when you need to cut the tape to specific lengths ensuring a strong bond once applied. This tape is UL 723 Classified and mold resistant.

Applications

- Use for lap seals on laminated, reflective and pipe jacketing insulation
- Use to mount smooth surface substrates in freezers
- Use for permanently bonding foams, plastics, metals and composite materials.
- Use for insulation mounting

Features & Benefits

- Hand tearable
- Hand or machine applied
- Excellent holding power
- Specially formulated cold weather adhesive
- Bonds well to a variety of surfaces
- PET carrier allows for UV resistance
- Performs well under a broad range of environmental



conditions

Technical Data

SIZES	1.41 in x 60 yd. 36 mm x 55 m 1.41 in x 180 yd. 36 mm x 165 m 1.41 in x 360 yd. 36 mm x 330 m
Carrier	Polyester Film
Adhesive	Acrylic
Release Liner	Siliconized Paper
Total Thickness	3.6 mils
Tensile	7.7 lbs/in
Adhesion	40 oz/in
Application Temperature Range	-4°F to 176°F (-20°C to 90°C)
Service Temperature Range	-40°F to 176°F (-40°C to 80°C)
Elongation	75%
Color	Transparent

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and



free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

All

Weather

FSK



(Foil/Scrim/Kraft) Insulation Facing Tape

FS-K7751 is an adhesive tape used to primarily seal foil faced insulation such as FSK faced fiberglass ductboard and blanket systems installed by mechanical insulation contractors. It is coated with a high performance, flame retardant cold weather acrylic adhesive that does well in low temperatures and provides a strong bond to a variety of surfaces and textures. The epoxy resin coating helps protect the surface against corrosion from moisture. The paper liner protects the adhesive from contaminants when you need to cut the tape to specific lengths ensuring a strong bond once applied. This tape is UL 723 Classified and mold resistant.

Applications

- Use for lap seals on laminated, reflective and pipe jacketing insulation
- Use to mount smooth surface substrates in freezers
- Use for permanently bonding foams, plastics, metals and composite materials.
- Use for insulation mounting

Features & Benefits

- Hand tearable
- Hand or machine applied
- Excellent holding power



- Specially formulated cold weather adhesive
- Bonds well to a variety of surfaces
- PET carrier allows for UV resistance
- Performs well under a broad range of environmental conditions

Technical Data

SIZES	1.41 in x 60 yd. 36 mm x 55 m 1.41 in x 180 yd. 36 mm x 165 m 1.41 in x 360 yd. 36 mm x 330 m
Carrier	Polyester Film
Adhesive	Acrylic
Release Liner	Siliconized Paper
Total Thickness	3.6 mils
Tensile	7.7 lbs/in
Adhesion	40 oz/in
Application Temperature Range	-4°F to 176°F (-20°C to 90°C)
Service Temperature Range	-40°F to 176°F (-40°C to 80°C)
Elongation	75%
Color	Transparent



Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.



All Weather White Aluminum Foil Tape

MT-A7729 is a high strength off white aluminum foil tape used to primarily seal joints for foam core insulation boards. It is coated with a superior performance flame retardant cold weather acrylic adhesive, and conforms well to surfaces providing a strong bond. This adhesive tape offers good reliability across both high and low temperature ranges. The paper release liner protects the adhesive from contaminants when the tape needs to be cut to specific lengths for use in tight spaces ensuring a strong bond once applied.

Applications

- Use for lap seals on laminated, reflective and pipe jacketing insulation
- Use to mount smooth surface substrates in freezers
- Use for permanently bonding foams, plastics, metals and composite materials.
- Use for insulation mounting

Features & Benefits

- Hand tearable
- Hand or machine applied
- Excellent holding power
- Specially formulated cold weather adhesive
- Bonds well to a variety of surfaces



- PET carrier allows for UV resistance
- Performs well under a broad range of environmental conditions

Technical Data

SIZES	1.41 in x 60 yd. 36 mm x 55 m 1.41 in x 180 yd. 36 mm x 165 m 1.41 in x 360 yd. 36 mm x 330 m
Carrier	Polyester Film
Adhesive	Acrylic
Release Liner	Siliconized Paper
Total Thickness	3.6 mils
Tensile	7.7 lbs/in
Adhesion	40 oz/in
Application Temperature Range	-4°F to 176°F (-20°C to 90°C)
Service Temperature Range	-40°F to 176°F (-40°C to 80°C)
Elongation	75%
Color	Transparent

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape



should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.



All Weather Aluminum Foil Tape

MT-A7772 is a high strength aluminum foil tape coated with a superior performance flame retardant solvent acrylic adhesive. The foil material allows maximum conformability in vapor sealing fiberglass duct boards and FSK systems. A low moisture vapor transmission rate offers outstanding sealing and patching performance, providing an excellent vapor seal. This tape features good aging resistance both indoors and outdoors. A superior quick stick at normal operating temperatures and great performance at low temperatures.

Applications

- Use for lap seals on laminated, reflective and pipe jacketing insulation
- Use to mount smooth surface substrates in freezers
- Use for permanently bonding foams, plastics, metals and composite materials.
- Use for insulation mounting

Features & Benefits

- Hand tearable
- Hand or machine applied
- Excellent holding power
- Specially formulated cold weather adhesive
- Bonds well to a variety of surfaces



- PET carrier allows for UV resistance
- Performs well under a broad range of environmental conditions

Technical Data

SIZES	1.41 in x 60 yd. 36 mm x 55 m 1.41 in x 180 yd. 36 mm x 165 m 1.41 in x 360 yd. 36 mm x 330 m
Carrier	Polyester Film
Adhesive	Acrylic
Release Liner	Siliconized Paper
Total Thickness	3.6 mils
Tensile	7.7 lbs/in
Adhesion	40 oz/in
Application Temperature Range	-4°F to 176°F (-20°C to 90°C)
Service Temperature Range	-40°F to 176°F (-40°C to 80°C)
Elongation	75%
Color	Transparent

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape



should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.



Embossed Vinyl Seaming & Patching Tape

VI-V6460 is a single sided tape primarily used to seam and patch white vinyl insulation in metal building construction applications. It is coated with an aggressive all temperature acrylic adhesive making it reliable across a variety of temperature ranges and reliable enough to stand up to the elements. The paper liner protects the adhesive from contaminants when you need to cut the tape to specific lengths ensuring a strong bond once applied.

Applications

- Use for lap seals on laminated, reflective and pipe jacketing insulation
- Use to mount smooth surface substrates in freezers
- Use for permanently bonding foams, plastics, metals and composite materials.
- Use for insulation mounting

Features & Benefits

- Hand tearable
- Hand or machine applied
- Excellent holding power
- Specially formulated cold weather adhesive
- Bonds well to a variety of surfaces
- PET carrier allows for UV resistance



- Performs well under a broad range of environmental conditions

Technical Data

SIZES	1.41 in x 60 yd. 36 mm x 55 m 1.41 in x 180 yd. 36 mm x 165 m 1.41 in x 360 yd. 36 mm x 330 m
Carrier	Polyester Film
Adhesive	Acrylic
Release Liner	Siliconized Paper
Total Thickness	3.6 mils
Tensile	7.7 lbs/in
Adhesion	40 oz/in
Application Temperature Range	-4°F to 176°F (-20°C to 90°C)
Service Temperature Range	-40°F to 176°F (-40°C to 80°C)
Elongation	75%
Color	Transparent

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape



works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.