

Premium Grade 7-Day Stucco Duct Tape

CL-W6045 is a premium grade, 7-day cloth, stucco duct tape designed for stucco applications. Used to protect vinyl windows, profiles, and door frames, the stucco duct tape has superior holding power and leaves limited residue if removed within seven days.

APPLICATIONS FOR THE TAPE

The most common applications for the 7-day stucco duct tape include:

- protects door frames, vinyl windows, and profiles during outdoor stucco application
- used for one-coat stucco processes

FEATURES OF THE TAPE

Features of the 7-day stucco duct tape include:

- strong holding power and durability (prevents lifting)
- doesn't leave residue (if removed within 7 days)
- conforms to uneven surfaces
- can tear the tape by hand (leaving a clean, straight edge)
- easy to apply (doesn't curl or splinter)

TAPE ADHESIVE

The tape has a high-performance rubber adhesive.



WEATHER RESISTANCE

The 7-day stucco duct tape is weather resistant:

- can be used indoors and outdoors
- outstanding UV resistance (lasting up to 7 days)

TAPE SIZES

The 7-day stucco duct tape is available in the following size:

- 2 inches by 60 yards / 48 mm by 55 m

TAPE COLORS

The 7-day stucco duct tape is available in blue.

WHO USES THE TAPE

The tape is most commonly used by:

- stucco contractors
- painting contractors

ECHOtape PART NUMBER

The part number for this tape is CL-W6045.

Applications

- Designed to protect window and door frames in outdoor stucco masking applications
- Designed for single family, multi-family and commercial construction projects
- Used in one coat stucco processes



Features & Benefits

- Outstanding UV resistance lasting up to 7 days
- Residue free when removed within 7 days
- Excellent holding power and durability
- Conforms to uneven surfaces
- Holds strong which prevents lifting
- Can be torn by hand leaving a clean and straight edge
- Does not curl or splinter making it easy to apply
- Trusted by professional contractors nationwide

Technical Data

SIZES	1.89 in x 60 yd 48 mm x 55 m
CARRIER	Waterproof Polyethylene Coated Cloth
ADHESIVE	Rubber
TOTAL THICKNESS	9.5 mils
TENSILE	25 lbs/in
ADHESION	22 oz/in
COLOR	Blue

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best



when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability

Premium Grade 60 Day Stucco Duct Tape Gray

CL-W6059 is a premium grade, gray 60-day cloth stucco duct tape that was developed for stucco professionals. Designed to protect window frames and door frames during outdoor masking applications, the tape is strong and durable and will peel off without leaving residue.

APPLICATIONS FOR THE TAPE

The most common applications for the 60-day stucco duct tape include:

- protects vinyl windows, profiles, and doorframes during outdoor stucco applications
- recommended by Milgard for use with their vinyl and fiberglass windows
- used in 2-step and 3-step stucco processes (scratch, brown, and finish) where the protective barrier is used throughout the entire stucco application

FEATURES OF THE TAPE

Features of the 60-day stucco duct tape include:

- superior holding power and durability in hot temperatures
- limited residue when removed within 60 days of application



-
- sticks well to smooth surfaces (such as steel and plastic)
 - sticks well to rough or textured surfaces (such as wood)
 - conforms to uneven surfaces
 - can tear the tape by hand (leaving a clean, straight edge)
 - easy to apply (doesn't curl or splinter)

TAPE ADHESIVE

The tape has a high-performance rubber adhesive.

WEATHER RESISTANCE

The 60-day stucco duct tape is weather resistant:

- can be used indoors and outdoors
- outstanding UV resistance
- holds up in hot temperatures

TAPE SIZES

The 60-day stucco duct tape is available in the following sizes:

- 2 inches by 60 yards / 48 mm by 55 m

TAPE COLORS

The 60-day stucco duct tape is available in gray.



WHO USES THE TAPE

The tape is most commonly used by:

- stucco contractors
- painting contractors

ECHOtape PART NUMBER

The part number for this tape is CL-W6059.

Applications

- Designed to protect window and door frames in outdoor stucco masking applications
- Designed for single family, multi-family and commercial construction projects
- Used in one coat stucco processes

Features & Benefits

- Outstanding UV resistance lasting up to 7 days
- Residue free when removed within 7 days
- Excellent holding power and durability
- Conforms to uneven surfaces
- Holds strong which prevents lifting
- Can be torn by hand leaving a clean and straight edge
- Does not curl or splinter making it easy to apply
- Trusted by professional contractors nationwide

Technical Data

SIZES	1.89 in x 60 yd 48 mm x 55 m
CARRIER	Waterproof Polyethylene Coated Cloth
ADHESIVE	Rubber
TOTAL THICKNESS	9.5 mils
TENSILE	25 lbs/in
ADHESION	22 oz/in
COLOR	Blue

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or

otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability

Premium Grade 60-Day Stucco Duct Tape [Red]

CL-W6089 is a premium grade, red cloth duct tape that's designed to protect and mask windows, profiles, and door frames during outdoor stucco applications. Strong and durable, this 60-day stucco duct tape has a high-tack rubber adhesive that holds up well in hot temperatures, high winds, and moist conditions. Easy to apply, the tape leaves limited residue if removed within 60 days.

APPLICATIONS FOR THE TAPE

The most common applications for the 60-day stucco duct tape



include:

- protects vinyl windows, profiles, and doorframes during outdoor stucco applications
- used in 2-step and 3-step stucco processes (scratch, brown, and finish) where the protective barrier is left in place throughout the entire stucco application

FEATURES OF THE TAPE

Features of the 60-day stucco duct tape include:

- superior holding power in hot temperatures, high winds, and moist conditions
- limited residue when removed within 60 days of application
- conforms to uneven surfaces
- can tear the tape by hand (leaving a clean, straight edge)
- easy to apply (doesn't curl or splinter)

TAPE ADHESIVE

The tape has a high-performance rubber adhesive.

WEATHER RESISTANCE

The 60-day stucco duct tape is weather resistant:

- holds well in high temperatures
- holds well in high winds
- holds well in moist conditions
- outstanding UV resistance (lasting up to 60 days)

TAPE SIZES



The 60-day stucco duct tape is available in the following sizes:

- 2 inches by 60 yards / 48 mm by 55 m

TAPE COLORS

The 60-day stucco duct tape is available in red.

WHO USES THE TAPE

The tape is most commonly used by:

- stucco contractors
- painting contractors

ECHOtape PART NUMBER

The part number for this tape is CL-W6089.

Applications

- Designed to protect window and door frames in outdoor stucco masking applications
- Designed for single family, multi-family and commercial construction projects
- Used in one coat stucco processes

Features & Benefits

- Outstanding UV resistance lasting up to 7 days
- Residue free when removed within 7 days
- Excellent holding power and durability
- Conforms to uneven surfaces

- Holds strong which prevents lifting
- Can be torn by hand leaving a clean and straight edge
- Does not curl or splinter making it easy to apply
- Trusted by professional contractors nationwide

Technical Data

SIZES	1.89 in x 60 yd 48 mm x 55 m
CARRIER	Waterproof Polyethylene Coated Cloth
ADHESIVE	Rubber
TOTAL THICKNESS	9.5 mils
TENSILE	25 lbs/in
ADHESION	22 oz/in
COLOR	Blue

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The

values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability

Utility Grade General Purpose Paper Masking Tape

MK-K5417 is a utility grade masking tape (5.5 mils thick) that can be used for general purpose adhesion on a variety of substrates, materials, and surfaces. Easy to use and quick to stick, the masking tape is resistant to water and oil.



APPLICATIONS FOR THE TAPE

The most common applications for the masking tape include:

- packaging
- bundling
- holding
- splicing
- tabbing
- general purposes

FEATURES OF THE TAPE

Features of the utility-grade masking tape include:

- good adhesion on a variety of surfaces and materials
- flexible and easy to use
- excellent quick stick
- resistant to water and oil

TAPE ADHESIVE

The tape has a blended, rubber-based adhesive.

TAPE SIZES

The utility-grade masking tape is available in the following sizes:

- 1 inch by 60 yards / 24 mm x 55 m
- 2 inches by 60 yards / 48 mm x 55 m

TAPE COLORS

The utility-grade masking tape is available in tan.

WHO USES THE TAPE

The tape is most commonly used by:

- general contractors
- small businesses
- painters
- decorators

ECHOtape PART NUMBER

The part number for this tape is MK-K5417

Applications

- Designed to protect window and door frames in outdoor stucco masking applications
- Designed for single family, multi-family and commercial construction projects
- Used in one coat stucco processes

Features & Benefits

- Outstanding UV resistance lasting up to 7 days
- Residue free when removed within 7 days
- Excellent holding power and durability
- Conforms to uneven surfaces
- Holds strong which prevents lifting
- Can be torn by hand leaving a clean and straight edge
- Does not curl or splinter making it easy to apply
- Trusted by professional contractors nationwide

Technical Data

SIZES	1.89 in x 60 yd 48 mm x 55 m
CARRIER	Waterproof Polyethylene Coated Cloth
ADHESIVE	Rubber
TOTAL THICKNESS	9.5 mils
TENSILE	25 lbs/in
ADHESION	22 oz/in
COLOR	Blue

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or

otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability

Blue Painter's Paper Indoor/Outdoor Masking Tape (14 Day)

MK-K5497 is a high-performance blue painter's tape (5.1 mils thick) that can be used for most types of masking applications. Designed for indoor use and outdoor use, the blue painter's tape removes cleanly from most surfaces for up to 14 days. And in that time, the painter's tape won't dry out or lose its holding power.



APPLICATIONS FOR THE TAPE

The most common applications for the blue painter's tape include:

- masking for painting
- masking of drywall
- masking of wood trim
- masking of windows
- masking of hardwood floors and other flooring surfaces

FEATURES OF THE TAPE

Features of the blue painter's tape include:

- removes cleanly from most surfaces
- suitable for indoor use and outdoor use
- outdoor UV protection up to 14 days

TAPE ADHESIVE

The tape has a natural rubber (resin) adhesive.

WEATHER RESISTANCE

The blue painter's tape is suitable for outdoor use and has outdoor UV protection for up to 14 days.

TAPE SIZES

The blue painter's tape is available in the following size:

- 2 inches by 60 yards / 48 mm x 55 m



TAPE COLORS

The painter's tape is available in blue.

WHO USES THE TAPE

The tape is most commonly used by:

- painters
- general contractors

ECHOtape PART NUMBER

The part number for this tape is MK-K5497.

Applications

- Designed to protect window and door frames in outdoor stucco masking applications
- Designed for single family, multi-family and commercial construction projects
- Used in one coat stucco processes

Features & Benefits

- Outstanding UV resistance lasting up to 7 days
- Residue free when removed within 7 days
- Excellent holding power and durability
- Conforms to uneven surfaces
- Holds strong which prevents lifting
- Can be torn by hand leaving a clean and straight edge
- Does not curl or splinter making it easy to apply

- Trusted by professional contractors nationwide

Technical Data

SIZES	1.89 in x 60 yd 48 mm x 55 m
CARRIER	Waterproof Polyethylene Coated Cloth
ADHESIVE	Rubber
TOTAL THICKNESS	9.5 mils
TENSILE	25 lbs/in
ADHESION	22 oz/in
COLOR	Blue

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many

factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability

Multi Purpose No Residue Polyethylene Vinyl Tape

VI-N6120 is one of our most popular adhesive tapes, thanks to its versatility and consistent performance! Used extensively by stucco contractors and mold and asbestos abatement contractors, this vinyl tape is made from an extra-strength polyethylene film, and it's coated with a high-tack synthetic rubber adhesive. The vinyl tape is available in several colors, and when it's removed within 7-10 days, it leaves little or no residue on most surfaces.



APPLICATIONS FOR THE TAPE

The most common applications for the polyethylene vinyl tape include:

- temporary holding
- general repairs
- masking windows and doors in stucco applications
- taping in containment rooms and clean rooms
- taping polyethylene films for mold and asbestos remediation and demolition
- seaming polyethylene film for underslab vapor barriers
- splicing polyethylene films during manufacturing
- color-coding and floor marking (for events, exhibits, and tradeshow)

FEATURES OF THE TAPE

Features of the polyethylene vinyl tape include:

- bonds well and conforms well to a variety of surfaces
- tough and flexible
- superior low temperature bonding
- works well over a wide temperature range
- waterproof backing material
- maintains a watertight seal in all weather conditions (if applied properly)
- on most surfaces, leaves little to no residue if the tape is removed within 7-10 days
- hangs and tears straight
- is easy to unwind
- holds strong, which prevents lifting



- can be torn by hand
- doesn't curl or splinter (which makes it easy to apply)

TAPE ADHESIVE

The tape has a synthetic rubber adhesive.

WEATHER RESISTANCE

The polyethylene vinyl tape is weather resistant:

- bonds well in low temperatures
- bonds well over a wide temperature range
- maintains a watertight seal in all weather conditions (if applied properly)

TAPE SIZES

The polyethylene vinyl tape is available in the following sizes:

- 2 inches by 60 yards / 48 mm x 55 m
- 3 inches by 60 yards / 72 mm x 55 m

TAPE COLORS

The polyethylene vinyl tape is available in black, blue, red, white, and transparent.

WHO USES THE TAPE

The tape is most commonly used by:

- stucco contractors
- abatement companies

- asbestos removal companies
- mold remediation companies
- flooring contractors
- general contractors
- builders
- event, exhibit, and tradeshow contractors
- manufacturers

ECHOtape PART NUMBER

The part number for this tape is VI-N6120.

Applications

- Designed to protect window and door frames in outdoor stucco masking applications
- Designed for single family, multi-family and commercial construction projects
- Used in one coat stucco processes

Features & Benefits

- Outstanding UV resistance lasting up to 7 days
- Residue free when removed within 7 days
- Excellent holding power and durability
- Conforms to uneven surfaces
- Holds strong which prevents lifting
- Can be torn by hand leaving a clean and straight edge
- Does not curl or splinter making it easy to apply
- Trusted by professional contractors nationwide

Technical Data

SIZES	1.89 in x 60 yd 48 mm x 55 m
CARRIER	Waterproof Polyethylene Coated Cloth
ADHESIVE	Rubber
TOTAL THICKNESS	9.5 mils
TENSILE	25 lbs/in
ADHESION	22 oz/in
COLOR	Blue

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or

otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability

Resistant 30-Day Stucco Masking Tape

VI-N6149 is a UV resistant, red stucco tape. Trusted by professional stucco contractors, this polyethylene stucco tape is used to protect and mask windows, door frames, and profiles during outdoor stucco applications. The stucco tape has a high-performance rubber adhesive that's designed to bond well to most surfaces and provide a watertight seal in a range of weather conditions. The stucco tape can be cleanly removed within 30 days, leaving no residue.

APPLICATIONS FOR THE TAPE

The most common applications for the polyethylene red stucco tape include:

- protecting and masking windows during outdoor stucco applications
- protecting and masking door frames during outdoor stucco applications
- protecting and masking profiles during outdoor stucco applications

FEATURES OF THE TAPE

Features of the polyethylene red stucco tape include:

- excellent holding power and durability
- bonds well to most surfaces
- conforms well to uneven surfaces
- clean removal within 30 days (leaving no residue)
- UV resistant
- provides a watertight seal in a variety of weather conditions
- hand tearable, leaving a clean edge

TAPE ADHESIVE

The tape has a high-performance rubber adhesive.

WEATHER RESISTANCE

The polyethylene red stucco tape is weather resistant:

- UV resistant



- maintains a watertight seal in all weather conditions (if applied properly)

TAPE SIZES

The polyethylene red stucco tape is available in the following size:

- 2 inches by 60 yards / 48 mm x 55 m

TAPE COLORS

The polyethylene stucco tape is available in red.

WHO USES THE TAPE

The tape is most commonly used by:

- stucco contractors
- general contractors
- builders

ECHOtape PART NUMBER

The part number for this tape is VI-N6149.

Applications

- Designed to protect window and door frames in outdoor stucco masking applications
- Designed for single family, multi-family and commercial construction projects
- Used in one coat stucco processes

Features & Benefits

- Outstanding UV resistance lasting up to 7 days
- Residue free when removed within 7 days
- Excellent holding power and durability
- Conforms to uneven surfaces
- Holds strong which prevents lifting
- Can be torn by hand leaving a clean and straight edge
- Does not curl or splinter making it easy to apply
- Trusted by professional contractors nationwide

Technical Data

SIZES	1.89 in x 60 yd 48 mm x 55 m
CARRIER	Waterproof Polyethylene Coated Cloth
ADHESIVE	Rubber
TOTAL THICKNESS	9.5 mils
TENSILE	25 lbs/in
ADHESION	22 oz/in
COLOR	Blue

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best

when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability