Premium Grade 60-Day Stucco Duct Tape [Red]

CL-W6089 is a premium grade, red cloth duct tape that’s designed to protect and mask windows, profiles, and door frames during outdoor stucco applications. Strong and durable, this 60-day stucco duct tape has a high-tack rubber adhesive that holds up well in hot temperatures, high winds, and moist conditions. Easy to apply, the tape leaves limited residue if removed within 60 days.

APPLICATIONS FOR THE TAPE

The most common applications for the 60-day stucco duct tape include:

- protects vinyl windows, profiles, and doorframes during outdoor stucco applications
- used in 2-step and 3-step stucco processes (scratch, brown, and finish) where the protective barrier is left in place throughout the entire stucco application

FEATURES OF THE TAPE

Features of the 60-day stucco duct tape include:

- superior holding power in hot temperatures, high winds, and moist conditions
- limited residue when removed within 60 days of application
- conforms to uneven surfaces

- can tear the tape by hand (leaving a clean, straight edge)
- easy to apply (doesn’t curl or splinter)

TAPE ADHESIVE
The tape has a high-performance rubber adhesive.

WEATHER RESISTANCE
The 60-day stucco duct tape is weather resistant:

- holds well in high temperatures
- holds well in high winds
- holds well in moist conditions
- outstanding UV resistance (lasting up to 60 days)

TAPE SIZES
The 60-day stucco duct tape is available in the following sizes:

- 2 inches by 60 yards / 48 mm by 55 m

TAPE COLORS
The 60-day stucco duct tape is available in red.

WHO USES THE TAPE
The tape is most commonly used by:

- stucco contractors
- painting contractors

ECHOtape PART NUMBER
The part number for this tape is CL-W6089.

Applications

- Designed to protect window and door frames in outdoor stucco masking applications where a maximum adhesion is required
- Designed for single family, multi–family and commercial construction projects
- Used in two- and three-step stucco processes (scratch, brown and finish) where the protective barrier is left in place throughout the entire application

Features & Benefits

- Excellent holding power and durability in high winds and moisture conditions
- Outstanding UV resistance lasting up to 60 days
- Residue free under extreme summerlike weather conditions
- Conforms to uneven surfaces
- Holds strong which prevents lifting
- Hand tearable , leaving a clean and straight edge
- Does not curl or splinter making it easy to apply

Technical Data

SIZES	1.89 in x 60 yd | 48mm x 55m
CARRIER	Waterproof Polyethylene Coated Cloth
ADHESIVE	Rubber
TOTAL THICKNESS	13 mils
TENSILE	25 lbs/in

ADHESION	55 oz/in
COLOR	Red

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to,

contract, negligence, warranty or strict liability.