

All Weather Lamtec WMP-10/PSK Facing Tape

FS-G7735 is an adhesive tape used primarily to seal and seam Lamtec WMP-10/PSK faced insulation that's used in metal buildings. This facing tape is coated with a high-performance, cold weather acrylic adhesive that has a superior quick stick, creates a strong bond, and performs exceptionally well in low temperatures.

APPLICATIONS FOR THE TAPE

The Lamtec WMP-10/PSK facing tape is used to:

- seam and join Lamtec WMP-10/PSK faced insulation
- repair tears on Lamtec WMP-10/PSK faced insulation

FEATURES OF THE TAPE

Features of the Lamtec WMP-10/PSK facing tape include:

- quick to stick
- creates a strong bond
- performs well across a broad range of temperatures (including cold temperatures)
- excellent vapor barrier
- low WVTR (water vapor transmission rate)
- paper liner is easy to remove
- can be cut to specific lengths for use in tight areas

TAPE ADHESIVE

The Lamtec WMP-10/PSK facing tape has a cold-weather, acrylic



adhesive.

WEATHER RESISTANCE

The Lamtec WMP-10/PSK facing tape is weather resistant:

- works well in cold weather – bonds well at low temperatures
- excellent vapor barrier
- low WVTR (water vapor transmission rate)

TAPE SIZES

The Lamtec WMP-10/PSK facing tape is available in the following size:

- 2.75 inches by 50 yards / 72 mm x 46 m

TAPE COLORS

The Lamtec WMP-10/PSK facing tape is available in black and white.

WHO USES THE TAPE

The tape is most commonly used by:

- metal building insulation contractors

ECHOtape PART NUMBER

The part number for this tape is FS-G7735.

Note that Lamtec and WMP are registered trademarks of Lamtec Corporation.



Applications

- Use to seam and join Lamtec WMP-10/PSK faced insulation
- Use to repair tears on Lamtec WMP-10/PSK faced insulation

Features & Benefits

- An initial quick stick helps speed up application
- Creates a strong bond
- Easy to remove paper liner
- Excellent vapor barrier & low WVTR (Water Vapor Transmission Rate)
- Outstanding performance across a broad range of temperatures
- Excellent low temperature bonding

Technical Data

SIZES	2.83 in x 50 yd 72mm x 45,72m
CARRIER	Poly film/Scrim/Kraft
ADHESIVE	Acrylic
RELEASE LINER	Siliconized Paper
TOTAL THICKNESS	8.5 mils
TENSILE	42 lbs/in
ADHESION	40 oz/in
APPLICATION TEMPERATURE	-4°F to 104°F (-20°C to 48°C)
SERVICE TEMPERATURE	-40°F to 176°F (-40°C to 80°C)



ELONGATION	1%
COLOR	White, Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.