



---

# Strong Double Sided Tape For Temporary Hold

DC-K048A is the right choice when you need a tape that is extremely aggressive and strong but you only need to mount or bond something temporarily. It sticks very well to smooth surfaces such as steel and paper but can also adhere to more porous or textured surfaces such as wood or fabric. Designed to work at room temperature, it can also perform for medium heat applications.

## Applications

- Use to temporarily hold down steel or metal components in manufacturing or printing applications
- Use to temporarily hold down wooden components in woodworking applications
- Use to mount posters or photographs on walls
- Use to temporarily hold small carpets in place

## Features & Benefits

- Hand tearable making it very easy to apply and use
- Excellent holding power from the onset helps speed up application
- Easy to remove paper liner
- Removes cleanly from most hard and smooth surfaces



---

## Technical Data

<b>SIZES</b>	.94 in x 36 yd   24 mm x 33m
<b>CARRIER</b>	Crepe Paper
<b>ADHESIVE</b>	Rubber
<b>TOTAL THICKNESS</b>	6 mils
<b>RELEASE LINER</b>	Crepe Paper
<b>TENSILE</b>	23 lbs/in
<b>ADHESION</b>	47 oz/in
<b>APPLICATION TEMPERATURE</b>	50°F to 110°F (10°C to 43°C)
<b>SERVICE TEMPERATURE</b>	32°F to 180°F (0°C to 82°C)
<b>ELONGATION</b>	8.5%
<b>COLOR</b>	Beige

## Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are



---

warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

---

## **Clear Double Sided Tape for Permanent Mounting and Bonding**

DC-M012P is the right choice when you need a tape that is extremely aggressive and strong for permanent mounting and bonding purposes. It sticks very well to smooth surfaces such as steel and plastic. Designed to work at room temperature, it can also perform for medium heat applications. It is engineered with an acrylic adhesive for maximum performance and durability both indoors and outdoors.



---

## Applications

- Use to temporarily hold down steel or metal components in manufacturing or printing applications
- Use to temporarily hold down wooden components in woodworking applications
- Use to mount posters or photographs on walls
- Use to temporarily hold small carpets in place

## Features & Benefits

- Hand tearable making it very easy to apply and use
- Excellent holding power from the onset helps speed up application
- Easy to remove paper liner
- Removes cleanly from most hard and smooth surfaces

## Technical Data

<b>SIZES</b>	.94 in x 36 yd   24 mm x 33m
<b>CARRIER</b>	Crepe Paper
<b>ADHESIVE</b>	Rubber
<b>TOTAL THICKNESS</b>	6 mils
<b>RELEASE LINER</b>	Crepe Paper
<b>TENSILE</b>	23 lbs/in
<b>ADHESION</b>	47 oz/in
<b>APPLICATION TEMPERATURE</b>	50°F to 110°F (10°C to 43°C)
<b>SERVICE TEMPERATURE</b>	32°F to 180°F (0°C to 82°C)
<b>ELONGATION</b>	8.5%



---

<b>COLOR</b>	Beige
--------------	-------

## **Storage & Usage Conditions**

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.