

Industrial Strength Utility Grade Duct Tape

CL-W6064 is an industrial-strength duct tape that's no ordinary duct tape! Made with an advanced adhesive technology, the duct tape provides superior holding power, yet is easy to tear and apply. This heavy-duty duct tape sticks well to smooth and rough surfaces, and it can be used for holding, seaming, repairing, and bundling.

Applications For the Tape

The most common applications for the industrial duct tape include:

- temporary holding and bonding
- general purpose use and repair
- hanging and patching polyethylene sheeting
- duct work
- bundling
- color coding
- applications in manufacturing and industrial environments

Features Of the Tape

Features of the industrial duct tape include:

- aggressive adhesive
- superior holding power
- sticks well to a wide variety of smooth and rough



surfaces

- conforms to uneven surfaces
- can tear the tape by hand (leaving a clean, straight edge)
- unwinds smoothly (making it easier to apply)
- tape lays flat (no twisting or curling)

Tape Adhesive

The tape has a high-performance rubber adhesive.

Tape Sizes

The industrial duct tape is available in the following size:

- 2 inches by 60 yards / 48 mm by 55 m

Tape Colors

The industrial duct tape is available in silver, black, yellow, red, blue, green, and white.

Who Uses the Tape

The tape is most commonly used by:

- construction professionals
- HVAC contractors
- contractors

ECHOtape Part Number

The part number for this tape is CL-W6064.



Applications

- General purpose construction use and repair
- Patching and seaming a wide variety of materials
- Temporary holding and bonding
- Hanging and patching polyethylene sheeting
- Sealing polyethylene waste disposal bags
- Duct work and contractor uses
- Multiple applications in manufacturing & Industrial environments
- Bundling and color coding

Features & Benefits

- Aggressive adhesive provides superior holding power
- Excellent quick stick to a wide variety of smooth and rough surfaces
- Flexible enough to adhere to uneven surfaces
- Smooth unwind makes it easier to apply in the field
- Fine mesh easy-tear backing produces a clean crisp edge when torn by hand
- Tape lays flat so there is no twisting and curling

Technical Data

SIZES	24mm – 96mm x 55m
CARRIER	Polyethylene Coated Cloth
ADHESIVE	Synthetic Rubber
TOTAL THICKNESS	7 mils

TENSILE	17 lbs/in
ADHESION	65 oz/in
ELONGATION	12%
COLORS	Silver, Black, Yellow, Red, Blue, Green, White

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct,

indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

All Weather FSK (Foil/Scrim/Kraft) Insulation Facing Tape

FS-K7751 is a high-performance, all weather tape that's primarily used to seal foil-faced insulation (such as FSK-faced fiberglass duct board and blanket systems). Coated with a flame-retardant, cold-weather acrylic adhesive, this insulation facing tape provides a strong and secure bond on a variety of surfaces and textures.

APPLICATIONS FOR THE TAPE

The most common applications for the FSK insulation facing tape include:

- sealing and seaming FSK (Foil-Scrim-Kraft) laminated board
- sealing and seaming FSK (Foil-Scrim-Kraft) jacketing insulation
- repairing tears in foil faced insulation



FEATURES OF THE TAPE

Features of the FSK insulation facing tape include:

- initial quick stick
- creates a strong bond to a variety of surfaces and textures
- paper liner is easy to remove and protects the adhesive from contaminants when you need to cut the tape to specific lengths
- designed for tear-resistant sealing
- mold resistant
- coated with a flame-retardant acrylic adhesive
- an epoxy resin coating on the insulation tape helps protect the surface from corrosion caused by moisture.
- UL 723 classified

TAPE ADHESIVE

The tape has an acrylic adhesive.

WEATHER RESISTANCE

The all weather insulation facing tape works well in a wide range of temperatures (can be applied in -4°F to 104°F weather).

TAPE SIZES

The FSK insulation facing tape is available in the following sizes:

- 2.75 inches by 50 yards / 72 mm x 46 m
- 3.75 inches by 50 yards / 96 mm x 46 m



TAPE COLORS

The all weather FSK insulation facing tape is available in silver.

WHO USES THE TAPE

The tape is most commonly used by:

- mechanical insulation contractors
- HVAC contractors

ECHOtape PART NUMBER

The part number for this tape is FS-K7751.

Applications

- General purpose construction use and repair
- Patching and seaming a wide variety of materials
- Temporary holding and bonding
- Hanging and patching polyethylene sheeting
- Sealing polyethylene waste disposal bags
- Duct work and contractor uses
- Multiple applications in manufacturing & Industrial environments
- Bundling and color coding

Features & Benefits

- Aggressive adhesive provides superior holding power
- Excellent quick stick to a wide variety of smooth and

rough surfaces

- Flexible enough to adhere to uneven surfaces
- Smooth unwind makes it easier to apply in the field
- Fine mesh easy-tear backing produces a clean crisp edge when torn by hand
- Tape lays flat so there is no twisting and curling

Technical Data

SIZES	24mm – 96mm x 55m
CARRIER	Polyethylene Coated Cloth
ADHESIVE	Synthetic Rubber
TOTAL THICKNESS	7 mils
TENSILE	17 lbs/in
ADHESION	65 oz/in
ELONGATION	12%
COLORS	Silver, Black, Yellow, Red, Blue, Green, White

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—



The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

All Weather Aluminum Foil Tape

MT-A7772 is a high-strength, aluminum foil tape that's primarily used for vapor sealing fiberglass duct boards and FSK systems. The aluminum foil tape provides an excellent vapor seal and can be used for sealing and patching. The tape has a flame-retardant solvent acrylic adhesive and works well

indoors and outdoors.

APPLICATIONS FOR THE TAPE

The most common applications for the aluminum foil tape include:

- sealing joints and seams of foil-faced insulation materials (UL 723 classified, CAN/ULC-S102)
- seaming foil faced insulation
- seaming FSK systems (Foil Scrim Kraft systems)

FEATURES OF THE TAPE

Features of the aluminum foil tape include:

- initial quick stick
- outstanding sealing and patching performance
- maximum conformability
- low MVTR (Moisture Vapor Transmission Rate)
- mold resistant
- paper liner is easy to remove
- coated with a flame-retardant solvent acrylic adhesive

TAPE ADHESIVE

The tape has an acrylic adhesive.

WEATHER RESISTANCE

The aluminum foil tape is weather resistant:

- can be used indoors and outdoors
- superior stick at normal operating temperatures



- great performance at low temperatures

TAPE SIZES

The aluminum foil tape is available in the following sizes:

- 2 inches by 50 yards / 48 mm x 46 m
- 3 inches by 50 yards / 72 mm x 46 m

TAPE COLORS

The aluminum foil tape is available in silver.

WHO USES THE TAPE

The tape is most commonly used by:

- insulation contractors
- HVAC contractors
- general contractors
- appliance contractors
- automotive shops

ECHOtape PART NUMBER

The part number for this tape is MT-A7772.

Applications

- General purpose construction use and repair
- Patching and seaming a wide variety of materials
- Temporary holding and bonding
- Hanging and patching polyethylene sheeting
- Sealing polyethylene waste disposal bags

- Duct work and contractor uses
- Multiple applications in manufacturing & Industrial environments
- Bundling and color coding

Features & Benefits

- Aggressive adhesive provides superior holding power
- Excellent quick stick to a wide variety of smooth and rough surfaces
- Flexible enough to adhere to uneven surfaces
- Smooth unwind makes it easier to apply in the field
- Fine mesh easy-tear backing produces a clean crisp edge when torn by hand
- Tape lays flat so there is no twisting and curling

Technical Data

SIZES	24mm – 96mm x 55m
CARRIER	Polyethylene Coated Cloth
ADHESIVE	Synthetic Rubber
TOTAL THICKNESS	7 mils
TENSILE	17 lbs/in
ADHESION	65 oz/in
ELONGATION	12%
COLORS	Silver, Black, Yellow, Red, Blue, Green, White

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

All Weather Construction Seaming Tape

PE-M4535 is an all-weather construction seaming tape that's available in three colors. This next-generation seam tape is engineered to adhere to a wide range of building materials and surfaces. Formulated with a proprietary cold-weather adhesive and an advanced polyester backing, the seam tape is extremely strong and easy to apply. You can use this seam tape on just about anything, including: house wrap, sheathing, vapor barriers, underlayments, and exterior and rigid insulation.

APPLICATIONS FOR THE TAPE

The most common applications for the seam tape include:

- seaming the building envelope
- seaming house wrap
- seaming insulation (including polyisocyanurate insulation and reflective insulation)
- seaming exterior sheathing
- seaming vapor barriers (including polyethylene films)
- seaming flooring underlayments
- seaming roofing underlayments

FEATURES OF THE TAPE

Features of the seam tape include:

- strong, with durable holding power
- conforms well to a variety of irregular surfaces
- instant tack, on a wide range of surfaces and materials
- tack strengthens over time
- made from an advanced polyester film (PET)
- water resistant and moisture resistant
- excellent cold weather adhesion
- UV resistant (up to 90 days)
- can tear the tape by hand
- colors allow for easy inspection

TAPE ADHESIVE

The tape has an acrylic adhesive.

WEATHER RESISTANCE

The seam tape is weather resistant:

- excellent cold weather adhesion (to -4° F)
- minimum 90 day UV resistance
- water resistant and moisture resistant

TAPE SIZES

The seam tape is available in the following size:

- 2 inches by 55 yards / 48 mm x 50 m

TAPE COLORS

The seam tape is available in the following colors:

- red seam tape

- silver seam tape
- white seam tape

WHO USES THE TAPE

The tape is most commonly used by:

- general contractors
- insulation companies

ECHOtape PART NUMBER

The part number for this tape is PE-M4535.

Applications

- General purpose construction use and repair
- Patching and seaming a wide variety of materials
- Temporary holding and bonding
- Hanging and patching polyethylene sheeting
- Sealing polyethylene waste disposal bags
- Duct work and contractor uses
- Multiple applications in manufacturing & Industrial environments
- Bundling and color coding

Features & Benefits

- Aggressive adhesive provides superior holding power
- Excellent quick stick to a wide variety of smooth and rough surfaces

- Flexible enough to adhere to uneven surfaces
- Smooth unwind makes it easier to apply in the field
- Fine mesh easy-tear backing produces a clean crisp edge when torn by hand
- Tape lays flat so there is no twisting and curling

Technical Data

SIZES	24mm – 96mm x 55m
CARRIER	Polyethylene Coated Cloth
ADHESIVE	Synthetic Rubber
TOTAL THICKNESS	7 mils
TENSILE	17 lbs/in
ADHESION	65 oz/in
ELONGATION	12%
COLORS	Silver, Black, Yellow, Red, Blue, Green, White

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been

established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.