

Resistant 30-Day Stucco Masking Tape

VI-N6149 is a UV resistant, red stucco tape. Trusted by professional stucco contractors, this polyethylene stucco tape is used to protect and mask windows, door frames, and profiles during outdoor stucco applications. The stucco tape has a high-performance rubber adhesive that's designed to bond well to most surfaces and provide a watertight seal in a range of weather conditions. The stucco tape can be cleanly removed within 30 days, leaving no residue.

APPLICATIONS FOR THE TAPE

The most common applications for the polyethylene red stucco tape include:

- protecting and masking windows during outdoor stucco applications
- protecting and masking door frames during outdoor stucco applications
- protecting and masking profiles during outdoor stucco applications

FEATURES OF THE TAPE

Features of the polyethylene red stucco tape include:

- excellent holding power and durability
- bonds well to most surfaces
- conforms well to uneven surfaces



- clean removal within 30 days (leaving no residue)
- UV resistant
- provides a watertight seal in a variety of weather conditions
- hand tearable, leaving a clean edge

TAPE ADHESIVE

The tape has a high-performance rubber adhesive.

WEATHER RESISTANCE

The polyethylene red stucco tape is weather resistant:

- UV resistant
- maintains a watertight seal in all weather conditions (if applied properly)

TAPE SIZES

The polyethylene red stucco tape is available in the following size:

- 2 inches by 60 yards / 48 mm x 55 m

TAPE COLORS

The polyethylene stucco tape is available in red.

WHO USES THE TAPE

The tape is most commonly used by:

- stucco contractors
- general contractors



- builders

ECHOtape PART NUMBER

The part number for this tape is VI-N6149.

Applications

- Designed to protect window and door frames in outdoor stucco masking applications
- Designed for single family, multi-family and commercial construction projects

Features & Benefits

- Excellent holding power and durability
- Outstanding UV resistance lasting up to 30 days
- Residue free when removed within 30 days
- Waterproof
- Hand tearable, leaving a clean edge
- Conforms to uneven surfaces
- Holds strong which prevents lifting
- Trusted by professional contractors nationwide

Technical Data

SIZES	1.89 in x 60 yd 48mm x 55m
CARRIER	Polyethylene Film
ADHESIVE	Rubber
TOTAL THICKNESS	7 mils



TENSILE	22 lbs/in
ADHESION	75 oz/in
ELONGATION	90%
COLOR	Red

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.