

# All Weather Construction Seaming Tape

PE-M4535 is an all-weather construction seaming tape that's available in three colors. This next-generation seam tape is engineered to adhere to a wide range of building materials and surfaces. Formulated with a proprietary cold-weather adhesive and an advanced polyester backing, the seam tape is extremely strong and easy to apply. You can use this seam tape on just about anything, including: house wrap, sheathing, vapor barriers, underlayments, and exterior and rigid insulation.

#### APPLICATIONS FOR THE TAPE

The most common applications for the seam tape include:

- seaming the building envelope
- seaming house wrap
- seaming insulation (including polyisocyanurate insulation and reflective insulation)
- seaming exterior sheathing
- seaming vapor barriers (including polyethylene films)
- seaming flooring underlayments
- seaming roofing underlayments

#### FEATURES OF THE TAPE

Features of the seam tape include:

- strong, with durable holding power
- conforms well to a variety of irregular surfaces



- instant tack, on a wide range of surfaces and materials
- tack strengthens over time
- made from an advanced polyester film (PET)
- water resistant and moisture resistant
- excellent cold weather adhesion
- UV resistant (up to 90 days)
- can tear the tape by hand
- colors allow for easy inspection

### TAPE ADHESIVE

The tape has an acrylic adhesive.

#### **WEATHER RESISTANCE**

The seam tape is weather resistant:

- excellent cold weather adhesion (to -4° F)
- minimum 90 day UV resistance
- water resistant and moisture resistant

#### TAPE SIZES

The seam tape is available in the following size:

 $extbf{-}$  2 inches by 55 yards / 48 mm x 50 m

#### TAPE COLORS

The seam tape is available in the following colors:

- red seam tape
- silver seam tape
- white seam tape



#### WHO USES THE TAPE

The tape is most commonly used by:

- general contractors
- insulation companies

## ECHOtape PART NUMBER

The part number for this tape is PE-M4535.

## **Applications**

- Use to seam the building envelope
- Use to seam house wrap
- Use to seam a variety of insulation including polyisocyanurate and reflective insulation
- Use to seam exterior sheathing
- Use to seam vapor barriers including polyethylene films
- Use to seam a variety of flooring and roofing underlayments

# Features & Benefits

- Tape is hand tearable and easy to use in the field
- Strong and durable holding power
- Excellent cold temperature adhesion to -4°F
- Minimum 90 day UV resistance
- Instant tack on a wide variety of materials that strengthens over time



- Made from an advanced polyester film (PET)
- Water and moisture resistant
- Good conformability to irregular surfaces
- Colors allow for easy inspection

## Technical Data

SIZES	1.89 in x 54.6 yd   48 mm x 50 m
CARRIER	PET Film
ADHESIVE	Acrylic
TOTAL THICKNESS	3.38 mils
TENSILE	20 lbs/in
ADHESION	60 oz/in
APPLICATION TEMPERATURE	-4°F to 105°F (-20°C to 40°C)
SERVICE TEMPERATURE	-40°F to 148°F (-40°C to 120°C)
COLOR	White, silver, red

# **Storage & Usage Conditions**

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

\_

The information cited is in good faith and has been established from sources held to be secure and reliable. The



values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.