

Premium Grade 60 Day Stucco Duct Tape Gray

CL-W6059 is a premium grade, gray 60-day cloth stucco duct tape that was developed for stucco professionals. Designed to protect window frames and door frames during outdoor masking applications, the tape is strong and durable and will peel off without leaving residue.

APPLICATIONS FOR THE TAPE

The most common applications for the 60-day stucco duct tape include:

- protects vinyl windows, profiles, and doorframes during outdoor stucco applications
- recommended by Milgard for use with their vinyl and fiberglass windows
- used in 2-step and 3-step stucco processes (scratch, brown, and finish) where the protective barrier is used throughout the entire stucco application

FEATURES OF THE TAPE

Features of the 60-day stucco duct tape include:

- superior holding power and durability in hot temperatures
- limited residue when removed within 60 days of application



-
- sticks well to smooth surfaces (such as steel and plastic)
 - sticks well to rough or textured surfaces (such as wood)
 - conforms to uneven surfaces
 - can tear the tape by hand (leaving a clean, straight edge)
 - easy to apply (doesn't curl or splinter)

TAPE ADHESIVE

The tape has a high-performance rubber adhesive.

WEATHER RESISTANCE

The 60-day stucco duct tape is weather resistant:

- can be used indoors and outdoors
- outstanding UV resistance
- holds up in hot temperatures

TAPE SIZES

The 60-day stucco duct tape is available in the following sizes:

- 2 inches by 60 yards / 48 mm by 55 m

TAPE COLORS

The 60-day stucco duct tape is available in gray.



WHO USES THE TAPE

The tape is most commonly used by:

- stucco contractors
- painting contractors

ECHOtape PART NUMBER

The part number for this tape is CL-W6059.

Applications

- Designed to protect window and door frames in outdoor stucco masking applications
- Designed for single family, multi-family and commercial construction projects
- Used in two and three-step stucco processes (scratch, brown and finish) where the protective barrier is left in place throughout the entire application

Features and Benefits

- Excellent holding power and durability
- Outstanding UV resistance lasting up to 60 days
- Residue free under extreme summerlike weather conditions
- Conforms to uneven surfaces
- Holds strong which prevents lifting
- Hand tearable , leaving a clean and straight edge
- Does not curl or splinter making it easy to apply



- Recommended by Milgard to mask their vinyl and fiberglass windows

Technical Information

SIZES	1.89 in x 60 yd 48mm x 55m
CARRIER	Waterproof Polyethylene Coated Cloth
ADHESIVE	Rubber
TOTAL THICKNESS	13 mils
TENSILE	25 lbs/in
ADHESION	24 oz/in
COLOR	Gray

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been



established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, 1.800.461.8273 | info@echotape.com | echotape.com concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.