

# Embossed Vinyl Seaming & Patching Tape

VI-V6460 is a single-sided, acrylic adhesive tape that's primarily used to seam and patch white vinyl insulation in metal buildings. The aggressive adhesive on this seaming and patching insulation tape makes it work well in cold and hot temperatures, high humidity, and other environmental conditions. The insulation tape has an easy-to-remove paper liner, and it's easy to cut to specific lengths.

## APPLICATIONS FOR THE TAPE

The most common applications for the seaming and patching insulation tape include:

- seaming of vinyl faced insulation
- patching of vinyl faced insulation

## FEATURES OF THE TAPE

Features of the seaming and patching insulation tape include:

- outstanding performance across a variety of temperature ranges and environmental conditions
- easy to remove paper liner
- paper liner protects the adhesive from contaminants when you're cutting the tape to specific lengths
- sticks quickly
- conforms well to a variety of surfaces



## **TAPE ADHESIVE**

The tape has an acrylic adhesive.

## **WEATHER RESISTANCE**

The seaming and patching insulation tape:

- works well across a wide variety of temperature ranges
- works well in high heat and high humidity conditions
- bonds well in low temperatures

## **TAPE COLORS**

The seaming and patching insulation tape is available in white.

## **WHO USES THE TAPE**

The tape is most commonly used by:

- insulation contractors
- metal building contractors
- HVAC contractors
- roofing contractors
- maintenance workers
- general contractors
- builders

## **ECHOtape PART NUMBER**

The part number for this tape is VI-V6460.

## Applications

- Use for seaming and patching of vinyl faced insulation

## Features & Benefits

- Outstanding performance across a wide variety of environmental conditions and temperature ranges
- Excellent low temperature bonding
- Works well in high heat and humidity conditions
- Easy to remove paper liner

## Technical Data

<b>SIZES</b>	2.83 in x 50 yd   72 mm x 45,72 m
<b>CARRIER</b>	Embossed Vinyl Vapor Retarder Film
<b>ADHESIVE</b>	Acrylic
<b>RELEASE LINER</b>	Siliconized Paper
<b>TOTAL THICKNESS</b>	4.6 mils
<b>TENSILE</b>	10 lb/in
<b>ADHESION</b>	60 oz/in
<b>ELONGATION</b>	70%
<b>COLOR</b>	White

## Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape



---

should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.