

# All Weather Lamtec WMP-50 Metal Facing Tape

FS-G7736 is an adhesive tape used primarily to seal and seam Lamtec WMP-50 faced insulation that's used in metal buildings. This metal facing tape is coated with a high-performance, cold weather acrylic adhesive that offers a superior quick stick. Able to create a strong bond, the tape performs very well at low temperatures.

## APPLICATIONS FOR THE TAPE

The Lamtec WMP-50 metal facing tape is used to:

- seam and join Lamtec WMP-50 faced insulation
- repair tears on Lamtec WMP-50 faced insulation

## FEATURES OF THE TAPE

Features of the Lamtec WMP-50 metal facing tape include:

- quick to stick
- creates a strong bond
- performs well across a broad range of temperatures (including cold temperatures)
- excellent vapor barrier
- low WVTR (water vapor transmission rate)
- paper liner is easy to remove
- can be cut to specific lengths for use in tight areas

## TAPE ADHESIVE

The Lamtec WMP-50 metal facing tape has a cold-weather,



acrylic adhesive.

### **WEATHER RESISTANCE**

The Lamtec WMP-50 metal facing tape is weather resistant:

- works well in cold weather – bonds well at low temperatures
- excellent vapor barrier
- low WVTR (water vapor transmission rate)

### **TAPE SIZES**

The Lamtec WMP-50 metal facing tape is available in the following size:

- 2.75 inches by 50 yards / 72 mm x 46 m

### **TAPE COLORS**

The Lamtec WMP-50 metal facing tape is available in white.

### **WHO USES THE TAPE**

The tape is most commonly used by:

- metal building insulation contractors

### **ECHOtape PART NUMBER**

The part number for this tape is FS-G7736.

Note that Lamtec and WMP are registered trademarks of Lamtec Corporation.

### **Applications**

- Use to seam and join Lamtec® WMP-50 faced insulation



- Use to repair tears on Lamtec® WMP-50 faced insulation

## Features & Benefits

- An initial quick stick helps speed up application
- Creates a strong bond
- Easy to remove paper liner
- Excellent vapor barrier & low WVTR (Water Vapor Transmission Rate)
- Outstanding performance across a broad range of temperatures
- Excellent low temperature bonding

## Technical Data

<b>SIZES</b>	2.83 in x 50 yd   72 mm x 45,72 m
<b>CARRIER</b>	Poly film/Scrim/Kraft
<b>ADHESIVE</b>	Acrylic
<b>RELEASE LINER</b>	Siliconized Paper
<b>TOTAL THICKNESS</b>	8.5 mils
<b>TENSILE</b>	42 lbs/in
<b>ADHESION</b>	40.0 oz/in
<b>APPLICATION TEMPERATURE</b>	-4°F to 104°F (-20°C to 48°C)
<b>SERVICE TEMPERATURE</b>	-40°F to 176°F (-40°C to 80°C)
<b>ELONGATION</b>	1%
<b>COLOR</b>	White



---

## **Storage & Usage Conditions**

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.