

White Double Sided Tape for Permanent Mounting & Bonding

DC-U032A is an extremely aggressive and strong double-sided mounting tape that is designed for permanent bonding and will stick to just about any surface.

APPLICATIONS FOR THE TAPE

The most common applications for the permanent, double-sided mounting tape include:

- permanent bonding of metal, plastic, rubber, plexiglass, and wood
- mounting small to medium, lightweight indoor and outdoor signs
- mounting name plates
- mounting decorative trim
- bonding applications where other tapes might not adhere properly

FEATURES OF THE TAPE

Features of the permanent, double-sided mounting tape include:

- superior holding power (from the onset)
- sticks well to smooth surfaces (such as steel and plastic)
- adheres to rough and textured surfaces (such as wood)
- conforms to most surfaces
- easy to apply (the tape can be easily removed from its

liner)

- designed to work at room temperature, the tape can also perform for medium heat applications

TAPE ADHESIVE

The tape has an acrylic adhesive.

WEATHER RESISTANCE

The permanent, double-sided mounting tape is weather resistant:

- can be used indoors and outdoors
- resistant to extreme weather and other environmental conditions

TAPE SIZES

The permanent, double-sided mounting tape is available in the following sizes:

- 1/2 inch by 54.6 yards / 12 mm by 50 m
- 3/4 inch by 54.6 yards / 18 mm by 50 m
- 1 inch by 54.6 yards / 24 mm by 50 m
- 2 inches by 54.6 yards / 48 mm by 50 m

TAPE COLORS

The permanent, double-sided mounting tape is available in white.

WHO USES THE TAPE

The tape is most commonly used by:

- construction professionals
- flooring contractors
- insulation contractors
- handymen
- sign makers
- interior decorators and designers

ECHOtape PART NUMBER

The part number for this tape is DC-U032A.

Applications

- Use for permanently bonding metal, plastic, rubber, plexiglass and wood
- Use for mounting small to medium lightweight indoor and outdoor signs
- Use for mounting name plates & decorative trims
- Use for difficult bonding applications where other tapes may not adhere properly

Features & Benefits

- Excellent holding power from the onset for most surfaces
- Easy to remove paper liner making it easy to apply and use
- Easily conforms to most surfaces
- Offers great resistance to extreme weather and environmental conditions



Technical Data

SIZES	.47 in x 54.6 yd 12mm x 50m .71 in x 54.6 yd / 18mm x 50m .94 in x 54.6 yd / 24mm x 50m 1.89 in x 54.6 yd / 48mm x 50m
CARRIER	PVC
ADHESIVE	Acrylic
RELEASE LINER	Glassine Paper
TOTAL THICKNESS	9.5 mils
ADHESION	80 oz/in
APPLICATION TEMPERATURE	68°F to 95°F (20°C to 35°C)
SERVICE TEMPERATURE	32°F to 176°F (0°C to 80°C)
COLOR	White

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may

vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.