

Blue Painter's Paper Indoor/Outdoor Masking Tape (14 Day)

MK-K5497 is a high-performance blue painter's tape (5.1 mils thick) that can be used for most types of masking applications. Designed for indoor use and outdoor use, the blue painter's tape removes cleanly from most surfaces for up to 14 days. And in that time, the painter's tape won't dry out or lose its holding power.

APPLICATIONS FOR THE TAPE

The most common applications for the blue painter's tape include:

- masking for painting
- masking of drywall
- masking of wood trim
- masking of windows
- masking of hardwood floors and other flooring surfaces

FEATURES OF THE TAPE

Features of the blue painter's tape include:

- removes cleanly from most surfaces
- suitable for indoor use and outdoor use
- outdoor UV protection up to 14 days



TAPE ADHESIVE

The tape has a natural rubber (resin) adhesive.

WEATHER RESISTANCE

The blue painter's tape is suitable for outdoor use and has outdoor UV protection for up to 14 days.

TAPE SIZES

The blue painter's tape is available in the following size:

- 2 inches by 60 yards / 48 mm x 55 m

TAPE COLORS

The painter's tape is available in blue.

WHO USES THE TAPE

The tape is most commonly used by:

- painters
- general contractors

ECHOtape PART NUMBER

The part number for this tape is MK-K5497.

Applications

- Masking of drywall, glass, wood trim, hardwood floors and other surfaces
- Masking of windows prior to painting
- Other industrial, construction, and do-it-yourself

projects

Features & Benefits

- Outdoor UV protection up to 14 days
- Removes cleanly from most surfaces
- Suitable for indoor and outdoor use

Technical Data

SIZES	18mm, 24mm, 36mm, 48mm, 72mm x 55m
CARRIER	Blue Crepe Paper
ADHESIVE	Natural Rubber / Resin
TOTAL THICKNESS	5.1mils
TENSILE	24 lbs/in
ADHESION	25 oz/in
APPLICATION TEMPERATURE	50°F (10 °C) to 150°F (66°C)
SERVICE TEMPERATURE	Up to 150°F (66°C)
ELONGATION	8%
COLOR	Blue

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and

free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.