

Premium Grade 7-Day Stucco Duct Tape

CL-W6045 is a premium grade, 7-day cloth, stucco duct tape designed for stucco applications. Used to protect vinyl windows, profiles, and door frames, the stucco duct tape has superior holding power and leaves limited residue if removed within seven days.

APPLICATIONS FOR THE TAPE

The most common applications for the 7-day stucco duct tape include:

- protects door frames, vinyl windows, and profiles during outdoor stucco application
- used for one-coat stucco processes

FEATURES OF THE TAPE

Features of the 7-day stucco duct tape include:

- strong holding power and durability (prevents lifting)
- doesn't leave residue (if removed within 7 days)
- conforms to uneven surfaces
- can tear the tape by hand (leaving a clean, straight edge)
- easy to apply (doesn't curl or splinter)

TAPE ADHESIVE

The tape has a high-performance rubber adhesive.



WEATHER RESISTANCE

The 7-day stucco duct tape is weather resistant:

- can be used indoors and outdoors
- outstanding UV resistance (lasting up to 7 days)

TAPE SIZES

The 7-day stucco duct tape is available in the following size:

- 2 inches by 60 yards / 48 mm by 55 m

TAPE COLORS

The 7-day stucco duct tape is available in blue.

WHO USES THE TAPE

The tape is most commonly used by:

- stucco contractors
- painting contractors

ECHOtape PART NUMBER

The part number for this tape is CL-W6045.

Applications

- Designed to protect window and door frames in outdoor stucco masking applications
- Designed for single family, multi-family and commercial construction projects
- Used in one coat stucco processes



Features & Benefits

- Outstanding UV resistance lasting up to 7 days
- Residue free when removed within 7 days
- Excellent holding power and durability
- Conforms to uneven surfaces
- Holds strong which prevents lifting
- Can be torn by hand leaving a clean and straight edge
- Does not curl or splinter making it easy to apply
- Trusted by professional contractors nationwide

Technical Data

SIZES	1.89 in x 60 yd 48 mm x 55 m
CARRIER	Waterproof Polyethylene Coated Cloth
ADHESIVE	Rubber
TOTAL THICKNESS	9.5 mils
TENSILE	25 lbs/in
ADHESION	22 oz/in
COLOR	Blue

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best



when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability

High Strength Kraft Flatback Tape

FB-K4329 is a strong flat back tape designed primarily for splicing and tabbing but also can be used for various packaging applications. It is engineered for a wide range of humidity and temperature conditions and sticks to most surfaces. This product complies with the Federal Food, Drug and Cosmetic Act, CFR Title 21, Subpart B, par. 175.105 (which covers the use of pressure-sensitive adhesives and tapes for 'indirect contact' food packaging such as box sealing).

Applications

- Designed to protect window and door frames in outdoor stucco masking applications
- Designed for single family, multi-family and commercial construction projects
- Used in one coat stucco processes

Features & Benefits

- Outstanding UV resistance lasting up to 7 days
- Residue free when removed within 7 days
- Excellent holding power and durability
- Conforms to uneven surfaces
- Holds strong which prevents lifting

- Can be torn by hand leaving a clean and straight edge
- Does not curl or splinter making it easy to apply
- Trusted by professional contractors nationwide

Technical Data

SIZES	1.89 in x 60 yd 48 mm x 55 m
CARRIER	Waterproof Polyethylene Coated Cloth
ADHESIVE	Rubber
TOTAL THICKNESS	9.5 mils
TENSILE	25 lbs/in
ADHESION	22 oz/in
COLOR	Blue

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may

vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability