



Clear Double Sided Tape for Permanent Mounting & Bonding

DC-U101A a double sided UPVC tape incorporating an exceptionally high tack, high peel, acrylic adhesive system. DC-U101A performs well in many difficult bonding and splicing applications. Recommended application temperature to achieve best results is 65°F (18°C).

Applications

- Product assembly
- Difficult bonding and splicing applications
- Lamination to EPDM rubber, plastics, glass, and urethane foams

Features & Benefits

- Exceptionally high tack and peel
- UPVC film allows conformability
- High adhesive mass provides excellent gap filling properties
- Excellent resistance to environmental extremes
- Exhibits excellent adhesion to ether and ester foams
- Bonds well to rough or porous surfaces
- Excellent water resistance

Technical Data



SIZES	6mm x 55m 9mm x 55m 12mm x 55m 18mm x 55m 24mm x 55m 36mm x 55m 48mm x 55m 72mm x 55m custom slitting
Carrier	1.5 mils UPVC
Adhesive	Acrylic
Release Liner	60# Kraft
Total Thickness	8.5 mils
Adhesion	136 oz/in
Service Temperature	-20°F to 200°F (-29°C to 93°C)
Elongation	60%
Color	Transparent

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been



established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

High Strength Kraft Flatback Tape

FB-K4329 is a strong flat back tape designed primarily for splicing and tabbing but also can be used for various packaging applications. It is engineered for a wide range of humidity and temperature conditions and sticks to most surfaces. This product complies with the Federal Food, Drug and Cosmetic Act, CFR Title 21, Subpart B, par. 175.105 (which covers the use of pressure-sensitive adhesives and tapes for



`indirect contact' food packaging such and box sealing).

Applications

- Product assembly
- Difficult bonding and splicing applications
- Lamination to EPDM rubber, plastics, glass, and urethane foams

Features & Benefits

- Exceptionally high tack and peel
- UPVC film allows conformability
- High adhesive mass provides excellent gap filling properties
- Excellent resistance to environmental extremes
- Exhibits excellent adhesion to ether and ester foams
- Bonds well to rough or porous surfaces
- Excellent water resistance

Technical Data

SIZES	6mm x 55m
	9mm x 55m
	12mm x 55m
	18mm x 55m
	24mm x 55m
	36mm x 55m
	48mm x 55m
	72mm x 55m
	custom slitting



Carrier	1.5 mils UPVC
Adhesive	Acrylic
Release Liner	60# Kraft
Total Thickness	8.5 mils
Adhesion	136 oz/in
Service Temperature	-20°F to 200°F (-29°C to 93°C)
Elongation	60%
Color	Transparent

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product



is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

High Tensile Kraft Flatback Tape

FB-K4347 is a strong flat back tape designed primarily for splicing and tabbing applications and also performs well for packaging applications. It is engineered for a wide range of humidity and temperature conditions and sticks to most surfaces. This product complies with the Federal Food, Drug and Cosmetic Act, CFR Title 21, Subpart B, par. 175.105 (which covers the use of pressure-sensitive adhesives and tapes for 'indirect contact' food packaging such and box sealing).

Applications

- Product assembly
- Difficult bonding and splicing applications
- Lamination to EPDM rubber, plastics, glass, and urethane foams



Features & Benefits

- Exceptionally high tack and peel
- UPVC film allows conformability
- High adhesive mass provides excellent gap filling properties
- Excellent resistance to environmental extremes
- Exhibits excellent adhesion to ether and ester foams
- Bonds well to rough or porous surfaces
- Excellent water resistance

Technical Data

SIZES	6mm x 55m 9mm x 55m 12mm x 55m 18mm x 55m 24mm x 55m 36mm x 55m 48mm x 55m 72mm x 55m custom slitting
Carrier	1.5 mils UPVC
Adhesive	Acrylic
Release Liner	60# Kraft
Total Thickness	8.5 mils
Adhesion	136 oz/in
Service Temperature	-20°F to 200°F (-29°C to 93°C)
Elongation	60%



Color	Transparent
-------	-------------

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

–

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.



Resistant 30-Day Stucco Masking Tape

VI-N6149 is a UV resistant red polyethylene tape used by professional stucco contractors. It is used to protect and mask windows, profiles and door frames during outdoor stucco application on building walls. Engineered with a high performance rubber adhesive, it is designed to bond well to most surfaces and provide clean removal in 30 days. It also provides a watertight seal in a range of weather conditions.

Applications

- Product assembly
- Difficult bonding and splicing applications
- Lamination to EPDM rubber, plastics, glass, and urethane foams

Features & Benefits

- Exceptionally high tack and peel
- UPVC film allows conformability
- High adhesive mass provides excellent gap filling properties
- Excellent resistance to environmental extremes
- Exhibits excellent adhesion to ether and ester foams



- Bonds well to rough or porous surfaces
- Excellent water resistance

Technical Data

SIZES	6mm x 55m 9mm x 55m 12mm x 55m 18mm x 55m 24mm x 55m 36mm x 55m 48mm x 55m 72mm x 55m custom slitting
Carrier	1.5 mils UPVC
Adhesive	Acrylic
Release Liner	60# Kraft
Total Thickness	8.5 mils
Adhesion	136 oz/in
Service Temperature	-20°F to 200°F (-29°C to 93°C)
Elongation	60%
Color	Transparent

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.



—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.