Self Adhesive Protective Film for Windows

PR-N3287 is a self-adhesive, protective film for windows that offers temporary protection against stucco, paint, and mortar overspray. This protective film is widely used by stucco contractors, painters, masons, builders, and remodelers.

APPLICATIONS FOR THE FILM

The most common applications for the protective film include protection for windows during:

- stucco work
- masonry and mortar work
- painting
- other construction tasks

FEATURES OF THE FILM

Features of the protective window film include:

- self-adhesive
- easy to unwind and apply by hand
- easy to remove
- removes cleanly (without leaving adhesive residue)
- UV resistant for up to 180 days, in all weather

FILM ADHESIVE

The film has an acrylic adhesive.

WEATHER RESISTANCE

The protective window film is UV resistant for up to 180 days, in all types of weather.

FILM SIZES

The window film is available in the following size:

- 24 inches by 600 yards / 610 mm x 183 m

FILM COLORS

The protective window film is available in blue or transparent.

WHO USES THE FILM

The window film is most commonly used by:

- stucco contractors
- painters
- masons
- general contractors
- builders
- remodelers

ECHOtape PART NUMBER

The part number for this film is PR-N3287.

Applications

- Masking windows in construction projects (i.e. stucco and masonry)

Features & Benefits

- Easy to unwind and apply by hand
- Easy to remove
- Removes cleanly without leaving adhesive residue
- UV resistant for 180 days in all weather

Technical Data

SIZES	24″ x 600′
CARRIER	Low Density Polyethylene Film
ADHESIVE	Acrylic
TOTAL THICKNESS	2 mils
TENSILE	5.5 lbs/in
ADHESION	2 oz/in
MAXIMUM TEMPERATURE RESISTANCE	140°F (60°C)
ELONGATION	Long. >300% / Trans. >500%
UV RESISTANCE	180 days
COLOR	Blue, Transparent

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

–

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.