

Premium Grade 7-Day Stucco Duct Tape

CL-W6045 is a premium grade, 7-day cloth, stucco duct tape designed for stucco applications. Used to protect vinyl windows, profiles, and door frames, the stucco duct tape has superior holding power and leaves limited residue if removed within seven days.

APPLICATIONS FOR THE TAPE

The most common applications for the 7-day stucco duct tape include:

- protects door frames, vinyl windows, and profiles during outdoor stucco application
- used for one-coat stucco processes

FEATURES OF THE TAPE

Features of the 7-day stucco duct tape include:

- strong holding power and durability (prevents lifting)
- doesn't leave residue (if removed within 7 days)
- conforms to uneven surfaces
- can tear the tape by hand (leaving a clean, straight edge)
- easy to apply (doesn't curl or splinter)

TAPE ADHESIVE

The tape has a high-performance rubber adhesive.



WEATHER RESISTANCE

The 7-day stucco duct tape is weather resistant:

- can be used indoors and outdoors
- outstanding UV resistance (lasting up to 7 days)

TAPE SIZES

The 7-day stucco duct tape is available in the following size:

- 2 inches by 60 yards / 48 mm by 55 m

TAPE COLORS

The 7-day stucco duct tape is available in blue.

WHO USES THE TAPE

The tape is most commonly used by:

- stucco contractors
- painting contractors

ECHOtape PART NUMBER

The part number for this tape is CL-W6045.

Applications

- Designed to protect window and door frames in outdoor stucco masking applications
- Designed for single family, multi-family and commercial construction projects
- Used in one coat stucco processes

Features & Benefits

- Outstanding UV resistance lasting up to 7 days
- Residue free when removed within 7 days
- Excellent holding power and durability
- Conforms to uneven surfaces
- Holds strong which prevents lifting
- Can be torn by hand leaving a clean and straight edge
- Does not curl or splinter making it easy to apply
- Trusted by professional contractors nationwide

Technical Data

| | |
|------------------------|--------------------------------------|
| SIZES | 1.89 in x 60 yd 48 mm x 55 m |
| CARRIER | Waterproof Polyethylene Coated Cloth |
| ADHESIVE | Rubber |
| TOTAL THICKNESS | 9.5 mils |
| TENSILE | 25 lbs/in |
| ADHESION | 22 oz/in |
| COLOR | Blue |

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best



when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability

Premium Grade 60 Day Stucco Duct Tape Gray

CL-W6059 is a premium grade, gray 60-day cloth stucco duct tape that was developed for stucco professionals. Designed to protect window frames and door frames during outdoor masking applications, the tape is strong and durable and will peel off without leaving residue.

APPLICATIONS FOR THE TAPE

The most common applications for the 60-day stucco duct tape include:

- protects vinyl windows, profiles, and doorframes during outdoor stucco applications
- recommended by Milgard for use with their vinyl and fiberglass windows
- used in 2-step and 3-step stucco processes (scratch, brown, and finish) where the protective barrier is used throughout the entire stucco application

FEATURES OF THE TAPE

Features of the 60-day stucco duct tape include:

- superior holding power and durability in hot temperatures
- limited residue when removed within 60 days of application



-
- sticks well to smooth surfaces (such as steel and plastic)
 - sticks well to rough or textured surfaces (such as wood)
 - conforms to uneven surfaces
 - can tear the tape by hand (leaving a clean, straight edge)
 - easy to apply (doesn't curl or splinter)

TAPE ADHESIVE

The tape has a high-performance rubber adhesive.

WEATHER RESISTANCE

The 60-day stucco duct tape is weather resistant:

- can be used indoors and outdoors
- outstanding UV resistance
- holds up in hot temperatures

TAPE SIZES

The 60-day stucco duct tape is available in the following sizes:

- 2 inches by 60 yards / 48 mm by 55 m

TAPE COLORS

The 60-day stucco duct tape is available in gray.



WHO USES THE TAPE

The tape is most commonly used by:

- stucco contractors
- painting contractors

ECHOtape PART NUMBER

The part number for this tape is CL-W6059.

Applications

- Designed to protect window and door frames in outdoor stucco masking applications
- Designed for single family, multi-family and commercial construction projects
- Used in one coat stucco processes

Features & Benefits

- Outstanding UV resistance lasting up to 7 days
- Residue free when removed within 7 days
- Excellent holding power and durability
- Conforms to uneven surfaces
- Holds strong which prevents lifting
- Can be torn by hand leaving a clean and straight edge
- Does not curl or splinter making it easy to apply
- Trusted by professional contractors nationwide

Technical Data

| | |
|------------------------|--------------------------------------|
| SIZES | 1.89 in x 60 yd 48 mm x 55 m |
| CARRIER | Waterproof Polyethylene Coated Cloth |
| ADHESIVE | Rubber |
| TOTAL THICKNESS | 9.5 mils |
| TENSILE | 25 lbs/in |
| ADHESION | 22 oz/in |
| COLOR | Blue |

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or

otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability

Premium Grade 60-Day Stucco Duct Tape [Red]

CL-W6089 is a premium grade, red cloth duct tape that's designed to protect and mask windows, profiles, and door frames during outdoor stucco applications. Strong and durable, this 60-day stucco duct tape has a high-tack rubber adhesive that holds up well in hot temperatures, high winds, and moist conditions. Easy to apply, the tape leaves limited residue if removed within 60 days.

APPLICATIONS FOR THE TAPE

The most common applications for the 60-day stucco duct tape



include:

- protects vinyl windows, profiles, and doorframes during outdoor stucco applications
- used in 2-step and 3-step stucco processes (scratch, brown, and finish) where the protective barrier is left in place throughout the entire stucco application

FEATURES OF THE TAPE

Features of the 60-day stucco duct tape include:

- superior holding power in hot temperatures, high winds, and moist conditions
- limited residue when removed within 60 days of application
- conforms to uneven surfaces
- can tear the tape by hand (leaving a clean, straight edge)
- easy to apply (doesn't curl or splinter)

TAPE ADHESIVE

The tape has a high-performance rubber adhesive.

WEATHER RESISTANCE

The 60-day stucco duct tape is weather resistant:

- holds well in high temperatures
- holds well in high winds
- holds well in moist conditions
- outstanding UV resistance (lasting up to 60 days)

TAPE SIZES



The 60-day stucco duct tape is available in the following sizes:

- 2 inches by 60 yards / 48 mm by 55 m

TAPE COLORS

The 60-day stucco duct tape is available in red.

WHO USES THE TAPE

The tape is most commonly used by:

- stucco contractors
- painting contractors

ECHOtape PART NUMBER

The part number for this tape is CL-W6089.

Applications

- Designed to protect window and door frames in outdoor stucco masking applications
- Designed for single family, multi-family and commercial construction projects
- Used in one coat stucco processes

Features & Benefits

- Outstanding UV resistance lasting up to 7 days
- Residue free when removed within 7 days
- Excellent holding power and durability
- Conforms to uneven surfaces

- Holds strong which prevents lifting
- Can be torn by hand leaving a clean and straight edge
- Does not curl or splinter making it easy to apply
- Trusted by professional contractors nationwide

Technical Data

| | |
|-----------------|--------------------------------------|
| SIZES | 1.89 in x 60 yd 48 mm x 55 m |
| CARRIER | Waterproof Polyethylene Coated Cloth |
| ADHESIVE | Rubber |
| TOTAL THICKNESS | 9.5 mils |
| TENSILE | 25 lbs/in |
| ADHESION | 22 oz/in |
| COLOR | Blue |

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The

values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability

High Strength Kraft Flatback Tape

FB-K4329 is a strong flat back tape designed primarily for splicing and tabbing but also can be used for various packaging applications. It is engineered for a wide range of humidity and temperature conditions and sticks to most surfaces. This product complies with the Federal Food, Drug

and Cosmetic Act, CFR Title21, Subpart B, par. 175.105 (which covers the use of pressure-sensitive adhesives and tapes for `indirect contact' food packaging such and box sealing).

Applications

- Designed to protect window and door frames in outdoor stucco masking applications
- Designed for single family, multi-family and commercial construction projects
- Used in one coat stucco processes

Features & Benefits

- Outstanding UV resistance lasting up to 7 days
- Residue free when removed within 7 days
- Excellent holding power and durability
- Conforms to uneven surfaces
- Holds strong which prevents lifting
- Can be torn by hand leaving a clean and straight edge
- Does not curl or splinter making it easy to apply
- Trusted by professional contractors nationwide

Technical Data

| | |
|-----------------|--------------------------------------|
| SIZES | 1.89 in x 60 yd 48 mm x 55 m |
| CARRIER | Waterproof Polyethylene Coated Cloth |
| ADHESIVE | Rubber |
| TOTAL THICKNESS | 9.5 mils |



| | |
|-----------------|-----------|
| TENSILE | 25 lbs/in |
| ADHESION | 22 oz/in |
| COLOR | Blue |

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct,

indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability

Blue Painter's Paper Indoor/Outdoor Masking Tape (14 Day)

MK-K5497 is a high-performance blue painter's tape (5.1 mils thick) that can be used for most types of masking applications. Designed for indoor use and outdoor use, the blue painter's tape removes cleanly from most surfaces for up to 14 days. And in that time, the painter's tape won't dry out or lose its holding power.

APPLICATIONS FOR THE TAPE

The most common applications for the blue painter's tape include:

- masking for painting
- masking of drywall
- masking of wood trim
- masking of windows

- masking of hardwood floors and other flooring surfaces

FEATURES OF THE TAPE

Features of the blue painter's tape include:

- removes cleanly from most surfaces
- suitable for indoor use and outdoor use
- outdoor UV protection up to 14 days

TAPE ADHESIVE

The tape has a natural rubber (resin) adhesive.

WEATHER RESISTANCE

The blue painter's tape is suitable for outdoor use and has outdoor UV protection for up to 14 days.

TAPE SIZES

The blue painter's tape is available in the following size:

- 2 inches by 60 yards / 48 mm x 55 m

TAPE COLORS

The painter's tape is available in blue.

WHO USES THE TAPE

The tape is most commonly used by:

- painters
- general contractors



ECHOtape PART NUMBER

The part number for this tape is MK-K5497.

Applications

- Designed to protect window and door frames in outdoor stucco masking applications
- Designed for single family, multi-family and commercial construction projects
- Used in one coat stucco processes

Features & Benefits

- Outstanding UV resistance lasting up to 7 days
- Residue free when removed within 7 days
- Excellent holding power and durability
- Conforms to uneven surfaces
- Holds strong which prevents lifting
- Can be torn by hand leaving a clean and straight edge
- Does not curl or splinter making it easy to apply
- Trusted by professional contractors nationwide

Technical Data

| | |
|------------------------|--------------------------------------|
| SIZES | 1.89 in x 60 yd 48 mm x 55 m |
| CARRIER | Waterproof Polyethylene Coated Cloth |
| ADHESIVE | Rubber |
| TOTAL THICKNESS | 9.5 mils |

| | |
|----------|-----------|
| TENSILE | 25 lbs/in |
| ADHESION | 22 oz/in |
| COLOR | Blue |

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct,

indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability