

Strong Double Sided Tape For Temporary Hold

DC-K048A is an extremely strong, double-sided tape that's designed to mount or bond items temporarily. The tape sticks very well to smooth surfaces (such as steel and paper), but also can be used on wood, fabric, and other porous and textured surfaces. When you need your temporary hold to hold up, this double-sided tape will do the trick!

APPLICATIONS FOR THE TAPE

The most common applications for the temporary double-sided tape include:

- temporarily hold down steel or metal components
- temporarily hold down wooden components
- temporarily hold small carpets in place
- mount posters or photographs on walls

FEATURES OF THE TAPE

Features of the temporary double-sided tape include:

- excellent holding power from the onset
- removes cleanly from most hard and smooth surfaces
- easy to remove the paper liner
- can tear the tape by hand
- designed to work at room temperature, the tape can also perform for medium heat applications

TAPE ADHESIVE



The tape has a high-performance rubber adhesive.

TAPE SIZES

The temporary double-sided tape is available in the following size:

- 1 inch by 36 yards / 24 mm by 33 m

TAPE COLORS

The temporary double-sided tape is available in beige.

WHO USES THE TAPE

The tape is most commonly used by:

- manufacturers
- printers
- woodworkers
- interior decorators and designers

ECHOtape PART NUMBER

The part number for this tape is DC-K048A.

Applications

- Use to temporarily hold down steel or metal components in manufacturing or printing applications
- Use to temporarily hold down wooden components in woodworking applications
- Use to mount posters or photographs on walls
- Use to temporarily hold small carpets in place



Features & Benefits

- Hand tearable making it very easy to apply and use
- Excellent holding power from the onset helps speed up application
- Easy to remove paper liner
- Removes cleanly from most hard and smooth surfaces

Technical Data

SIZES	.94 in x 36 yd 24 mm x 33m
CARRIER	Crepe Paper
ADHESIVE	Rubber
TOTAL THICKNESS	6 mils
RELEASE LINER	Crepe Paper
TENSILE	23 lbs/in
ADHESION	47 oz/in
APPLICATION TEMPERATURE	50°F to 110°F (10°C to 43°C)
SERVICE TEMPERATURE	32°F to 180°F (0°C to 82°C)
ELONGATION	8.5%
COLOR	Beige

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape



should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

Clear Double Sided Tape for Permanent Mounting and Bonding

DC-M012P is an extremely strong and aggressive, double-sided tape that's designed to mount or bond items permanently. Thanks to its high-performance acrylic adhesive, this double-sided tape can be used for difficult bonding applications where other tapes might fail. The clear tape sticks well to a variety of surfaces, including plexiglass, rubber, plastic, metal, and steel.

APPLICATIONS FOR THE TAPE

The most common applications for the permanent double-sided tape include:

- permanent bonding of steel, metal, plastic, rubber, and plexiglass
- mounting small to medium, lightweight indoor and outdoor signs
- mounting nameplates
- mounting decorative trims
- mounting plastic profiles
- joining or splicing various types of polyester films
- difficult bonding applications where other tapes might not adhere properly

FEATURES OF THE TAPE



Features of the permanent double-sided tape include:

- strong hold from the onset
- easily conforms to most surfaces
- superior adhesion to polyester films
- easy-to-remove red paper liner makes it quick to apply the tape
- acrylic adhesive provides maximum performance indoors and outdoors

TAPE ADHESIVE

The tape has a high-performance acrylic adhesive.

WEATHER RESISTANCE

The permanent double-sided tape can be used indoors and outdoors.

TAPE SIZES

The permanent double-sided tape is available in the following size:

- 1 inch by 36 yards / 24 mm by 33 m

TAPE COLORS

The permanent double-sided tape is available in clear (transparent).

WHO USES THE TAPE

The tape is most commonly used by:

- sign companies
- plexiglass installers



- insulation companies
- contractors who use polyester film
- interior decorators and designers

ECHOtape PART NUMBER

The part number for this tape is DC-M012P.

Applications

- Use to temporarily hold down steel or metal components in manufacturing or printing applications
- Use to temporarily hold down wooden components in woodworking applications
- Use to mount posters or photographs on walls
- Use to temporarily hold small carpets in place

Features & Benefits

- Hand tearable making it very easy to apply and use
- Excellent holding power from the onset helps speed up application
- Easy to remove paper liner
- Removes cleanly from most hard and smooth surfaces

Technical Data

SIZES	.94 in x 36 yd 24 mm x 33m
CARRIER	Crepe Paper
ADHESIVE	Rubber

TOTAL THICKNESS	6 mils
RELEASE LINER	Crepe Paper
TENSILE	23 lbs/in
ADHESION	47 oz/in
APPLICATION TEMPERATURE	50°F to 110°F (10°C to 43°C)
SERVICE TEMPERATURE	32°F to 180°F (0°C to 82°C)
ELONGATION	8.5%
COLOR	Beige

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or

otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

Clear Double Sided Polyester Tape for General Purpose Mounting & Bonding

DC-M158A is the perfect permanent double-sided tape for everyday applications around the office, warehouse, workshop, or classroom. The aggressive, acrylic adhesive bonds to virtually any surface, and on hard surfaces, you can reposition the tape within 60 seconds of application. Designed for lightweight mounting and bonding, the double-sided tape can be applied to textiles, foils, films, papers, plastic, metal, and more!

APPLICATIONS FOR THE TAPE



The most common applications for the permanent double-sided tape include:

- permanent bonding of papers, films, foils, textiles, leather, plastic, and metal
- general assembly of decorative parts
- temporary bonding to keep items in place prior to fastening them
- bonding textiles and leather prior to sewing

FEATURES OF THE TAPE

Features of the permanent double-sided tape include:

- fast-grabbing adhesive sticks well from the onset
- can reposition the tape within 60 seconds (but only on hard surfaces)
- adheres well to a variety of surfaces
- polyester carrier is flexible and conforms to many surfaces
- can tear the tape by hand
- performs well across a broad range of temperatures

TAPE ADHESIVE

The tape has an aggressive, high-tack acrylic adhesive.

WEATHER RESISTANCE

The permanent double-sided tape performs well across a wide range of temperatures.

TAPE SIZES

The permanent double-sided tape is available in the following sizes:



- 1 inch by 55 yards / 24 mm by 50 m
- 2 inches by 55 yards / 48 mm by 50 m

TAPE COLORS

The permanent double-sided tape is available in clear (transparent).

WHO USES THE TAPE

The tape is most commonly used in:

- offices
- warehouses
- workshops
- classrooms
- sewing workrooms

ECHOtape PART NUMBER

The part number for this tape is DC-M158A.

Applications

- Use to temporarily hold down steel or metal components in manufacturing or printing applications
- Use to temporarily hold down wooden components in woodworking applications
- Use to mount posters or photographs on walls
- Use to temporarily hold small carpets in place



Features & Benefits

- Hand tearable making it very easy to apply and use
- Excellent holding power from the onset helps speed up application
- Easy to remove paper liner
- Removes cleanly from most hard and smooth surfaces

Technical Data

SIZES	.94 in x 36 yd 24 mm x 33m
CARRIER	Crepe Paper
ADHESIVE	Rubber
TOTAL THICKNESS	6 mils
RELEASE LINER	Crepe Paper
TENSILE	23 lbs/in
ADHESION	47 oz/in
APPLICATION TEMPERATURE	50°F to 110°F (10°C to 43°C)
SERVICE TEMPERATURE	32°F to 180°F (0°C to 82°C)
ELONGATION	8.5%
COLOR	Beige

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and

free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.