



Double Sided Foam Glazing Tape

The GL-N0708 and GL-N0716 tapes are designed for window glazing applications to ensure windows are properly sealed against the elements they face on a daily basis. These glazing tapes are made with a PE (Polyethylene) foam and a strong high tack acrylic adhesive coated on each side. The product's unique construction allows for flexibility and softness allowing it to adapt to many textured surfaces. The easy release poly liner makes it a breeze to use and apply.

Applications

- Use for window glazing applications on aluminum and PVC window framing
- Use for bonding and mounting of lightweight plastic and metal

Features & Benefits

- AAMA certification makes it suitable for glazing applications
- Excellent weather, oxidation, UV, and temperature resistance
- Seals well against water, dust, and light
- Flexible and soft to adjust to a variety of textured surfaces
- High initial adhesion makes it stick well from the onset



and the acrylic adhesive continues to strengthen over time

Technical Data

| | |
|----------------------------|--|
| SIZES | 1/8", 1/16", 1/32", 3/32" x 6mm, 9mm, 12mm, 15mm x 75' custom slitting |
| CARRIER | 2.0 PCF PE Foam (1/8") & 4.0 PCF PE Foam (1/16") |
| ADHESIVE | Acrylic |
| RELEASE LINER | 4 mil Blue PE |
| TOTAL THICKNESS | 1/8" and 1/16" |
| ADHESION | 110 oz/in |
| SERVICE TEMPERATURE | -4°F to 248°F (-20°C to 120°C) |
| ELONGATION | 180% |
| COLOR | Black, White |

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The



values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at the time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If the ECH0tape product is proven to be defective, the exclusive remedy shall be for ECH0tape to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty, or strict liability.