



---

# General Purpose Clear Double Sided Tape for Mounting Bonding (Paper)

DC-T274A is the ideal choice when you want a fast grabbing tape for those everyday applications around the office, warehouse, workshop or classroom. This double sided high performance tape is ideal for many lightweight mounting and bonding applications to paper, film, foils, plastic, textiles and more. It features an aggressive, high tack acrylic adhesive that sticks to almost any surface.

## Applications

- Use to bond papers, films, foils, textile, plastic and metal
- Use for general assembly of decorative parts
- Use for temporary bonding to keep items in place prior to fastening
- Use to bond textile and leather prior to sewing

## Features & Benefits

- Tears by hand making it very easy to use
- Fast grabbing adhesive sticks well from the onset and helps save you time
- Flexible enough to conform to many surfaces
- Adheres well to a variety of surfaces



- Easy to remove paper liner

## Technical Data

<b>Sizes</b>	.47 in x 54.6 yd   12mm x 50m .71 in x 54.6 yd / 18mm x 50m .94 in x 54.6 yd / 24mm x 50m 1.89 in x 54.6 yd / 48mm x 50m
<b>CARRIER</b>	Tissue
<b>ADHESIVE</b>	Acrylic
<b>RELEASE LINER</b>	White
<b>TOTAL THICKNESS</b>	3.9 mils
<b>ADHESION</b>	65 oz/in
<b>SERVICE TEMPERATURE</b>	32°F to 194°F (0°C to 90°C)
<b>COLOR</b>	Frosted Clear

## Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are



---

warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

---

## **White Double Sided Tape for Permanent Mounting & Bonding**

DC-U032A is an extremely aggressive and strong double-sided mounting tape that is designed for permanent bonding and will stick to just about any surface.

### **APPLICATIONS FOR THE TAPE**

The most common applications for the permanent, double-sided mounting tape include:

- permanent bonding of metal, plastic, rubber, plexiglass, and wood
- mounting small to medium, lightweight indoor and outdoor



---

signs

- mounting name plates
- mounting decorative trim
- bonding applications where other tapes might not adhere properly

## **FEATURES OF THE TAPE**

Features of the permanent, double-sided mounting tape include:

- superior holding power (from the onset)
- sticks well to smooth surfaces (such as steel and plastic)
- adheres to rough and textured surfaces (such as wood)
- conforms to most surfaces
- easy to apply (the tape can be easily removed from its liner)
- designed to work at room temperature, the tape can also perform for medium heat applications

## **TAPE ADHESIVE**

The tape has an acrylic adhesive.

## **WEATHER RESISTANCE**

The permanent, double-sided mounting tape is weather resistant:

- can be used indoors and outdoors
- resistant to extreme weather and other environmental conditions

## **TAPE SIZES**

The permanent, double-sided mounting tape is available in the



---

following sizes:

- 1/2 inch by 54.6 yards / 12 mm by 50 m
- 3/4 inch by 54.6 yards / 18 mm by 50 m
- 1 inch by 54.6 yards / 24 mm by 50 m
- 2 inches by 54.6 yards / 48 mm by 50 m

## **TAPE COLORS**

The permanent, double-sided mounting tape is available in white.

## **WHO USES THE TAPE**

The tape is most commonly used by:

- construction professionals
- flooring contractors
- insulation contractors
- handymen
- sign makers
- interior decorators and designers

## **ECH0tape PART NUMBER**

The part number for this tape is DC-U032A.

## **Applications**

- Use to bond papers, films, foils, textile, plastic and metal
- Use for general assembly of decorative parts
- Use for temporary bonding to keep items in place prior to fastening
- Use to bond textile and leather prior to sewing



---

## Features & Benefits

- Tears by hand making it very easy to use
- Fast grabbing adhesive sticks well from the onset and helps save you time
- Flexible enough to conform to many surfaces
- Adheres well to a variety of surfaces
- Easy to remove paper liner

## Technical Data

<b>Sizes</b>	.47 in x 54.6 yd   12mm x 50m .71 in x 54.6 yd / 18mm x 50m .94 in x 54.6 yd / 24mm x 50m 1.89 in x 54.6 yd / 48mm x 50m
<b>CARRIER</b>	Tissue
<b>ADHESIVE</b>	Acrylic
<b>RELEASE LINER</b>	White
<b>TOTAL THICKNESS</b>	3.9 mils
<b>ADHESION</b>	65 oz/in
<b>SERVICE TEMPERATURE</b>	32°F to 194°F (0°C to 90°C)
<b>COLOR</b>	Frosted Clear

## Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and



---

free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.