



Matte Black Professional Gaffers Tape

Rolls per Case (1.89 in / 48mm): 24

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years



Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a



particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

Premium Grade 7-Day Stucco Duct Tape

CL-W6045 is a premium grade, 7-day cloth, stucco duct tape designed for stucco applications. Used to protect vinyl windows, profiles, and door frames, the stucco duct tape has superior holding power and leaves limited residue if removed within seven days.

APPLICATIONS FOR THE TAPE

The most common applications for the 7-day stucco duct tape include:



- protects door frames, vinyl windows, and profiles during outdoor stucco application
- used for one-coat stucco processes

FEATURES OF THE TAPE

Features of the 7-day stucco duct tape include:

- strong holding power and durability (prevents lifting)
- doesn't leave residue (if removed within 7 days)
- conforms to uneven surfaces
- can tear the tape by hand (leaving a clean, straight edge)
- easy to apply (doesn't curl or splinter)

TAPE ADHESIVE

The tape has a high-performance rubber adhesive.

WEATHER RESISTANCE

The 7-day stucco duct tape is weather resistant:

- can be used indoors and outdoors
- outstanding UV resistance (lasting up to 7 days)

TAPE SIZES

The 7-day stucco duct tape is available in the following size:

- 2 inches by 60 yards / 48 mm by 55 m

TAPE COLORS

The 7-day stucco duct tape is available in blue.



WHO USES THE TAPE

The tape is most commonly used by:

- stucco contractors
- painting contractors

ECHOtape PART NUMBER

The part number for this tape is CL-W6045.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a



particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

Premium Grade 60 Day Stucco Duct Tape Gray

CL-W6059 is a premium grade, gray 60-day cloth stucco duct tape that was developed for stucco professionals. Designed to protect window frames and door frames during outdoor masking applications, the tape is strong and durable and will peel off without leaving residue.

APPLICATIONS FOR THE TAPE

The most common applications for the 60-day stucco duct tape include:

- protects vinyl windows, profiles, and doorframes during outdoor stucco applications
- recommended by Milgard for use with their vinyl and fiberglass windows
- used in 2-step and 3-step stucco processes (scratch, brown, and finish) where the protective barrier is used throughout the entire stucco application

FEATURES OF THE TAPE

Features of the 60-day stucco duct tape include:

- superior holding power and durability in hot temperatures
- limited residue when removed within 60 days of application
- sticks well to smooth surfaces (such as steel and plastic)
- sticks well to rough or textured surfaces (such as wood)
- conforms to uneven surfaces
- can tear the tape by hand (leaving a clean, straight edge)
- easy to apply (doesn't curl or splinter)

TAPE ADHESIVE

The tape has a high-performance rubber adhesive.

WEATHER RESISTANCE

The 60-day stucco duct tape is weather resistant:



-
- can be used indoors and outdoors
 - outstanding UV resistance
 - holds up in hot temperatures

TAPE SIZES

The 60-day stucco duct tape is available in the following sizes:

- 2 inches by 60 yards / 48 mm by 55 m

TAPE COLORS

The 60-day stucco duct tape is available in gray.

WHO USES THE TAPE

The tape is most commonly used by:

- stucco contractors
- painting contractors

ECHOtape PART NUMBER

The part number for this tape is CL-W6059.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords



- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

Industrial Strength Utility Grade Duct Tape

CL-W6064 is an industrial-strength duct tape that's no ordinary duct tape! Made with an advanced adhesive technology, the duct tape provides superior holding power, yet is easy to tear and apply. This heavy-duty duct tape sticks well to smooth and rough surfaces, and it can be used for holding, seaming, repairing, and bundling.

Applications For the Tape

The most common applications for the industrial duct tape include:

- temporary holding and bonding
- general purpose use and repair
- hanging and patching polyethylene sheeting
- duct work
- bundling
- color coding
- applications in manufacturing and industrial environments

Features Of the Tape

Features of the industrial duct tape include:



- aggressive adhesive
- superior holding power
- sticks well to a wide variety of smooth and rough surfaces
- conforms to uneven surfaces
- can tear the tape by hand (leaving a clean, straight edge)
- unwinds smoothly (making it easier to apply)
- tape lays flat (no twisting or curling)

Tape Adhesive

The tape has a high-performance rubber adhesive.

Tape Sizes

The industrial duct tape is available in the following size:

- 2 inches by 60 yards / 48 mm by 55 m

Tape Colors

The industrial duct tape is available in silver, black, yellow, red, blue, green, and white.

Who Uses the Tape

The tape is most commonly used by:

- construction professionals
- HVAC contractors
- contractors



ECHOtape Part Number

The part number for this tape is CL-W6064.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber



THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for

Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

Premium Grade 60-Day Stucco Duct Tape [Red]

CL-W6089 is a premium grade, red cloth duct tape that's designed to protect and mask windows, profiles, and door frames during outdoor stucco applications. Strong and durable, this 60-day stucco duct tape has a high-tack rubber adhesive that holds up well in hot temperatures, high winds, and moist conditions. Easy to apply, the tape leaves limited residue if removed within 60 days.

APPLICATIONS FOR THE TAPE

The most common applications for the 60-day stucco duct tape include:

- protects vinyl windows, profiles, and doorframes during outdoor stucco applications
- used in 2-step and 3-step stucco processes (scratch,



brown, and finish) where the protective barrier is left in place throughout the entire stucco application

FEATURES OF THE TAPE

Features of the 60-day stucco duct tape include:

- superior holding power in hot temperatures, high winds, and moist conditions
- limited residue when removed within 60 days of application
- conforms to uneven surfaces
- can tear the tape by hand (leaving a clean, straight edge)
- easy to apply (doesn't curl or splinter)

TAPE ADHESIVE

The tape has a high-performance rubber adhesive.

WEATHER RESISTANCE

The 60-day stucco duct tape is weather resistant:

- holds well in high temperatures
- holds well in high winds
- holds well in moist conditions
- outstanding UV resistance (lasting up to 60 days)

TAPE SIZES

The 60-day stucco duct tape is available in the following sizes:

- 2 inches by 60 yards / 48 mm by 55 m



TAPE COLORS

The 60-day stucco duct tape is available in red.

WHO USES THE TAPE

The tape is most commonly used by:

- stucco contractors
- painting contractors

ECHOtape PART NUMBER

The part number for this tape is CL-W6089.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant

- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are

warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

Strong Double Sided Tape For Temporary Hold

DC-K048A is an extremely strong, double-sided tape that's designed to mount or bond items temporarily. The tape sticks very well to smooth surfaces (such as steel and paper), but also can be used on wood, fabric, and other porous and textured surfaces. When you need your temporary hold to hold up, this double-sided tape will do the trick!

APPLICATIONS FOR THE TAPE



The most common applications for the temporary double-sided tape include:

- temporarily hold down steel or metal components
- temporarily hold down wooden components
- temporarily hold small carpets in place
- mount posters or photographs on walls

FEATURES OF THE TAPE

Features of the temporary double-sided tape include:

- excellent holding power from the onset
- removes cleanly from most hard and smooth surfaces
- easy to remove the paper liner
- can tear the tape by hand
- designed to work at room temperature, the tape can also perform for medium heat applications

TAPE ADHESIVE

The tape has a high-performance rubber adhesive.

TAPE SIZES

The temporary double-sided tape is available in the following size:

- 1 inch by 36 yards / 24 mm by 33 m

TAPE COLORS

The temporary double-sided tape is available in beige.

WHO USES THE TAPE

The tape is most commonly used by:

- manufacturers
- printers
- woodworkers
- interior decorators and designers

ECHOtape PART NUMBER

The part number for this tape is DC-K048A.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a

particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

Clear Double Sided Tape for Permanent Mounting and Bonding

DC-M012P is an extremely strong and aggressive, double-sided tape that's designed to mount or bond items permanently. Thanks to its high-performance acrylic adhesive, this double-sided tape can be used for difficult bonding applications where other tapes might fail. The clear tape sticks well to a variety of surfaces, including plexiglass, rubber, plastic, metal, and steel.

APPLICATIONS FOR THE TAPE

The most common applications for the permanent double-sided tape include:

- permanent bonding of steel, metal, plastic, rubber, and plexiglass
- mounting small to medium, lightweight indoor and outdoor signs
- mounting nameplates
- mounting decorative trims
- mounting plastic profiles
- joining or splicing various types of polyester films
- difficult bonding applications where other tapes might not adhere properly

FEATURES OF THE TAPE

Features of the permanent double-sided tape include:

- strong hold from the onset
- easily conforms to most surfaces
- superior adhesion to polyester films
- easy-to-remove red paper liner makes it quick to apply the tape
- acrylic adhesive provides maximum performance indoors and outdoors

TAPE ADHESIVE

The tape has a high-performance acrylic adhesive.

WEATHER RESISTANCE

The permanent double-sided tape can be used indoors and



outdoors.

TAPE SIZES

The permanent double-sided tape is available in the following size:

- 1 inch by 36 yards / 24 mm by 33 m

TAPE COLORS

The permanent double-sided tape is available in clear (transparent).

WHO USES THE TAPE

The tape is most commonly used by:

- sign companies
- plexiglass installers
- insulation companies
- contractors who use polyester film
- interior decorators and designers

ECHOtape PART NUMBER

The part number for this tape is DC-M012P.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape



should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

Clear Double Sided Polyester Tape for General Purpose Mounting & Bonding

DC-M158A is the perfect permanent double-sided tape for everyday applications around the office, warehouse, workshop, or classroom. The aggressive, acrylic adhesive bonds to virtually any surface, and on hard surfaces, you can reposition the tape within 60 seconds of application. Designed for lightweight mounting and bonding, the double-sided tape can be applied to textiles, foils, films, papers, plastic, metal, and more!

APPLICATIONS FOR THE TAPE

The most common applications for the permanent double-sided tape include:

- permanent bonding of papers, films, foils, textiles, leather, plastic, and metal
- general assembly of decorative parts
- temporary bonding to keep items in place prior to fastening them
- bonding textiles and leather prior to sewing

FEATURES OF THE TAPE

Features of the permanent double-sided tape include:

- fast-grabbing adhesive sticks well from the onset



- can reposition the tape within 60 seconds (but only on hard surfaces)
- adheres well to a variety of surfaces
- polyester carrier is flexible and conforms to many surfaces
- can tear the tape by hand
- performs well across a broad range of temperatures

TAPE ADHESIVE

The tape has an aggressive, high-tack acrylic adhesive.

WEATHER RESISTANCE

The permanent double-sided tape performs well across a wide range of temperatures.

TAPE SIZES

The permanent double-sided tape is available in the following sizes:

- 1 inch by 55 yards / 24 mm by 50 m
- 2 inches by 55 yards / 48 mm by 50 m

TAPE COLORS

The permanent double-sided tape is available in clear (transparent).

WHO USES THE TAPE

The tape is most commonly used in:

- offices
- warehouses
- workshops

- classrooms
- sewing workrooms

ECHOtape PART NUMBER

The part number for this tape is DC-M158A.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth

ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product

is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

All Weather/Cold Weather Double Sided Polyester Tape

DC-M194A is a high-performance, double-sided polyester film tape, designed specifically to work well in cold weather temperatures. Often used in commercial construction and metal building insulation applications, the double-sided PET tape is also versatile enough for a broad range of environmental conditions.

APPLICATIONS FOR THE TAPE

The most common applications for the double-sided polyester tape (PET tape) include:

- mounting insulation
- creating lap seals on laminated insulation, reflective insulation, and jacketing insulation

- permanently bonding foams, plastics, metals, and composite materials
- mounting smooth surface substrates in cold temperatures (such as freezers)

FEATURES OF THE TAPE

Features of the double-sided polyester tape (PET tape) include:

- superior holding power
- bonds well to a variety of surfaces
- specially formulated as a cold weather adhesive tape
- polyester (PET) carrier allows for UV resistance
- can tear the tape by hand
- can apply the tape by hand or with a machine

TAPE ADHESIVE

The double-sided polyester film tape (PET tape) tape is coated with a specially engineered acrylic adhesive that's designed to work exceptionally well in cold temperatures.

WEATHER RESISTANCE

The PET tape is an all-weather and cold temperature tape:

- specifically designed for extremely cold weather
- can be used indoors and outdoors
- UV resistant

TAPE SIZES

The polyester film tape (PET tape) is available in the



following sizes:

- 1 inch by 60 yards / 24 mm by 55 m
- 1.5 inches by 60 yards / 36 mm by 55 m
- 2 inches by 60 yards / 48 mm by 55 m

TAPE COLORS

The high-performance, polyester film tape (PET tape) is transparent.

WHO USES THE TAPE

The tape is most commonly used by:

- metal building insulation contractors
- commercial construction contractors

ECHOtape PART NUMBER

The part number for this tape is DC-M194A.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

General Purpose Clear Double

Sided Tape for Mounting Bonding (Paper)

DC-T274A is a general-purpose, double-sided tape that can be used for everyday applications around the office, warehouse, workshop, or classroom. Able to stick to almost any surface, this fast-grabbing, clear tape works well for lightweight mounting and bonding applications to textiles, foils, films, papers, plastic, metal, and more.

APPLICATIONS FOR THE TAPE

The most common applications for the double-sided tape include:

- permanent bonding of papers, films, foils, textiles, leather, plastic, and metal
- general assembly of decorative parts
- temporary bonding to keep items in place prior to fastening them
- bonding textiles and leather prior to sewing

FEATURES OF THE TAPE

Features of the double-sided tape include:

- fast-grabbing adhesive sticks well from the onset
- adheres well to a variety of surfaces
- flexible enough to conform to many surfaces
- can tear the tape by hand
- easy to remove the paper liner



TAPE ADHESIVE

The tape has an aggressive, high-tack acrylic adhesive.

TAPE SIZES

The double-sided tape is available in the following sizes:

- 1/2 inch by 55 yards / 12 mm by 50 m
- 3/4 inch by 55 yards / 18 mm by 50 m
- 1 inch by 55 yards / 24 mm by 50 m
- 2 inches by 55 yards / 48 mm by 50 m

TAPE COLORS

The double-sided tape is available in frosted clear.

WHO USES THE TAPE

The tape is most commonly used in:

- offices
- warehouses
- workshops
- classrooms
- sewing workrooms

ECHOtape PART NUMBER

The part number for this tape is DC-T274A.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords



- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

White Double Sided Tape for Permanent Mounting & Bonding

DC-U032A is an extremely aggressive and strong double-sided mounting tape that is designed for permanent bonding and will stick to just about any surface.

APPLICATIONS FOR THE TAPE

The most common applications for the permanent, double-sided mounting tape include:

- permanent bonding of metal, plastic, rubber, plexiglass, and wood
- mounting small to medium, lightweight indoor and outdoor signs
- mounting name plates
- mounting decorative trim
- bonding applications where other tapes might not adhere properly

FEATURES OF THE TAPE

Features of the permanent, double-sided mounting tape include:

- superior holding power (from the onset)
- sticks well to smooth surfaces (such as steel and plastic)



-
- adheres to rough and textured surfaces (such as wood)
 - conforms to most surfaces
 - easy to apply (the tape can be easily removed from its liner)
 - designed to work at room temperature, the tape can also perform for medium heat applications

TAPE ADHESIVE

The tape has an acrylic adhesive.

WEATHER RESISTANCE

The permanent, double-sided mounting tape is weather resistant:

- can be used indoors and outdoors
- resistant to extreme weather and other environmental conditions

TAPE SIZES

The permanent, double-sided mounting tape is available in the following sizes:

- 1/2 inch by 54.6 yards / 12 mm by 50 m
- 3/4 inch by 54.6 yards / 18 mm by 50 m
- 1 inch by 54.6 yards / 24 mm by 50 m
- 2 inches by 54.6 yards / 48 mm by 50 m

TAPE COLORS

The permanent, double-sided mounting tape is available in white.



WHO USES THE TAPE

The tape is most commonly used by:

- construction professionals
- flooring contractors
- insulation contractors
- handymen
- sign makers
- interior decorators and designers

ECHOtape PART NUMBER

The part number for this tape is DC-U032A.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection

- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The

values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

Clear Double Sided Tape for Permanent Mounting & Bonding

DC-U101A is double-sided UPVC tape that incorporates a high-tack and high-peel acrylic adhesive system. This unique UPVC tape is often used for product assembly, difficult bonding and splicing applications, and lamination on a variety of materials (including EPDM rubber, plastic, glass, and urethane foams).



APPLICATIONS FOR THE TAPE

The most common applications for the double-sided UPVC tape include:

- product assembly
- difficult bonding and splicing applications
- lamination to EPDM rubber, plastic, glass, and urethane foams

FEATURES OF THE TAPE

Features of the double-sided UPVC tape include:

- exceptionally high-tack and high-peel
- high-adhesive mass helps fill gaps
- UPVC film allows conformability
- adheres well to ether foams and ester foams
- bonds well to rough surfaces and porous surfaces
- excellent resistance to environmental extremes
- water resistant

TAPE ADHESIVE

The tape incorporates an exceptionally high-tack and high-peel acrylic adhesive system.

WEATHER RESISTANCE

The double-sided UPVC tape is weather resistant:

- excellent resistance to environmental extremes
- water resistant
- to achieve best results, recommended application temperature is 65 degrees Fahrenheit / 18 degrees Celsius



TAPE SIZES

The double-sided UPVC tape is available in the following sizes:

- 1/2 inch by 60 yards / 12 mm by 55 m
- 1 inch by 60 yards / 24 mm by 55 m
- 2 inches by 60 yards / 48 mm by 50 m

TAPE COLORS

The double-sided UPVC tape is available in clear (transparent).

WHO USES THE TAPE

The tape is most commonly used in:

- product assembly
- bonding and splicing
- manufacturing
- industrial environments
- construction and building
- electronics

ECHOtape PART NUMBER

The part number for this tape is DC-U101A.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords



- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

Double Sided Removable Carpet Tape

DC-W18FF is an extremely effective double-sided, removable carpet tape, with a strong adhesive that won't leave behind residue. The carpet tape is ideal for professionals who manage trade shows, conventions, and other large events that require carpeting and other types of temporary flooring to be quickly laid down and then easily removed.

And these aren't the only uses for this unique removable tape! It can also be used for construction and industrial mounting applications (for holding vapor barrier film, for mounting film for construction processes, for printing plates in industrial print packaging, and more).

APPLICATIONS FOR THE TAPE

The most common applications for the double-sided, removable carpet tape include:

- laying down carpet and other types of temporary flooring
- holding vapor barrier film in place when encapsulating crawl spaces
- mounting film when creating clean rooms or containment rooms
- mounting film for demolition and remediation processes

- mounting printing plates for industrial print packaging applications

FEATURES OF THE TAPE

Features of the double-sided, removable carpet tape include:

- aggressive adhesive on the liner side of the tape
- especially suited for adhesion to carpet
- adhesive on the exposed side of the tape leaves no residue when removed
- easy release poly liner
- fast to apply and easy to use

TAPE ADHESIVE

The tape has a rubber adhesive.

WEATHER RESISTANCE

The double-sided, removable carpet tape is designed for indoor use.

TAPE SIZES

The double-sided, removable carpet tape is available in the following sizes:

- 2 inches by 36 yards / 48 mm x 33 m
- 2.75 inches by 36 yards / 72 mm x 33 m

TAPE COLORS

The double-sided, removable carpet tape is available in beige.



WHO USES THE TAPE

The tape is most commonly used by:

- trade show contractors
- convention contractors
- event organizers
- construction contractors
- printers who specialize in industrial print packaging

ECHOtape PART NUMBER

The part number for this tape is DC-W188F.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong

- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may

vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

High Strength Kraft Flatback Tape

FB-K4329 is a strong flat back tape designed primarily for splicing and tabbing but also can be used for various packaging applications. It is engineered for a wide range of humidity and temperature conditions and sticks to most surfaces. This product complies with the Federal Food, Drug and Cosmetic Act, CFR Title 21, Subpart B, par. 175.105 (which covers the use of pressure-sensitive adhesives and tapes for

`indirect contact' food packaging such and box sealing).

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils

ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not

otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

High Tensile Kraft Flatback Tape

FB-K4347 is strong Kraft flatback tape that's designed primarily for splicing and tabbing applications, but also works well for a wide range of packaging applications (including food packaging). The high tensile Kraft tape sticks to most surfaces and is engineered to perform in a wide range of humidity and temperature conditions.

APPLICATIONS FOR THE TAPE

The most common applications for the high tensile Kraft flatback tape include:

- splicing and holding applications
- core starting and tabbing applications
- sealing cartons and boxes
- paper packaging
- food packaging (the tape complies with the section of



the Federal Food, Drug, and Cosmetic Act that covers the use of pressure-sensitive adhesives and tapes for “indirect contact” food packaging and box sealing)

FEATURES OF THE TAPE

Features of the high tensile Kraft flatback tape include:

- specially formulated adhesive provides excellent adhesion to heavy Kraft paper and many other surfaces
- tape can be torn by hand
- tape unwinds smoothly and is easy to apply
- extensible paper on the tape provides strength and flexibility
- performs well in a variety of temperature and humidity conditions

TAPE ADHESIVE

The tape has a rubber adhesive.

WEATHER RESISTANCE

The high tensile Kraft tape works well in a wide range of humidity and temperature conditions.

TAPE SIZES

The high tensile Kraft tape is available in the following sizes:

- 1 inch by 55 yards / 24 mm x 50 m
- 2 inches by 55 yards / 48 mm x 50 m
- 2.75 inches by 55 yards / 72 mm x 50 m

TAPE COLORS

The high tensile Kraft flatback tape is available in brown.

WHO USES THE TAPE

The tape is most commonly used by:

- commercial printers
- manufacturers (pulp, paper, corrugated board)
- silk screening companies
- picture framing companies
- packaging companies
- distribution companies / shipping companies

ECHOtape PART NUMBER

The part number for this tape is FB-K4347.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind

- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

Single Sided Thermal Break Tape (1/4" and 1/8" thick)

F0-V2344 and F0-V2348 are single-sided thermal break tapes, designed to reduce thermal bridging on outer and inner framing in metal buildings. Available in 1/4 inch and 1/8 inch thicknesses, the tape has excellent holding power and high-

load capability.

APPLICATIONS FOR THE TAPE

The most common applications for the single-sided thermal break tape include:

- create a vapor seal where large gaps occur
- create a lap joint seal on corrugated metal building panels or prefabricated wall panels
- create a flash break on building purlins and girt flanges
- maintain a seal in high movement joints

FEATURES OF THE TAPE

Features of the single-sided thermal break tape include:

- adheres strongly to smooth and rough surfaces (including corrugated metal)
- easy to apply
- sticks quickly (which speeds up application)
- conforms well to irregular surfaces
- easy to die-cut for custom sizing
- the paper release liner protects the adhesive from contaminants when cutting the tape to specific lengths

TAPE ADHESIVE

The tape has an acrylic adhesive.

TAPE SIZES

The single-sided thermal break tape is available in the



following sizes:

- 2 inches by 50 feet (1/4 inch thick)
- 3 inches by 50 feet (1/4 inch thick)
- 2 inches by 75 feet (1/8 inch thick)
- 3 inches by 75 feet (1/8 inch thick)

TAPE COLORS

The single-sided thermal break tape is available in gray.

WHO USES THE TAPE

The tape is most commonly used by:

- construction professionals
- building contractors
- insulation contractors
- metal building specialists

ECHOtape PART NUMBER

The part numbers for this tape are F0-V2344 (1/4 inch thickness) and F0-V2348 (1/8 inch thickness).

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape



should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

All Weather Lamtec WMP-VR Facing Tape

FS-G7731 is an all-weather, facing tape primarily used to seal and seam Lamtec WMP-VR faced insulation that's used in metal buildings. Easy to apply and quick to stick, the Lamtec WMP-VR facing tape delivers a strong bond, even at cold temperatures.

APPLICATIONS FOR THE TAPE

The Lamtec WMP-VR facing tape is used to:

- seam and join Lamtec WMP-VR faced insulation
- repair tears on Lamtec WMP-VR faced insulation

FEATURES OF THE TAPE

Features of the Lamtec WMP-VR facing tape include:

- quick to stick
- creates a strong bond
- performs well across a broad range of temperatures (including cold temperatures)
- excellent vapor barrier
- low WVTR (water vapor transmission rate)
- paper liner is easy to remove
- can be cut to specific lengths for use in tight areas

TAPE ADHESIVE

The Lamtec WMP-VR facing tape has a cold-weather, acrylic adhesive.



WEATHER RESISTANCE

The Lamtec WMP-VR tape is weather resistant:

- works well in cold weather – bonds well at low temperature
- excellent vapor barrier
- low WVTR (water vapor transmission rate)

TAPE SIZES

The Lamtec WMP-VR facing tape is available in the following size:

- 2.75 inches by 50 yards / 72 mm x 46 m

TAPE COLORS

The Lamtec WMP-VR facing tape is available in white and black.

WHO USES THE TAPE

The tape is most commonly used by:

- metal building insulation contractors

ECHOtape PART NUMBER

The part number for this tape is FS-G7731.

Note that Lamtec and WMP are registered trademarks of Lamtec Corporation.

x-APPLICATIONS



- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in

COLOR	Black
-------	-------

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract,

negligence, warranty or strict liability.

All Weather Lamtec WMP-VR-R Plus Facing Tape

FS-G7732 is an adhesive tape used primarily to seal and seam Lamtec WMP-VR-R Plus faced insulation that's used in metal buildings. This facing tape is coated with a high-performance, cold weather acrylic adhesive that offers a quick stick, provides a strong bond, and performs exceptionally well at low temperatures.

APPLICATIONS FOR THE TAPE

The Lamtec WMP-VR-R facing tape is used to:

- seam and join Lamtec WMP-VR-R faced insulation
- repair tears on Lamtec WMP-VR-R faced insulation

FEATURES OF THE TAPE

Features of the Lamtec WMP-VR-R facing tape include:

- quick to stick
- creates a strong bond
- performs well across a broad range of temperatures (including cold temperatures)
- excellent vapor barrier



- low WVTR (water vapor transmission rate)
- paper liner is easy to remove
- can be cut to specific lengths for use in tight areas

TAPE ADHESIVE

The Lamtec WMP-VR-R facing tape has a cold-weather, acrylic adhesive.

WEATHER RESISTANCE

The Lamtec WMP-VR-R tape is weather resistant:

- works well in cold weather – bonds well at low temperatures
- excellent vapor barrier
- low WVTR (water vapor transmission rate)

TAPE SIZES

The Lamtec WMP-VR-R facing tape is available in the following size:

- 2.75 inches by 50 yards / 72 mm x 46 m

TAPE COLORS

The Lamtec WMP-VR-R facing tape is available in black and white.

WHO USES THE TAPE

The tape is most commonly used by:

- metal building insulation contractors

ECHOtape PART NUMBER

The part number for this tape is FS-G7732.



Note that Lamtec and WMP are registered trademarks of Lamtec Corporation.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils

ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not

otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

All Weather Lamtec WMP-10/PSK Facing Tape

FS-G7735 is an adhesive tape used primarily to seal and seam Lamtec WMP-10/PSK faced insulation that's used in metal buildings. This facing tape is coated with a high-performance, cold weather acrylic adhesive that has a superior quick stick, creates a strong bond, and performs exceptionally well in low temperatures.

APPLICATIONS FOR THE TAPE

The Lamtec WMP-10/PSK facing tape is used to:

- seam and join Lamtec WMP-10/PSK faced insulation
- repair tears on Lamtec WMP-10/PSK faced insulation

FEATURES OF THE TAPE

Features of the Lamtec WMP-10/PSK facing tape include:

- quick to stick



- creates a strong bond
- performs well across a broad range of temperatures (including cold temperatures)
- excellent vapor barrier
- low WVTR (water vapor transmission rate)
- paper liner is easy to remove
- can be cut to specific lengths for use in tight areas

TAPE ADHESIVE

The Lamtec WMP-10/PSK facing tape has a cold-weather, acrylic adhesive.

WEATHER RESISTANCE

The Lamtec WMP-10/PSK facing tape is weather resistant:

- works well in cold weather – bonds well at low temperatures
- excellent vapor barrier
- low WVTR (water vapor transmission rate)

TAPE SIZES

The Lamtec WMP-10/PSK facing tape is available in the following size:

- 2.75 inches by 50 yards / 72 mm x 46 m

TAPE COLORS

The Lamtec WMP-10/PSK facing tape is available in black and white.

WHO USES THE TAPE

The tape is most commonly used by:



- metal building insulation contractors

ECHOtape PART NUMBER

The part number for this tape is FS-G7735.

Note that Lamtec and WMP are registered trademarks of Lamtec Corporation.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or

otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

All Weather Lamtec WMP-50 Metal Facing Tape

FS-G7736 is an adhesive tape used primarily to seal and seam Lamtec WMP-50 faced insulation that's used in metal buildings. This metal facing tape is coated with a high-performance, cold weather acrylic adhesive that offers a superior quick stick. Able to create a strong bond, the tape performs very well at low temperatures.

APPLICATIONS FOR THE TAPE

The Lamtec WMP-50 metal facing tape is used to:

- seam and join Lamtec WMP-50 faced insulation



- repair tears on Lamtec WMP-50 faced insulation

FEATURES OF THE TAPE

Features of the Lamtec WMP-50 metal facing tape include:

- quick to stick
- creates a strong bond
- performs well across a broad range of temperatures (including cold temperatures)
- excellent vapor barrier
- low WVTR (water vapor transmission rate)
- paper liner is easy to remove
- can be cut to specific lengths for use in tight areas

TAPE ADHESIVE

The Lamtec WMP-50 metal facing tape has a cold-weather, acrylic adhesive.

WEATHER RESISTANCE

The Lamtec WMP-50 metal facing tape is weather resistant:

- works well in cold weather – bonds well at low temperatures
- excellent vapor barrier
- low WVTR (water vapor transmission rate)

TAPE SIZES

The Lamtec WMP-50 metal facing tape is available in the following size:

- 2.75 inches by 50 yards / 72 mm x 46 m



TAPE COLORS

The Lamtec WMP-50 metal facing tape is available in white.

WHO USES THE TAPE

The tape is most commonly used by:

- metal building insulation contractors

ECHOtape PART NUMBER

The part number for this tape is FS-G7736.

Note that Lamtec and WMP are registered trademarks of Lamtec Corporation.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection



- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The

values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

All Weather EHP VR-R Plus Facing Tape

FS-G7739 is an adhesive tape used primarily to seal and seam EHP VR-R Plus faced insulation that's used in metal buildings. The initial quick stick of this all-weather facing tape helps speed up application. The tape creates a superior bond and works well at low temperatures.

APPLICATIONS FOR THE TAPE

The EHP VR-R Plus facing tape is used to:

- seam and join EHP VR-R Plus faced insulation
- repair tears on EHP VR-R Plus faced insulation

FEATURES OF THE TAPE

Features of the EHP VR-R Plus facing tape include:

- quick to stick
- creates a strong bond
- performs well across a broad range of temperatures (including cold temperatures)
- excellent vapor barrier
- low WVTR (water vapor transmission rate)
- paper liner is easy to remove
- can be cut to specific lengths for use in tight areas

TAPE ADHESIVE

The EHP VR-R Plus facing tape has a cold-weather, acrylic adhesive.

WEATHER RESISTANCE

The EHP VR-R Plus facing tape is weather resistant:

- works well in cold weather – bonds well at low temperatures
- excellent vapor barrier
- low WVTR (water vapor transmission rate)

TAPE SIZES

The EHP VR-R Plus facing tape is available in the following



size:

- 2.75 inches by 50 yards / 72 mm x 46 m

TAPE COLORS

The Lamtec EHP VR-R Plus facing tape is available in white.

WHO USES THE TAPE

The tape is most commonly used by:

- metal building insulation contractors

ECHOtape PART NUMBER

The part number for this tape is FS-G7739.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection



- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The

values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

All Weather ASJ Kraft Insulation Facing Tape

FS-J7744 is a high-performance, all weather ASJ Kraft insulation facing tape that's primarily used to seal and seam ASJ faced duct board and fiberglass pipe insulation. Coated with a flame-retardant, cold-weather acrylic adhesive, this insulation facing tape provides a strong and secure bond on a variety of surfaces and textures.



APPLICATIONS FOR THE TAPE

The most common applications for the ASJ Kraft insulation facing tape include:

- sealing and seaming ASJ faced duct board
- sealing and seaming fiberglass pipe insulation
- repairing tears in white Kraft scrim foil backed insulation

FEATURES OF THE TAPE

Features of the ASJ Kraft insulation facing tape include:

- initial quick stick
- creates a strong bond to a variety of surfaces and textures
- paper liner is easy to remove and protects the adhesive from contaminants when you need to cut the tape to specific lengths
- designed for tear-resistant sealing
- mold resistant
- coated with a flame-retardant acrylic adhesive
- UL 723 classified

TAPE ADHESIVE

The tape has an acrylic adhesive.

WEATHER RESISTANCE

The all weather insulation facing tape works well in a wide range of temperatures (can be applied in -4°F to 104°F weather).



TAPE SIZES

The ASJ Kraft insulation facing tape is available in the following size:

- 2.75 inches by 50 yards / 72 mm x 46 m

TAPE COLORS

The all weather ASJ Kraft insulation facing tape is available in white.

WHO USES THE TAPE

The tape is most commonly used by:

- mechanical insulation contractors
- HVAC contractors

ECHOtape PART NUMBER

The part number for this tape is FS-J7744.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays



FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and

free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

All Weather ASJ Poly Insulation Facing Tape

FS-J7754 is a high-performance, all weather ASJ poly insulation facing tape that's primarily used to seal and seam ASJ faced duct board and fiberglass pipe insulation. Coated with a flame-retardant, cold-weather acrylic adhesive, this insulation facing tape provides a strong and secure bond on a variety of surfaces and textures.

APPLICATIONS FOR THE TAPE

The most common applications for the ASJ poly insulation facing tape include:

- sealing and seaming ASJ faced duct board
- sealing and seaming fiberglass pipe insulation
- repairing tears in white poly scrim foil backed insulation

FEATURES OF THE TAPE

Features of the ASJ poly insulation facing tape include:

- initial quick stick
- creates a strong bond to a variety of surfaces and textures
- paper liner is easy to remove and protects the adhesive from contaminants when you need to cut the tape to specific lengths
- designed for tear-resistant sealing



- mold resistant
- coated with a flame-retardant acrylic adhesive
- UL 723 classified

TAPE ADHESIVE

The tape has an acrylic adhesive.

WEATHER RESISTANCE

The all weather insulation facing tape works well in a wide range of temperatures (can be applied in -4°F to 104°F weather).

TAPE SIZES

The ASJ poly insulation facing tape is available in the following size:

- 2.75 inches by 50 yards / 72 mm x 46 m

TAPE COLORS

The all weather ASJ poly insulation facing tape is available in white.

WHO USES THE TAPE

The tape is most commonly used by:

- mechanical insulation contractors
- HVAC contractors

ECHOtape PART NUMBER

The part number for this tape is FS-J7754.



x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in

ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal

theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

All Weather FSK (Foil/Scrim/Kraft) Insulation Facing Tape

FS-K7751 is a high-performance, all weather tape that's primarily used to seal foil-faced insulation (such as FSK-faced fiberglass duct board and blanket systems). Coated with a flame-retardant, cold-weather acrylic adhesive, this insulation facing tape provides a strong and secure bond on a variety of surfaces and textures.

APPLICATIONS FOR THE TAPE

The most common applications for the FSK insulation facing tape include:

- sealing and seaming FSK (Foil-Scrim-Kraft) laminated board
- sealing and seaming FSK (Foil-Scrim-Kraft) jacketing insulation
- repairing tears in foil faced insulation



FEATURES OF THE TAPE

Features of the FSK insulation facing tape include:

- initial quick stick
- creates a strong bond to a variety of surfaces and textures
- paper liner is easy to remove and protects the adhesive from contaminants when you need to cut the tape to specific lengths
- designed for tear-resistant sealing
- mold resistant
- coated with a flame-retardant acrylic adhesive
- an epoxy resin coating on the insulation tape helps protect the surface from corrosion caused by moisture.
- UL 723 classified

TAPE ADHESIVE

The tape has an acrylic adhesive.

WEATHER RESISTANCE

The all weather insulation facing tape works well in a wide range of temperatures (can be applied in -4°F to 104°F weather).

TAPE SIZES

The FSK insulation facing tape is available in the following sizes:

- 2.75 inches by 50 yards / 72 mm x 46 m
- 3.75 inches by 50 yards / 96 mm x 46 m



TAPE COLORS

The all weather FSK insulation facing tape is available in silver.

WHO USES THE TAPE

The tape is most commonly used by:

- mechanical insulation contractors
- HVAC contractors

ECHOtape PART NUMBER

The part number for this tape is FS-K7751.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection



- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The

values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

Double Sided Foam Glazing Tape

GL-N0708 and GL-N0716 are double-sided, foam glazing tapes that are designed for window glazing applications. Available in 1/8 inch and 1/16 inch thicknesses, the tape is coated on each side with a high-tack acrylic adhesive that's quick to set and continues to strengthen over time. Made with a soft and flexible polyethylene foam, the double-sided glazing tape



adapts to a variety of textured surfaces.

APPLICATIONS FOR THE TAPE

The most common applications for the double-sided, foam glazing tape include:

- window glazing applications on aluminum window framing
- window glazing applications on PVC window framing
- bonding and mounting lightweight plastic
- bonding and mounting lightweight metal

FEATURES OF THE TAPE

Features of the double-sided, foam glazing tape include:

- seals well against water, dust, and light
- resistant to weather, temperature, UV, and oxidation
- flexible and soft, which makes it easy to adjust to a variety of textured surfaces
- sticks well from the onset
- acrylic adhesive continues to strengthen over time
- easy release poly liner
- AAMA certified (which makes it suitable for glazing applications)

TAPE ADHESIVE

The tape has an acrylic adhesive.

WEATHER RESISTANCE

The double-sided, foam glazing tape has excellent weather resistance, UV resistance, temperature resistance, and

oxidation resistance.

TAPE SIZES

The double-sided foam glazing tape is available in the following sizes:

- 1/8 inch thick: 3/8 inch by 75 feet / 10 mm x 23 m
- 1/16 inch thick: 1/3 inch by 150 feet / 9 mm x 46 m
- 1/16 inch thick: 3/8 inch by 150 feet / 10 mm x 46 m
- 1/16 inch thick: 1/2 inch by 150 feet / 12 mm x 46 m

TAPE COLORS

The double-sided, foam glazing tape is available in black and white.

WHO USES THE TAPE

The tape is most commonly used by:

- window contractors
- glass companies

ECHOtape PART NUMBER

The part numbers for this tape are GL-N0708 (1/8 inch thickness) and GL-N0716 (1/16 inch thickness).

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production



- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

Self-Adhesive Fiberglass Reinforcing Mesh Tape

ME-W8306 is a self-adhesive, fiberglass reinforcing mesh tape that's strong, yet flexible enough to adhere to contoured surfaces with ease. The tape is primarily used by stucco contractors to reinforce architectural foam shapes and trim profiles in outdoor stucco construction. The fiberglass mesh helps anchor the stucco to the molded shapes and profiles during the stucco application process. The tape is also often used to reinforce drywall joint compounds (pulling drywall joints).

APPLICATIONS FOR THE TAPE

The most common applications for the fiberglass reinforcing mesh tape include:

- reinforcing architectural foam shapes and trim profiles
- reinforcing drywall joint compound
- permanently hiding joints, cracks, and holes in stucco repairs
- permanently hiding joints, cracks, and holes in drywall repairs

FEATURES OF THE TAPE

Features of the self-adhesive fiberglass reinforcing mesh tape



include:

- easy to apply
- contours well around shapes
- tear-proof
- shrink-proof
- won't bubble
- improves the adherence of stucco to trim profiles and foam shapes

TAPE SIZES

The self-adhesive fiberglass reinforcing mesh tape is available in the following size:

- 36 inches by 150 feet / 914 mm x 46 m

TAPE COLORS

The self-adhesive fiberglass mesh tape is available in blue and white.

WHO USES THE TAPE

The tape is most commonly used by:

- stucco contractors
- drywall contractors
- general contractors

ECHOtape PART NUMBER

The part number for this tape is ME-W8306.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in

ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal

theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

Utility Grade General Purpose Paper Masking Tape

MK-K5417 is a utility grade masking tape (5.5 mils thick) that can be used for general purpose adhesion on a variety of substrates, materials, and surfaces. Easy to use and quick to stick, the masking tape is resistant to water and oil.

APPLICATIONS FOR THE TAPE

The most common applications for the masking tape include:

- packaging
- bundling
- holding
- splicing
- tabbing
- general purposes

FEATURES OF THE TAPE

Features of the utility-grade masking tape include:

- good adhesion on a variety of surfaces and materials



- flexible and easy to use
- excellent quick stick
- resistant to water and oil

TAPE ADHESIVE

The tape has a blended, rubber-based adhesive.

TAPE SIZES

The utility-grade masking tape is available in the following sizes:

- 1 inch by 60 yards / 24 mm x 55 m
- 2 inches by 60 yards / 48 mm x 55 m

TAPE COLORS

The utility-grade masking tape is available in tan.

WHO USES THE TAPE

The tape is most commonly used by:

- general contractors
- small businesses
- painters
- decorators

ECHOtape PART NUMBER

The part number for this tape is MK-K5417

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in

ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal



theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

Blue Painter's Paper Indoor/Outdoor Masking Tape (14 Day)

MK-K5497 is a high-performance blue painter's tape (5.1 mils thick) that can be used for most types of masking applications. Designed for indoor use and outdoor use, the blue painter's tape removes cleanly from most surfaces for up to 14 days. And in that time, the painter's tape won't dry out or lose its holding power.

APPLICATIONS FOR THE TAPE

The most common applications for the blue painter's tape include:

- masking for painting
- masking of drywall
- masking of wood trim
- masking of windows
- masking of hardwood floors and other flooring surfaces

FEATURES OF THE TAPE

Features of the blue painter's tape include:

- removes cleanly from most surfaces
- suitable for indoor use and outdoor use
- outdoor UV protection up to 14 days

TAPE ADHESIVE

The tape has a natural rubber (resin) adhesive.

WEATHER RESISTANCE

The blue painter's tape is suitable for outdoor use and has outdoor UV protection for up to 14 days.

TAPE SIZES

The blue painter's tape is available in the following size:

- 2 inches by 60 yards / 48 mm x 55 m

TAPE COLORS

The painter's tape is available in blue.

WHO USES THE TAPE

The tape is most commonly used by:

- painters
- general contractors

ECHOtape PART NUMBER

The part number for this tape is MK-K5497.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in



ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal

theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

All Weather White Aluminum Foil Tape

MT-A7729 is a high-strength, aluminum foil tape that's primarily used to seal joints for foam core insulation boards and to join and seam flexible air duct seams and connections. With a flame-retardant and cold-weather, acrylic adhesive, the aluminum foil tape provides good reliability across high and low temperatures. The tape also conforms well to a variety of surfaces and provides a strong bond.

APPLICATIONS FOR THE TAPE

The most common applications for the aluminum foil tape include:

- sealing lap joints
- providing a vapor seal on foil faced board
- joining and sealing flexible air duct seams and connections

FEATURES OF THE TAPE

Features of the aluminum foil tape include:

- initial quick stick
- conforms well to a variety of surfaces
- low MVTR (Moisture Vapor Transmission Rate)
- mold resistant
- paper liner is easy to remove and protects the adhesive from contaminants
- coated with a flame retardant, cold weather acrylic adhesive

TAPE ADHESIVE

The tape has an acrylic adhesive.

WEATHER RESISTANCE

The aluminum foil tape is weather resistant:

- cold weather acrylic adhesive
- good reliability across low and high temperatures

TAPE SIZES

The aluminum foil tape is available in the following size:

- 3 inches by 50 yards / 72 mm x 46 m

TAPE COLORS

The aluminum foil tape is available in off white.

WHO USES THE TAPE

The tape is most commonly used by:

- insulation contractors

- HVAC contractors
- general contractors
- appliance contractors
- automotive shops

ECHOtape PART NUMBER

The part number for this tape is MT-A7729.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a

particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

All Weather Aluminum Foil Tape

MT-A7772 is a high-strength, aluminum foil tape that's primarily used for vapor sealing fiberglass duct boards and FSK systems. The aluminum foil tape provides an excellent vapor seal and can be used for sealing and patching. The tape has a flame-retardant solvent acrylic adhesive and works well indoors and outdoors.

APPLICATIONS FOR THE TAPE

The most common applications for the aluminum foil tape include:

- sealing joints and seams of foil-faced insulation materials (UL 723 classified, CAN/ULC-S102)
- seaming foil faced insulation
- seaming FSK systems (Foil Scrim Kraft systems)

FEATURES OF THE TAPE

Features of the aluminum foil tape include:

- initial quick stick
- outstanding sealing and patching performance
- maximum conformability
- low MVTR (Moisture Vapor Transmission Rate)
- mold resistant
- paper liner is easy to remove
- coated with a flame-retardant solvent acrylic adhesive

TAPE ADHESIVE

The tape has an acrylic adhesive.

WEATHER RESISTANCE

The aluminum foil tape is weather resistant:

- can be used indoors and outdoors
- superior stick at normal operating temperatures
- great performance at low temperatures

TAPE SIZES

The aluminum foil tape is available in the following sizes:

- 2 inches by 50 yards / 48 mm x 46 m



- 3 inches by 50 yards / 72 mm x 46 m

TAPE COLORS

The aluminum foil tape is available in silver.

WHO USES THE TAPE

The tape is most commonly used by:

- insulation contractors
- HVAC contractors
- general contractors
- appliance contractors
- automotive shops

ECHOtape PART NUMBER

The part number for this tape is MT-A7772.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue

- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

All Weather Construction Seaming Tape

PE-M4535 is an all-weather construction seaming tape that's available in three colors. This next-generation seam tape is

engineered to adhere to a wide range of building materials and surfaces. Formulated with a proprietary cold-weather adhesive and an advanced polyester backing, the seam tape is extremely strong and easy to apply. You can use this seam tape on just about anything, including: house wrap, sheathing, vapor barriers, underlayments, and exterior and rigid insulation.

APPLICATIONS FOR THE TAPE

The most common applications for the seam tape include:

- seaming the building envelope
- seaming house wrap
- seaming insulation (including polyisocyanurate insulation and reflective insulation)
- seaming exterior sheathing
- seaming vapor barriers (including polyethylene films)
- seaming flooring underlayments
- seaming roofing underlayments

FEATURES OF THE TAPE

Features of the seam tape include:

- strong, with durable holding power
- conforms well to a variety of irregular surfaces
- instant tack, on a wide range of surfaces and materials
- tack strengthens over time
- made from an advanced polyester film (PET)
- water resistant and moisture resistant
- excellent cold weather adhesion
- UV resistant (up to 90 days)



- can tear the tape by hand
- colors allow for easy inspection

TAPE ADHESIVE

The tape has an acrylic adhesive.

WEATHER RESISTANCE

The seam tape is weather resistant:

- excellent cold weather adhesion (to -4° F)
- minimum 90 day UV resistance
- water resistant and moisture resistant

TAPE SIZES

The seam tape is available in the following size:

- 2 inches by 55 yards / 48 mm x 50 m

TAPE COLORS

The seam tape is available in the following colors:

- red seam tape
- silver seam tape
- white seam tape

WHO USES THE TAPE

The tape is most commonly used by:

- general contractors
- insulation companies



ECHOtape PART NUMBER

The part number for this tape is PE-M4535.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber



THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for

Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

Self Adhesive Protective Film for Windows

PR-N3287 is a self-adhesive, protective film for windows that offers temporary protection against stucco, paint, and mortar overspray. This protective film is widely used by stucco contractors, painters, masons, builders, and remodelers.

APPLICATIONS FOR THE FILM

The most common applications for the protective film include protection for windows during:

- stucco work
- masonry and mortar work
- painting
- other construction tasks

FEATURES OF THE FILM

Features of the protective window film include:

- self-adhesive
- easy to unwind and apply by hand
- easy to remove
- removes cleanly (without leaving adhesive residue)
- UV resistant for up to 180 days, in all weather

FILM ADHESIVE

The film has an acrylic adhesive.

WEATHER RESISTANCE

The protective window film is UV resistant for up to 180 days, in all types of weather.

FILM SIZES

The window film is available in the following size:

- 24 inches by 600 yards / 610 mm x 183 m

FILM COLORS

The protective window film is available in blue or transparent.

WHO USES THE FILM

The window film is most commonly used by:

- stucco contractors
- painters

- masons
- general contractors
- builders
- remodelers

ECHOtape PART NUMBER

The part number for this film is PR-N3287.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a



particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

High Performance Indoor/Outdoor Double Sided Acrylic Foam Tape

UB-F3504 is a gray, heavy-duty, double-sided foam tape that's designed for demanding jobs! This double-sided tape has a high-performance, acrylic adhesive that's been engineered for permanent mounting and bonding to metal, plastics, and woods (including rough, textured, and painted surfaces). The double-sided foam tape is so strong that it's often used as an alternative to traditional fasteners. Designed for indoor and outdoor use, the tape offers outstanding resistance to hot



temperatures, cold temperatures, and extreme weather fluctuations.

APPLICATIONS FOR THE TAPE

The most common applications for the double-sided foam tape include:

- attaching automotive exterior trim parts
- attaching automotive side body moldings, claddings, roof ditch moldings, wheel flares, and tailgate appliques
- mounting muntin / SDL bars on wooden, metal, and vinyl doors
- mounting indoor signage (the tape can be used in place of a fastener)
- mounting outdoor signage (the tape can be used in place of a fastener)

FEATURES OF THE TAPE

Features of the double-sided foam tape include:

- adheres well to metal, wood, and plastics (including hard-to-stick plastics)
- adheres well to rough, textured, or painted surfaces
- strong enough to support heavier loads than typical double-sided tapes
- excellent temperature resistance
- highly flexible (sticks well to curved surfaces)
- easily adapts to a variety of surfaces
- good shock absorption properties



TAPE ADHESIVE

The tape has a high-performance acrylic adhesive.

WEATHER RESISTANCE

The double-sided foam tape is weather resistant:

- can be used indoors and outdoors
- resistant to heat and cold
- resistant to extreme weather fluctuations

TAPE SIZES

The double-sided foam tape is available in the following sizes:

- 1/3 inch by 36 yards / 9 mm x 33 m
- 1/2 inch by 36 yards / 12 mm x 33 m
- 3/4 inch by 36 yards / 18 mm x 33 m
- 1 inch by 36 yards / 24 mm x 33 m

TAPE COLORS

The double-sided foam tape is available in gray (with an easy-release red polyethylene film).

WHO USES THE TAPE

The tape is most commonly used by:

- auto repair shops
- auto body shops
- sign companies
- carpenters

- window and door installation specialists
- glass companies and glaziers
- general contractors
- handymen

ECHOtape PART NUMBER

The part number for this tape is UB-F3504.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a

particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

High Performance Indoor/Outdoor Double Sided Acrylic Foam Tape

UB-F3557 is a clear, heavy-duty, double-sided foam tape that's designed for demanding jobs! This double-sided tape has a high-performance, acrylic adhesive that's been engineered for permanent mounting and bonding to metal, plastics, and woods (including rough, textured, and painted surfaces). The double-sided foam tape is so strong that it's often used as an alternative to traditional fasteners. Designed for indoor and outdoor use, the tape offers outstanding resistance to hot



temperatures, cold temperatures, and extreme weather fluctuations.

APPLICATIONS FOR THE TAPE

The most common applications for the double-sided foam tape include:

- attaching automotive exterior trim parts
- attaching automotive side body moldings, claddings, roof ditch moldings, wheel flares, and tailgate appliques
- mounting muntin / SDL bars on wooden, metal, and vinyl doors
- mounting indoor signage (the tape can be used in place of a fastener)
- mounting outdoor signage (the tape can be used in place of a fastener)

FEATURES OF THE TAPE

Features of the double-sided foam tape include:

- adheres well to metal, wood, and plastics (including hard-to-stick plastics)
- adheres well to rough, textured, or painted surfaces
- strong enough to support heavier loads than typical double-sided tapes
- excellent temperature resistance
- highly flexible (sticks well to curved surfaces)
- easily adapts to a variety of surfaces
- good shock absorption properties



TAPE ADHESIVE

The tape has a high-performance acrylic adhesive.

WEATHER RESISTANCE

The double-sided foam tape is weather resistant:

- can be used indoors and outdoors
- resistant to heat and cold
- resistant to extreme weather fluctuations

TAPE SIZES

The double-sided foam tape is available in the following sizes:

- 1/2 inch by 36 yards / 12 mm x 33 m
- 1 inch by 36 yards / 24 mm x 33 m

TAPE COLORS

The double-sided foam tape is available in clear (with an easy-release red polyethylene film).

WHO USES THE TAPE

The tape is most commonly used by:

- auto repair shops
- auto body shops
- sign companies
- carpenters
- window and door installation specialists
- glass companies and glaziers

- general contractors
- handymen

ECHOtape PART NUMBER

The part number for this tape is UB-F3557.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
--------------	------------------------------

CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes

no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

High Performance White Vinyl Seaming Tape

VI-N6103 is a strong, single-sided, vinyl waterproof tape that bonds to most surfaces and works well across a wide range of temperatures. With a strong rubber adhesive, the white vinyl seaming tape is often used to seam polyethylene barriers for crawlspace containment and encapsulation, as well as underslab vapor barriers.

APPLICATIONS FOR THE TAPE

The most common applications for the white vinyl seaming tape include:

- seaming applications where waterproofing is required



-
- seaming polyethylene vapor barriers in crawlspace applications
 - seaming polyethylene barriers in underslab applications

FEATURES OF THE TAPE

Features of the white vinyl seaming tape include:

- excellent holding power and durability
- tough and flexible
- conforms well to a variety of surfaces
- superior low temperature bonding
- bonds well over a wide temperature range
- maintains a watertight seal in all weather conditions (if applied properly)
- can be repositioned

TAPE ADHESIVE

The tape has a rubber adhesive.

WEATHER RESISTANCE

The white vinyl seaming tape is weather resistant:

- bonds well in low temperatures
- bonds well over a wide temperature range
- maintains a watertight seal in all weather conditions (if applied properly)

TAPE SIZES

The white vinyl seaming tape is available in the following size:



- 3.75 inches by 210 feet / 96 mm x 64 m

TAPE COLORS

The vinyl seaming tape is available in white.

WHO USES THE TAPE

The tape is most commonly used by:

- basement and crawlspace contractors
- insulation contractors
- HVAC contractors
- flooring contractors
- general contractors
- builders

ECHOtape PART NUMBER

The part number for this tape is VI-N6103.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no

residue

- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

Multi Purpose No Residue Polyethylene Vinyl Tape

VI-N6120 is one of our most popular adhesive tapes, thanks to its versatility and consistent performance! Used extensively



by stucco contractors and mold and asbestos abatement contractors, this vinyl tape is made from an extra-strength polyethylene film, and it's coated with a high-tack synthetic rubber adhesive. The vinyl tape is available in several colors, and when it's removed within 7-10 days, it leaves little or no residue on most surfaces.

APPLICATIONS FOR THE TAPE

The most common applications for the polyethylene vinyl tape include:

- temporary holding
- general repairs
- masking windows and doors in stucco applications
- taping in containment rooms and clean rooms
- taping polyethylene films for mold and asbestos remediation and demolition
- seaming polyethylene film for underslab vapor barriers
- splicing polyethylene films during manufacturing
- color-coding and floor marking (for events, exhibits, and tradeshow)

FEATURES OF THE TAPE

Features of the polyethylene vinyl tape include:

- bonds well and conforms well to a variety of surfaces
- tough and flexible
- superior low temperature bonding
- works well over a wide temperature range
- waterproof backing material

- maintains a watertight seal in all weather conditions (if applied properly)
- on most surfaces, leaves little to no residue if the tape is removed within 7-10 days
- hangs and tears straight
- is easy to unwind
- holds strong, which prevents lifting
- can be torn by hand
- doesn't curl or splinter (which makes it easy to apply)

TAPE ADHESIVE

The tape has a synthetic rubber adhesive.

WEATHER RESISTANCE

The polyethylene vinyl tape is weather resistant:

- bonds well in low temperatures
- bonds well over a wide temperature range
- maintains a watertight seal in all weather conditions (if applied properly)

TAPE SIZES

The polyethylene vinyl tape is available in the following sizes:

- 2 inches by 60 yards / 48 mm x 55 m
- 3 inches by 60 yards / 72 mm x 55 m

TAPE COLORS

The polyethylene vinyl tape is available in black, blue, red,



white, and transparent.

WHO USES THE TAPE

The tape is most commonly used by:

- stucco contractors
- abatement companies
- asbestos removal companies
- mold remediation companies
- flooring contractors
- general contractors
- builders
- event, exhibit, and tradeshow contractors
- manufacturers

ECHOtape PART NUMBER

The part number for this tape is VI-N6120.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no

residue

- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECH0tape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECH0tape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

Resistant 30-Day Stucco Masking Tape

VI-N6149 is a UV resistant, red stucco tape. Trusted by professional stucco contractors, this polyethylene stucco tape

is used to protect and mask windows, door frames, and profiles during outdoor stucco applications. The stucco tape has a high-performance rubber adhesive that's designed to bond well to most surfaces and provide a watertight seal in a range of weather conditions. The stucco tape can be cleanly removed within 30 days, leaving no residue.

APPLICATIONS FOR THE TAPE

The most common applications for the polyethylene red stucco tape include:

- protecting and masking windows during outdoor stucco applications
- protecting and masking door frames during outdoor stucco applications
- protecting and masking profiles during outdoor stucco applications

FEATURES OF THE TAPE

Features of the polyethylene red stucco tape include:

- excellent holding power and durability
- bonds well to most surfaces
- conforms well to uneven surfaces
- clean removal within 30 days (leaving no residue)
- UV resistant
- provides a watertight seal in a variety of weather conditions
- hand tearable, leaving a clean edge



TAPE ADHESIVE

The tape has a high-performance rubber adhesive.

WEATHER RESISTANCE

The polyethylene red stucco tape is weather resistant:

- UV resistant
- maintains a watertight seal in all weather conditions (if applied properly)

TAPE SIZES

The polyethylene red stucco tape is available in the following size:

- 2 inches by 60 yards / 48 mm x 55 m

TAPE COLORS

The polyethylene stucco tape is available in red.

WHO USES THE TAPE

The tape is most commonly used by:

- stucco contractors
- general contractors
- builders

ECHOtape PART NUMBER

The part number for this tape is VI-N6149.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth
ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in

ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal

theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

Embossed Vinyl Seaming & Patching Tape

VI-V6460 is a single-sided, acrylic adhesive tape that's primarily used to seam and patch white vinyl insulation in metal buildings. The aggressive adhesive on this seaming and patching insulation tape makes it work well in cold and hot temperatures, high humidity, and other environmental conditions. The insulation tape has an easy-to-remove paper liner, and it's easy to cut to specific lengths.

APPLICATIONS FOR THE TAPE

The most common applications for the seaming and patching insulation tape include:

- seaming of vinyl faced insulation
- patching of vinyl faced insulation

FEATURES OF THE TAPE

Features of the seaming and patching insulation tape include:

- outstanding performance across a variety of temperature

ranges and environmental conditions

- easy to remove paper liner
- paper liner protects the adhesive from contaminants when you're cutting the tape to specific lengths
- sticks quickly
- conforms well to a variety of surfaces

TAPE ADHESIVE

The tape has an acrylic adhesive.

WEATHER RESISTANCE

The seaming and patching insulation tape:

- works well across a wide variety of temperature ranges
- works well in high heat and high humidity conditions
- bonds well in low temperatures

TAPE COLORS

The seaming and patching insulation tape is available in white.

WHO USES THE TAPE

The tape is most commonly used by:

- insulation contractors
- metal building contractors
- HVAC contractors
- roofing contractors
- maintenance workers
- general contractors



- builders

ECHOtape PART NUMBER

The part number for this tape is VI-V6460.

x-APPLICATIONS

- Use to secure and protect overhead lighting and audio wires for entertainment applications including concerts, trade shows, plays and video production
- Use to tape down power cords
- Use for artwork, framing, book binding and displays

FEATURES & BENEFITS

- Works like duct tape but removes cleanly leaving no residue
- Easy to unwind
- Can be torn by hand
- Can be used indoor and outdoor
- Matte surface minimizes glare and light reflection
- Durable and strong
- Waterproof and water resistant
- Proven performance, used by professionals for years

Technical Information

Sizes	1.89 in x 60 yd 48mm x 55m
CARRIER	Cloth

ADHESIVE	Rubber
THICKNESS	10.5 mils
ADHESIVE THICKNESS	3.75 mils
TENSILE	45 lbs/in
ADHESION	25 oz/in
COLOR	Black

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product

is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the 1.800.461.8273 | info@echotape.com | echotape.com legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.