

DESCRIPTION

RE-K7333 is a single-sided, repulpable adhesive tape (3.5 mils) that works well for tabbing and temporary or permanent butt splices of uncoated and coated lightweight paper. The tape has high adhesion, high heat resistance, and very high tensile strength. The repulpable tape is coated with a water soluble, modified acrylic adhesive. Available in white, this tape meets the TAPPI 213 repulpable standard.

APPLICATIONS

- Tabbing and core starting heavyweight uncoated and coated paper
- Temporary or permanent butt splices of heavyweight uncoated and coated paper

FEATURES & BENEFITS

- Very high tensile strength
- High adhesion
- High heat resistance
- Repulpable
- Meets the TAPPI 213 repulpable standard

PRODUCT CONSTRUCTION

Backing	White Siliconized Repulpable Paper
Adhesive	Water Soluble Acrylic

TECHNICAL DATA

Thickness	3.5 mils
Tensile	28.5 lbs/in
Adhesion	≥ 35 oz/in
Maximum Operating Temperature	392°F (200°C)
Elongation	5%
Color	White, Blue
Sizes	Please call for sizes and availability

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOTape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOTape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOTape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.