



High Performance Double Sided Tissue Splicing Tape **SC-211HT**

DESCRIPTION

SC-211HT is a 3.9 mils double-sided, non-woven tissue splicing tape. This high-performance splicing tape has an aggressive, high tack, heat resistant, pressure-sensitive adhesive. Ideally suited for high-speed flying splice applications, the tissue tape provides excellent stick and holding power and is easy to tear by hand. The double-sided tissue splicing tape has a fast-grabbing acrylic adhesive. The tissue carrier is flexible and conformable, which adds dimensional stability. Available in white, this tape is commonly used for high-speed splicing of papers, films, foils, and corrugated fiber board, as well as general bonding.

APPLICATIONS

- High-speed splicing of papers, films, foils, and corrugated fiber board
- Decorative parts
- General bonding

FEATURES & BENEFITS

- Fast-grabbing adhesive
- Excellent holding power
- Easy to tear by hand
- Laminates well to a variety of substrates
- Tissue carrier is flexible and conformable, which adds dimensional stability
- Heat resistant
- Performs well over a wide temperature range

PRODUCT CONSTRUCTION

Backing	Tissue
Adhesive	Acrylic
Release Liner	Polycoated paper

TECHNICAL DATA

Thickness	3.9 mils
Adhesion	65 oz/in
Service Temperature	32°F to 194°F (0°C to 90°C)
Maximum Operating Temperature (3 min)	266°F (130°F)
Color	Natural (Translucent)
Sizes	24mm to 72mm x 50m, custom slitting available

STORAGE & USAGE CONDITIONS: Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOTape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application, and the user must, by test or otherwise, determine suitability for purpose; ECHOTape makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOTape product is proved to be defective, the exclusive remedy, shall be for ECHOTape to replace the defective product. ECHOTape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.