

DESCRIPTION

TT-634 is a 63 micron (4 mm) tensilized polypropylene tear tape that's spool wound. This high-tensile polypropylene tear tape offers good initial tack and strong ultimate adhesion on a variety of corrugated and solid board surfaces. The tape is available in a variety of lengths and widths and conforms to FDA requirements for indirect food contact. The polypropylene tape is engineered with an acrylic adhesive system. Available in white, this tape has excellent shear resistance and is often used on food packaging, detergent cartons, consumer cartons, envelopes, and corrugated cartons.

APPLICATIONS

- Detergent cartons
- Consumer cartons
- Envelopes (padded shipping envelopes, express delivery envelopes, and courier envelopes)
- Corrugated cartons (medium to heavy weight)
- Food packaging (conforms to FDA requirements for indirect food contact)

FEATURES & BENEFITS

- Good initial tack
- Strong ultimate adhesion
- Excellent shear resistance

PRODUCT CONSTRUCTION

| | |
|----------|--------------------------|
| Backing | Tensilized Polypropylene |
| Adhesive | Acrylic |

TECHNICAL DATA

| | |
|-----------------|-----------------|
| Total Thickness | 63 microns |
| Tensile | 110 lbs/in |
| Adhesion | 23 oz/in |
| Elongation | 35 % |
| Color | White, Red |
| Sizes | 4mm X 20000 yds |

***STORAGE & USAGE CONDITIONS:** Store under dry conditions at 50°C to 300°C in the container supplied, ideally at 50% relative humidity. Always keep the container the correct way up, as indicated by the arrow. Stored under the recommended conditions, it is expected to have a shelf life of at least twelve months from the date of manufacture.

Store tape away from direct sunlight in dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application, and the user must, by test or otherwise, determine suitability for purpose; ECHOtape makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for ECHOtape to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.