



Premium Grade 60 Day Stucco Duct Tape CL-W6059

DESCRIPTION

CL-W6059 is a premium grade, 60-day cloth stucco duct tape that was developed for stucco professionals. Designed to protect window frames and door frames during outdoor masking applications, the tape is strong and durable and will peel off without leaving residue. The tape has a high-performance rubber adhesive, can be used indoors and outdoors, has outstanding UV resistance, and holds up in hot temperatures. This gray stucco tape is used in 2-step and 3-step stucco processes (scratch, brown, and finish) in which the protective barrier is used throughout the entire stucco application. The tape sticks well to smooth surfaces (such as steel and plastic) and rough or textured surfaces (such as wood) and conforms to uneven surfaces.

**Milgard recommends this stucco tape for use with their vinyl and fiberglass windows. **

APPLICATIONS

- Protects vinyl windows, profiles, and doorframes during outdoor stucco applications (Recommended by Milgard windows for use with their vinyl and fiberglass windows)
- Used in 2-step and 3-step stucco processes (scratch, brown, and finish) where the protective barrier is used throughout the entire stucco application

FEATURES & BENEFITS

- Superior holding power and durability in hot temperatures
- Limited residue when removed within 60 days of application
- Sticks well to smooth surfaces (such as steel and plastic)
- Sticks well to rough or textured surfaces (such as wood)
- Conforms to uneven surfaces
- Easy to apply (doesn't curl or splinter) and you can tear the tape by hand (leaving a clean, straight edge)

PRODUCT CONSTRUCTION

Backing	Waterproof polyethylene coated cloth
Adhesive	Natural Rubber

TECHNICAL DATA

Thickness	13 mils
Tensile Strength	25 lbs/in
Adhesion	24 oz./in
Color	Gray
Sizes	1.89 in x 60 yd / 48mm x 55m

STORAGE & USAGE CONDITIONS : Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application, and the user must, by test or otherwise, determine suitability for purpose; ECHOtape makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for ECHOtape to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.