



# Clear Double Sided Tape for General Purpose Mounting and Bonding DC-M158A

## DESCRIPTION

DC-M158A is the perfect permanent double-sided tape for everyday applications around the office, warehouse, workshop, or classroom. The aggressive, acrylic adhesive bonds to virtually any surface, and on hard surfaces, you can reposition the tape within 60 seconds of application. Designed for lightweight mounting and bonding, the double-sided tape can be applied to textiles, foils, films, papers, plastic, metal, and more! The tape has an aggressive, fast-grabbing, high-tack acrylic adhesive that sticks well from the onset and performs well across a wide range of temperatures. This double-sided tape is also often used for general assembly of decorative parts, as well as bonding textiles and leather prior to sewing.

## APPLICATIONS

- Permanent bonding of papers, films, foils, textiles, leather, plastic, and metal
- General assembly of decorative parts
- Temporary bonding to keep items in place prior to fastening them
- Bonding textiles and leather prior to sewing

## FEATURES & BENEFITS

- Fast-grabbing adhesive sticks well from the onset and can reposition the tape within 60 seconds (only on hard surfaces)
- Adheres well to a variety of surfaces
- Polyester carrier is flexible and conforms to many surfaces
- Can tear the tape by hand and performs well across a broad range of temperatures

## PRODUCT CONSTRUCTION

|               |                   |
|---------------|-------------------|
| Backing       | Polyester Film    |
| Adhesive      | Acrylic           |
| Release Liner | Siliconized paper |

## TECHNICAL DATA

|                     |                               |
|---------------------|-------------------------------|
| Thickness           | 3.6 mils                      |
| Adhesion            | 35 oz/in                      |
| Service Temperature | 32°F to 194°F (0°C to 90°C)   |
| Elongation          | 116 %                         |
| Colors              | Transparent                   |
| Sizes               | .94 in x 54.6 yd   24mm x 50m |

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.