

DESCRIPTION

DC-M158A is the perfect permanent double-sided tape for everyday applications around the office, warehouse, workshop, or classroom. The aggressive, acrylic adhesive bonds to virtually any surface, and on hard surfaces, you can reposition the tape within 60 seconds of application. Designed for lightweight mounting and bonding, the double-sided tape can be applied to textiles, foils, films, papers, plastic, metal, and more! The tape has an aggressive, fast-grabbing, high-tack acrylic adhesive that sticks well from the onset and performs well across a wide range of temperatures. This double-sided tape is also often used for general assembly of decorative parts, as well as bonding textiles and leather prior to sewing.

APPLICATIONS

- Permanent bonding of papers, films, foils, textiles, leather, plastic, and metal
- General assembly of decorative parts
- Temporary bonding to keep items in place prior to fastening them
- Bonding textiles and leather prior to sewing

FEATURES & BENEFITS

- Fast-grabbing adhesive sticks well from the onset and can reposition the tape within 60 seconds (only on hard surfaces)
- Adheres well to a variety of surfaces
- Polyester carrier is flexible and conforms to many surfaces
- Can tear the tape by hand and performs well across a broad range of temperatures

PRODUCT CONSTRUCTION

Backing	Polyester Film
Adhesive	Acrylic
Release Liner	Siliconized paper

TECHNICAL DATA

Thickness	3.6 mils
Adhesion	35 oz/in
Service Temperature	32°F to 194°F (0°C to 90°C)
Elongation	116 %
Colors	Transparent
Sizes	.94 in x 54.6 yd 24mm x 50m

STORAGE & USAGE CONDITIONS: Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application, and the user must, by test or otherwise, determine suitability for purpose; ECHOtape makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for ECHOtape to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.