



White Double Sided Tape for
Permanent Mounting & Bonding

DC-U032A

DESCRIPTION

DC-U032A is an extremely aggressive and strong double-sided mounting tape that's designed for permanent bonding and will stick to just about any surface. Weather resistant, the tape can be used indoors and outdoors. The tape has an acrylic adhesive that provides superior holding power from the onset and sticks well to smooth surfaces (such as steel and plastic), as well as rough and textured surfaces (such as wood). The most common applications for the permanent, double-sided mounting tape include permanent bonding of metal, plastic, rubber, plexiglass, and wood; mounting small to medium, lightweight indoor and outdoor signs, decorative trim and name plates; and bonding applications in which other tapes might not adhere properly.

APPLICATIONS

- Permanent bonding of metal, plastic, rubber, plexiglass, and wood
- Mounting small to medium, lightweight indoor and outdoor signs
- Mounting name plates and decorative trim
- Bonding applications where other tapes might not adhere properly

FEATURES & BENEFITS

- Superior holding power (from the onset)
- Sticks well to smooth surfaces (such as steel and plastic) and adheres to rough and textured surfaces (such as wood)
- Conforms to most surfaces and easy to apply (the tape can be easily removed from its liner)
- Designed to work at room temperature, the tape can also perform for medium heat applications

PRODUCT CONSTRUCTION

Backing	PVC
Adhesive	Acrylic
Release Liner	Glassine Paper

TECHNICAL DATA

Thickness	9.5 mils
Tensile	7.7 lbs/in
Adhesion	80 oz/in
Application Temperature	68°F to 95°F (20°C to 35°C)
Service Temperature	32°F to 176°F (0°C to 80°C)
Color	White
Sizes	.47 in x 54.6 yd 12mm x 50m / .71 in x 54.6 yd 18mm x 50m .94 in x 54.6 yd 24mm x 50m / 1.89 in x 54.6 yd 48mm x 50m

STORAGE & USAGE CONDITIONS: Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application, and the user must, by test or otherwise, determine suitability for purpose; ECHOtape makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for ECHOtape to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

1.800.461.8273 | info@echotape.com

echotape.com

LET'S TALK TAPE