



# Double Sided Removable Carpet Tape **DC-W188F**

## DESCRIPTION

DC-W188F is a double-sided, removable carpet tape, with a strong adhesive that won't leave behind residue. The carpet tape is ideal for professionals who manage trade shows, conventions, and other large events that require carpeting and other types of temporary flooring to be quickly laid down and then easily removed. And these aren't the only uses for this unique removable tape! It can also be used for construction and industrial mounting applications, including holding vapor barrier films; mounting film for construction processes; and printing plates in industrial print packaging. The tape has an aggressive rubber adhesive on the liner side of the tape, and the adhesive on the exposed side of the tape leaves no residue when the tape is removed.

## APPLICATIONS

- Laying down carpet and other types of temporary flooring
- Holding vapor barrier film in place when encapsulating crawl spaces
- Mounting film when creating clean rooms and containment rooms for demolition and remediation processes
- Mounting printing plates for industrial print packaging applications

## FEATURES & BENEFITS

- Aggressive adhesive on the liner side of the tape and on the exposed side of the tape leaves no residue when removed
- Especially suited for adhesion to carpet and easy release poly liner makes it fast to apply and easy to use

## PRODUCT CONSTRUCTION

Backing	Cloth
Adhesive	Rubber
Release Liner	Polyethylene Film

## TECHNICAL DATA

Thickness	11 mils
Tensile	28 lbs/in
Adhesion	Exposed Side = 30 oz/in / Liner Side = 40 oz/in
Application Temperature	65°F (18°C) or above
Service Temperature	5°F to 158°F (-15°C to 70°C)
Elongation	10 %
Color	Beige
Sizes	1.89 in x 36 yd   48mm x 33m / 2.83 in x 36 yd   72mm x 33m

**STORAGE & USAGE CONDITIONS:** Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application, and the user must, by test or otherwise, determine suitability for purpose; ECHOtape makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for ECHOtape to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

1.800.461.8273 | [info@echotape.com](mailto:info@echotape.com)

[echotape.com](http://echotape.com)

LET'S TALK TAPE