

DESCRIPTION

VI-N6120 is one of our most popular adhesive tapes, thanks to its versatility, consistent performance, and ability to bond well and conform to a variety of surfaces. Used extensively by stucco contractors and mold and asbestos abatement contractors, this tape is used for temporary holding, general repairs, masking, seaming, splicing, and color coding. The polyethylene vinyl is made from an extra-strength polyethylene film, and it's coated with a high-tack synthetic rubber adhesive. When the tape is removed within 7-10 days, it leaves little or no residue on most surfaces. Available in black, blue, white, or transparent, this vinyl tape has superior low temperature bonding, works well over a wide temperature range, and has a waterproof backing material. The tape will maintain a watertight seal in all weather conditions (if applied properly).

APPLICATIONS

- Temporary holding, general repairs Masking windows and door frames in stucco applications
- Taping polyethylene films for containment in clean rooms, mold and asbestos remediation and demolition
- Seaming polyethylene film for underslab vapor barriers
- Splicing polyethylene films, color-coding and floor marking (for events, exhibits, and tradeshow)

FEATURES & BENEFITS

- Bonds well and conforms to a variety of surfaces, is tough and flexible and has superior low temperature bonding
- Works well over a wide temperature range, waterproof backing material maintains a watertight seal in all weather conditions (if applied properly)
- Leaves little to no residue if removed within 7-10 days (on most surfaces)
- Hangs and tears straight, is easy to unwind, holds strong, preventing lifting
- Can be applied by hand, doesn't curl or splinter, making it easy to apply

PRODUCT CONSTRUCTION

Backing	Polyethylene Film
Adhesive	Synthetic Rubber

TECHNICAL DATA

Thickness	7 mils
Tensile	18 lbs/in
Adhesion	60 oz/in
Elongation	80%
Color	Blue, Black, Red, White, Transparent
Sizes	1.89 in x 60 yd / 48mm x 55m 2.83 in x 60 yd / 24mm x 55m

STORAGE & USAGE CONDITIONS: Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application, and the user must, by test or otherwise, determine suitability for purpose; ECHOtape makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for ECHOtape to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.