

DESCRIPTION

DC-K048A is an extremely strong, double-sided tape that's designed to mount or bond items temporarily. The tape sticks very well to smooth surfaces (such as steel and paper), and also can be used on wood, fabric, and other porous and textured surfaces. When you need your temporary hold to hold up, this double-sided tape will do the trick! The tape has a high-performance rubber adhesive, removes cleanly from most hard and smooth surfaces, and provides excellent holding power from the onset. The most common applications for this temporary double-sided tape include: temporarily holding down steel, metal or wooden components; temporarily holding small carpets in place; and mounting posters or photographs on walls.

APPLICATIONS

- Temporarily hold down steel, metal and wooden components
- Holds small carpets in place
- Mount posters or photographs on walls

FEATURES & BENEFITS

- Excellent holding power from the onset and removes cleanly from most hard and smooth surfaces
- Easy to remove the paper liner and you can tear the tape by hand
- Designed to work at room temperature, also performs well for medium heat applications

PRODUCT CONSTRUCTION

Backing	Crepe Paper
Adhesive	Rubber
Release Liner	Crepe Paper

TECHNICAL DATA

Thickness	6 mils
Tensile	23 lbs/in
Adhesion	47 oz/in
Application Temperature	50°F to 110°F (10°C to 43°C)
Service Temperature	32°F to 180-°F (0°C to 82°C)
Elongation	8.5 %
Color	Beige
Sizes	.94 in x 36 yd 24mm x 33m

STORAGE & USAGE CONDITIONS: Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOTape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application, and the user must, by test or otherwise, determine suitability for purpose; ECHOTape makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOTape product is proved to be defective, the exclusive remedy, shall be for ECHOTape to replace the defective product. ECHOTape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.