

DESCRIPTION

DC-M012P is an extremely strong and aggressive, double-sided tape that's designed to mount or bond items permanently. This double-sided tape can be used for difficult bonding applications in which other tapes might fail. The clear tape sticks well to a variety of surfaces, including plexiglass, rubber, plastic, metal, and steel. The tape has a high-performance acrylic adhesive that provides a strong hold from the onset. The most common applications for this permanent double-sided tape include permanent bonding of steel, metal, plastic, rubber, and plexiglass; mounting small to medium indoor and outdoor signs, decorative trim, and nameplates; and joining or splicing various types of polyester films.

APPLICATIONS

- Permanent bonding of steel, metal, plastic, rubber, and plexiglass
- Mounting small to medium, lightweight indoor and outdoor signs, nameplates, decorative trims and plastic profiles & joining or splicing various types of polyester films
- Difficult bonding applications where other tapes might not adhere properly

FEATURES & BENEFITS

- Strong hold from the onset and easily conforms to most surfaces
- Superior adhesion to polyester films, with easy-to-remove red poly liner making it quick to apply the tape
- Acrylic adhesive provides maximum performance indoors and outdoors

PRODUCT CONSTRUCTION

Backing	Polyester Film
Adhesive	Acrylic
Release Liner	Red Polyfilm

TECHNICAL DATA

Thickness	8 mils
Tensile Strength	23 lbs/in
Adhesion	70 oz/in
Application Temperature	68°F to 104°F (20°C to 40°C)
Service Temperature	32°F to 176°F (0°C to 80°C)
Elongation	116 %
Colors	Clear
Sizes	.94 in x 36 yd 24mm x 33m

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOTape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOTape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOTape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.