

DESCRIPTION

DC-T274A is a general-purpose, double-sided tape that can be used for everyday applications around the office, warehouse, workshop, or classroom. Able to stick to almost any surface, this fast-grabbing, clear tape works well for lightweight mounting and bonding applications to textiles, foils, films, papers, plastic, metal, and more. The tape has an aggressive, high-tack acrylic adhesive that sticks well from the onset, and the tape is flexible enough to conform to most surfaces. This clear double-sided tape is also often used to temporarily hold items in place prior to fastening them and for bonding textiles and leather prior to sewing.

APPLICATIONS

- Permanent bonding of papers, films, foils, textiles, leather, plastic, and metal
- General assembly of decorative parts
- Temporary bonding to keep items in place prior to fastening them
- Bonding textiles and leather prior to sewing

FEATURES & BENEFITS

- Fast-grabbing adhesive sticks well from the onset
- Adheres well to a variety of surfaces
- Flexible enough to conform to many surfaces
- Can tear the tape by hand and has an easy to remove paper liner

PRODUCT CONSTRUCTION

Backing	Tissue
Adhesive	Acrylic
Release Liner	White Siliconized paper

TECHNICAL DATA

Thickness	3.9 mils
Tensile	7.7 lbs/in
Adhesion	65 oz/in
Service Temperature	-32°F to 194°F (0°C to 90°C)
Elongation	75%
Colors	Frosted Clear
Sizes	.47 in x 54.6 yd 12mm x 50m / .71 in x 54.6 yd 18mm x 50m .94 in x 54.6 yd 24mm x 50m / 1.89 in x 54.6 yd 48mm x 50m

STORAGE & USAGE CONDITIONS: Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application, and the user must, by test or otherwise, determine suitability for purpose; ECHOtape makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for ECHOtape to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.