

**DESCRIPTION**

FO-V2344 and FO-V2348 are single-sided thermal break tapes, designed to reduce thermal bridging on outer and inner framing in metal buildings. Available in 1/4 inch and 1/8 inch thicknesses, these tapes have excellent holding power and high-load capability. The tapes have an acrylic adhesive, and they adhere quickly and well to smooth and rough surfaces (including corrugated metal), as well as irregular surfaces. These thermal break tapes have a range of applications, including creating a vapor seal where large gaps occur; creating a lap joint seal on corrugated metal building panels or prefabricated wall panels; creating a flash break on building purlins and girt flanges; and maintaining a seal in high movement joints.

**APPLICATIONS**

- Create a vapor seal where large gaps occur, lap joint seals on corrugated metal building panels and prefabricated wall panels
- Create a flash break on building purlins and girt flanges and maintains a seal in high movement joints

**FEATURES & BENEFITS**

- Adheres strongly to smooth and rough surfaces (including corrugated metal), is easy to apply and sticks quickly.
- Conforms well to irregular surfaces and is easy to die-cut for custom sizing.
- The paper release liner protects the adhesive from contaminants when cutting the tape to specific lengths.

**PRODUCT CONSTRUCTION**

<b>Backing</b>	PVC Foam
<b>Adhesive</b>	Acrylic

**TECHNICAL DATA**

<b>Thickness</b>	1/4" (FO-V2344)   1/8" (FO-V2348)
<b>Tensile</b>	60 PSI
<b>Adhesion</b>	20 oz/in
<b>Service Temperature</b>	-20°F to 130°F (-29°C to 54°C)
<b>Compression Deflection</b>	5 PSI
<b>R Value</b>	1.15 (1/4")   .576 (1/8")
<b>Holding Power</b>	>24 hours @ 2.2psi load, R.T. (Room Temp)
<b>Elongation</b>	120 %
<b>Color</b>	Gray
<b>Sizes</b>	¼ in x 2 in x 50 ft, ¼ in x 3 in x 50 ft   1/8 in x 2 in x 75 ft, 1/8 in x 3 in x 75 ft

**STORAGE & USAGE CONDITIONS:** Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application, and the user must, by test or otherwise, determine suitability for purpose; ECHOtape makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for ECHOtape to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.