

**DESCRIPTION**

FS-G7732 is an all weather adhesive tape that's used primarily to seal, seam, and repair tears on Lamtec WMP-VR-R Plus faced insulation that's used in metal buildings. This facing tape provides a strong bond, and performs exceptionally well at low temperatures. The Lamtec WMP-VR-R facing tape has a cold-weather, acrylic adhesive that's quick to stick. Available in black or white, this facing tape creates an excellent vapor barrier, has a low WVTR (water vapor transmission rate), and can be cut to specific lengths for use in tight areas.

**APPLICATIONS**

- Seam and join Lamtec WMP-VR-R faced insulation
- Repair tears on Lamtec WMP-VR-R faced insulation

**FEATURES & BENEFITS**

- Quick to stick and creates a strong bond
- Performs well across a broad range of temperatures (including cold temperatures)
- Excellent vapor barrier
- Low WVTR (water vapor transmission rate)
- Paper liner is easy to remove
- Can be cut to specific lengths for use in tight areas

**PRODUCT CONSTRUCTION**

Backing	Poly Film/Scrim/Metalized Polyester
Adhesive	Acrylic
Release liner	Siliconized Paper

**TECHNICAL DATA**

Thickness	8.5 mils
Tensile	42 lbs/in
Adhesion	40 oz/in
Application Temperature	-4°F to 104°F (-20°C to 48°C)
Service Temperature	-40°F to 176°F (-40°C to 80°C)
Elongation	1 %
Color	White, Black
Sizes	2.83 in x 50 yd   72mm x 45,72m

**STORAGE & USAGE CONDITIONS:** Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application, and the user must, by test or otherwise, determine suitability for purpose; ECHOtape makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for ECHOtape to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.