

**DESCRIPTION**

CL-W6064 is an industrial-strength duct tape that's no ordinary duct tape! Made with an advanced adhesive technology, the duct tape provides superior holding power yet is easy to tear and apply. Available in 6 colors, this heavy-duty duct tape sticks well to smooth and rough surfaces, and it can be used for holding, seaming, repairing, and bundling. The tape has a high-performance rubber adhesive and conforms well to uneven surfaces. Common applications for this aggressive duct tape include temporary holding and bonding, general purpose use and repair, hanging and patching polyethylene sheeting, duct work, and color coding.

**APPLICATIONS**

- Temporary holding and bonding
- General purpose use and repair
- Hanging and patching polyethylene sheeting
- Duct work, bundling and color coding
- Applications in manufacturing and industrial environments

**FEATURES & BENEFITS**

- Aggressive adhesive and superior holding power
- Sticks well to a wide variety of smooth and rough surfaces
- Conforms to uneven surfaces
- Can tear the tape by hand (leaving a clean, straight edge)
- Unwinds smoothly (making it easier to apply)
- Tape lays flat (no twisting or curling)

**PRODUCT CONSTRUCTION**

<b>Backing</b>	Polyethylene Coated Cloth
<b>Adhesive</b>	Synthetic Rubber

**TECHNICAL DATA**

<b>Thickness</b>	7 mils
<b>Tensile Strength</b>	17 lbs/in
<b>Adhesion</b>	65 oz/in
<b>Elongation</b>	12 %
<b>Colors</b>	Silver, Black, Yellow, Red, Blue, Green, White
<b>Sizes</b>	1.89 in x 60 yd / 48mm x 55m

**STORAGE & USAGE CONDITIONS :** Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOTape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application, and the user must, by test or otherwise, determine suitability for purpose; ECHOTape makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOTape product is proved to be defective, the exclusive remedy, shall be for ECHOTape to replace the defective product. ECHOTape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.