

**DESCRIPTION**

FS-J7744 is a high-performance, reinforced ASJ Kraft insulation facing tape that's primarily used to seal and seam ASJ faced duct board and fiberglass pipe insulation and repair tears in white Kraft scrim foil backed insulation. The ASJ Kraft insulation facing tape is coated with a flame retardant, cold-weather acrylic adhesive. Available in white, this tape provides a strong and secure bond on a variety of surfaces and textures, is mold resistant, and is UL 723 classified.

**APPLICATIONS**

- Sealing and seaming ASJ faced duct board and fiberglass pipe insulation
- Repairing tears in white poly scrim foil backed insulation

**FEATURES & BENEFITS**

- Initial quick stick and creates a strong bond to a variety of surfaces and textures
- Paper liner is easy to remove and protects the adhesive from contaminants when you need to cut the tape to specific lengths
- Designed for tear-resistant sealing, mold resistant, coated with a flame-retardant acrylic adhesive and is UL 723 classified

**PRODUCT CONSTRUCTION**

<b>Backing</b>	Kraft/Scrim/Foil Laminate Facing
<b>Adhesive</b>	Acrylic
<b>Release liner</b>	Siliconized Paper

**TECHNICAL DATA**

<b>Thickness</b>	6.8 mils
<b>Tensile</b>	27.3 lbs/in
<b>Adhesion</b>	60 oz/in
<b>Application Temperature</b>	-4°F to 104°F (-20°C to 48°C)
<b>Service Temperature</b>	-37°F to 248°F (-35°C to 120°C)
<b>UL Classification</b>	UL 723 General Use Tape Surface Burning Characteristics 38MP / Applied to Inorganic Reinforced cement board
<b>Flame Spread</b>	10
<b>Smoke Developed</b>	5
<b>Color</b>	White
<b>Sizes</b>	2.83 in x 50 yd   72mm x 45,72m

**STORAGE & USAGE CONDITIONS:** Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application, and the user must, by test or otherwise, determine suitability for purpose; ECHOtape makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for ECHOtape to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.