



DESCRIPTION

ME-W8306 is a self-adhesive, fiberglass reinforcing mesh tape that's strong, yet flexible enough to adhere to contoured surfaces with ease. The tape is primarily used by stucco contractors to reinforce architectural foam shapes and trim profiles in outdoor stucco construction. The fiberglass mesh helps anchor the stucco to the molded shapes and profiles during the stucco application process. The tape is also often used to reinforce drywall joint compounds (pulling drywall joints). The mesh tape has a latex-based adhesive, and the tape won't bubble and is tear-proof and shrink-proof. Available in blue or white, this reinforcing tape is often used to permanently hide joints cracks and repair holes in stucco and drywall.

APPLICATIONS

- Reinforcing architectural foam shapes and trim profiles
- Reinforcing drywall joint compound
- Permanently hiding joints, cracks, and holes in stucco repairs
- Permanently hiding joints, cracks, and holes in drywall repairs

FEATURES & BENEFITS

- Easy to apply and contours well around shapes
- Tear-proof and shrink-proof
- Won't bubble
- Improves the adherence of stucco to trim profiles and foam shapes

PRODUCT CONSTRUCTION

Backing	Woven Fiberglass Mesh
---------	-----------------------

Adhesive	Latex-based
----------	-------------

TECHNICAL DATA

Tensile	MD \geq 440 N/50mm / TD \geq 440 N/50mm
---------	---

Weight	65 g/sq.m (2.2 oz/sq.m)
--------	-------------------------

Fabric Count	Warp 9 ± 0.5 mesh/in / Weft 9 ± 0.5 mesh/in
--------------	---

Latex %	≥ 26
---------	-----------

Color	White, Blue
-------	-------------

Sizes	36 in x 150 ft
-------	----------------

STORAGE & USAGE CONDITIONS: Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application, and the user must, by test or otherwise, determine suitability for purpose; ECHOtape makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for ECHOtape to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.