

DESCRIPTION

PE-M4535 is an all weather construction seaming tape that's engineered to adhere to a wide range of building materials and surfaces. Formulated with a proprietary cold-weather adhesive and an advanced polyester backing, the seaming tape is extremely strong and easy to apply. You can use this seam tape on just about anything, including: house wrap, sheathing, vapor barriers, flooring and roofing underlayments, and exterior and rigid insulation. The seaming tape has an acrylic adhesive that provides an instant tack, which strengthens over time. Available in red, silver, or white, this heavy-duty seaming tape is water resistant, moisture resistant, and UV resistant (for up to 90 days).

APPLICATIONS

- Seaming the building envelope
- Seaming house wrap
- Seaming insulation (including polyisocyanurate insulation and reflective insulation)
- Seaming exterior sheathing
- Seaming vapor barriers (including polyethylene films)
- Seaming flooring underlayments
- Seaming roofing underlayments

FEATURES & BENEFITS

- Strong, with durable holding power
- Conforms well to a variety of irregular surfaces
- Instant tack, on a wide range of surfaces and materials
- Tack strengthens over time
- Made from an advanced polyester film (PET)
- Water resistant and moisture resistant
- Excellent cold weather adhesion
- UV resistant (up to 90 days)
- Can tear the tape by hand
- Colors allow for easy inspection

PRODUCT CONSTRUCTION

| | |
|----------|----------|
| Backing | PET Film |
| Adhesive | Acrylic |

TECHNICAL DATA

| | |
|-------------------------|---------------------------------|
| Thickness | 3.54 mils |
| Tensile | 20 lbs/in |
| Adhesion | 60 oz/in |
| Application Temperature | -4°F to 105°F (-20°C to 40°C) |
| Service Temperature | -40°F to 148°F (-40°C to 120°C) |
| Color | White, Silver, Red |
| Sizes | .94 in x 36 yd 24mm x 33m |

STORAGE & USAGE CONDITIONS: Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application, and the user must, by test or otherwise, determine suitability for purpose; ECHOtape makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for ECHOtape to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.