



High Strength
Kraft Flatback Tape
FB-K4329

DESCRIPTION

FB-K4329 is a strong Kraft flatback tape that's designed primarily for splicing and tabbing applications, but also works well for core starting and tabbing, as well as a wide range of packaging applications (including food packaging). The tape has a specially formulated rubber adhesive that provides excellent adhesion to heavy Kraft paper and many other surfaces. The extensible paper on the brown Kraft tape provides strength and flexibility, and the tape holds up in a wide range of temperature and humidity conditions.

APPLICATIONS

- Splicing and holding applications
- Core starting and tabbing applications
- Sealing cartons and boxes
- Paper packaging
- Food packaging (the tape complies with the section of the Federal Food, Drug, and Cosmetic Act that covers the use of pressure-sensitive adhesives and tapes for "indirect contact" food packaging and box sealing)

FEATURES & BENEFITS

- Specially formulated adhesive provides excellent adhesion to heavy Kraft paper and many other surfaces
- Tape can be torn by hand
- Tape unwinds smoothly and is easy to apply
- Extensible paper on the tape provides strength and flexibility
- Performs well in a variety of temperature and humidity conditions

PRODUCT CONSTRUCTION

Backing Natural Kraft Paper

Adhesive Rubber

TECHNICAL DATA

Thickness 7.5 mils

Tensile 50 lbs/in

Adhesion 50 oz/in

Elongation 2.5 %

Color Kraft

Sizes 48mm, 72mm, 96mm and 120mm x 50m

STORAGE & USAGE CONDITIONS: Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application, and the user must, by test or otherwise, determine suitability for purpose; ECHOtape makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for ECHOtape to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.