

DESCRIPTION

GL-N0708 and GL-N0716 are double-sided, foam glazing tapes that are designed for window glazing applications. Available in 1/8 inch and 1/16 inch thicknesses, the tapes are coated on each side with a high-tack acrylic adhesive that's quick to set and continues to strengthen over time. Made with a soft and flexible polyethylene foam, the double-sided glazing tapes adapt to a variety of textured surfaces. The foam glazing tapes have an acrylic adhesive that seals well against water, dust, and light, and also makes them resistant to weather, temperatures, and oxidation. Available in black or white, these double-sided foam tapes are AAMA certified and are often used for glazing on aluminum window framing and PVC window framing. The tapes also work well for general bonding and mounting of lightweight plastics and metals.

APPLICATIONS

- Window glazing applications on aluminum and PVC window framing
- Bonding and mounting lightweight plastic and metals

FEATURES & BENEFITS

- Seals well against water, dust, and light
- Resistant to weather, temperature, UV, and oxidation
- Flexible and soft, which makes it easy to adjust to a variety of textured surfaces
- Sticks well from the onset, acrylic adhesive continues to strengthen over time and has an easy release poly liner
- AAMA certified (which makes it suitable for glazing applications)

PRODUCT CONSTRUCTION

Backing	2.0 PCF PE Foam
Adhesive	Acrylic
Release liner	4 mil Blue PE

TECHNICAL DATA

Thickness	1/8" (GL-N0708) and 1/16" (GL-N0716)
Tensile	27.3 lbs/in
Adhesion	110 oz/in
Service Temperature	-4°F to 248°F (-20°C to 120°C)
Elongation	180%
Color	White, Black
Sizes	Thicknesses 1/8", 1/16", 1/32", 3/32" 6mm, 9mm, 12mm, 15mm (Custom slitting available)

STORAGE & USAGE CONDITIONS: Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application, and the user must, by test or otherwise, determine suitability for purpose; ECHOtape makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for ECHOtape to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.