

MK-K5417

Utility Grade General Purpose Paper Masking Tape

MK-K5417 is a 5.5 mils utility grade masking tape used on a variety of substrates for general purpose adhesion.

Application

- General purpose masking tape
- Used for packaging, bundling, holding, splicing and tabbing of various substrates

Features & Benefits

- Good adhesion on variety of substrates
- Flexible and easy to use
- Excellent quick stick
- Resistant to water and oil

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.



Sizes

12mm, 18mm, 24mm, 36mm, 48mm, 72mm, 96mm x 55m
custom slitting

Technical Data

Carrier	Crepe Paper
Adhesive	Blended Rubber Based
Total Thickness	5.5 mils
Tensile	20 lbs/in
Adhesion	48 oz/in
Service Temperature	50° F to 150° F (10°C to 66° C)
Elongation	8%
Color	Natural

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.