



Clear Double Sided Tape for
Permanent Mounting & Bonding

DC-U101A

DESCRIPTION

DC-U101A is a double-sided UPVC tape that incorporates a high-tack and high-peel acrylic adhesive system. This unique UPVC tape is often used for product assembly, difficult bonding and splicing applications, and lamination on a variety of materials (including EPDM rubber, plastic, glass, ether foams, ester foams, and urethane foams). The tape incorporates an exceptionally high-tack and high-peel acrylic adhesive system. The high-adhesive mass on this double-sided tape helps fill gaps, and the UPVC film allows conformability. Weather resistant and water resistant, the tape bonds well to rough surfaces and porous surfaces.

APPLICATIONS

- Product assembly
- Difficult bonding and splicing applications
- Lamination to EPDM rubber, plastic, glass, and urethane foams

FEATURES & BENEFITS

- Exceptionally high-tack and high-peel
- High-adhesive mass helps fill gaps and UPVC film allows conformability
- Adheres well to ether foams and ester foams and bonds well to rough and porous surfaces
- Excellent resistance to environmental extremes and water resistant

PRODUCT CONSTRUCTION

Backing	1.5 mils UPVC
Adhesive	Acrylic
Release Liner	60# Kraft Siliconized Paper

TECHNICAL DATA

Thickness	8.5 mils
Tensile	7.7 lbs/in
Adhesion	136 oz/in
Service Temperature	-20°F to 200°F (-29°C to 93°C)
Elongation	60 %
Color	Clear
Sizes	.47 in x 54.6 yd 12mm x 50m .94 in x 54.6 yd 24mm x 50m 1.89 in x 60 yd 48mm x 50m

STORAGE & USAGE CONDITIONS: Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application, and the user must, by test or otherwise, determine suitability for purpose; ECHOtape makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for ECHOtape to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.

1.800.461.8273 | info@echotape.com

echotape.com

LET'S TALK TAPE