



DESCRIPTION

VI-N6103 is a strong, single-sided, vinyl waterproof tape that bonds to most surfaces and works well across a wide range of temperatures. With excellent holding power and durability, the white vinyl tape is often used to seam polyethylene barriers for crawlspace containment and encapsulation, as well as underslab vapor barriers. The vinyl seaming tape has a strong rubber adhesive that provides superior low temperature bonding and maintains a watertight seal (when applied properly). Available in white, this seaming tape is flexible and can be easily repositioned.

APPLICATIONS

- Seaming applications where waterproofing is required
- Seaming polyethylene vapor barriers in crawlspace applications
- Seaming polyethylene barriers in underslab applications

FEATURES & BENEFITS

- Excellent holding power and durability
- Tough and flexible
- Conforms well to a variety of surfaces
- Superior low temperature bonding
- Bonds well over a wide temperature range
- Maintains a watertight seal in all weather conditions (if applied properly)
- Can be repositioned

PRODUCT CONSTRUCTION

| | |
|---------|-------------------|
| Backing | Polyethylene Film |
|---------|-------------------|

| | |
|----------|--------|
| Adhesive | Rubber |
|----------|--------|

TECHNICAL DATA

| | |
|-----------|--------|
| Thickness | 9 mils |
|-----------|--------|

| | |
|---------|-----------|
| Tensile | 21 lbs/in |
|---------|-----------|

| | |
|----------|----------|
| Adhesion | 60 oz/in |
|----------|----------|

| | |
|---------------------|-----------------------------|
| Service Temperature | 32°F to 160°F (0°C to 70°C) |
|---------------------|-----------------------------|

| | |
|------------|-------|
| Elongation | 100 % |
|------------|-------|

| | |
|-------|-------|
| Color | White |
|-------|-------|

| | |
|-------|---------------|
| Sizes | 96mm x 210 ft |
|-------|---------------|

STORAGE & USAGE CONDITIONS: Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application, and the user must, by test or otherwise, determine suitability for purpose; ECHOtape makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for ECHOtape to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.