

DESCRIPTION

DC-M194A is a high-performance, double-sided polyester film tape that's often used in commercial construction and metal building insulation applications due to its superior holding power and ability to bond well to a variety of surfaces. Weather resistant and UV resistant, the double-sided polyester film tape (PET tape) is coated with a specially engineered acrylic adhesive that's designed to work exceptionally well in cold temperatures. The most common applications for the double-sided polyester tape (PET tape) include mounting insulation; creating lap seals on laminated insulation, reflective insulation, and jacketing insulation; permanently bonding foams, plastics, metals, and composite material; and mounting smooth surface substrates in cold temperatures (such as freezers).

APPLICATIONS

- Mounting insulation
- Creating lap seals on laminated insulation, reflective insulation, and jacketing insulation
- Permanently bonding foams, plastics, metals, and composite materials
- Mounting smooth surface substrates in cold temperatures (such as freezers)

FEATURES & BENEFITS

- Superior holding power and bonds well to a variety of surfaces
- Specially formulated as a cold weather adhesive tape and the polyester (PET) carrier allows for UV resistance
- Can tear the tape by hand and can be applied by hand or with a machine

PRODUCT CONSTRUCTION

Backing	Polyester Film
Adhesive	Acrylic
Release Liner	Siliconized paper

TECHNICAL DATA

Thickness	3.6 mils
Tensile	7.7 lbs/in
Adhesion	40 oz/in
Application Temperature	-4°F to 176°F (-20°C to 90°C)
Service Temperature	-40°F to 176°F (-40°C to 80°C)
Elongation	75%
Colors	Transparent

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOTape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOTape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOTape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.