

RE-T6701

Double Sided Repulpable Tape for Manual Splicing of Newsprint

RE-T6701 is a 0.105 mm, double coated repulpable light blue tape with a cellulose fiber tissue carrier, coated with a water soluble acrylic adhesive High wet grab. Bi-siliconized, white, stiff, repulpable, easy release liner.

Application

- Recommended for flying splice at low speed (<600 m./min.), on off-line coaters, supercalenders, or sheeters operating with automatic zero speed splicers. Useable on uncoated and coated paper. Heat resistant to 200°C.

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

Sizes

18 mm x 50 m

24 mm x 50 m

Technical Data

Carrier	Tissue
Adhesive	Water Soluble
Total Thickness	.105 mm
Adhesion	35.8 oz/in

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.