

**DESCRIPTION**

FS-K7768 is a high-performance, all weather tape that's primarily used to seal, seam, and repair tears in foil-faced insulation (such as FSK-faced fiberglass duct board and blanket systems). The FSK insulation facing tape is coated with a flame retardant, acrylic adhesive. Available in silver, this tape provides a strong and secure bond on a variety of surfaces and textures, is mold resistant, and is UL 723 classified. An epoxy resin coating on the insulation tape helps protect the surface from corrosion caused by moisture.

**APPLICATIONS**

- Sealing and seaming FSK (Foil-Scrim-Kraft) laminated board and jacketing insulation
- Repairing tears in foil faced insulation

**FEATURES & BENEFITS**

- Initial quick stick and creates a strong bond to a variety of surfaces and textures
- Designed for tear-resistant sealing, is mold resistant and coated with a flame-retardant acrylic adhesive
- An epoxy resin coating on the tape helps protect the surface from corrosion caused by moisture and tape is UL 723 classified

**PRODUCT CONSTRUCTION**

<b>Backing</b>	Aluminum Foil/Scrim/Kraft (FSK)
<b>Adhesive</b>	Acrylic
<b>Release liner</b>	Kraft Paper

**TECHNICAL DATA**

<b>Thickness</b>	8.0 mils
<b>Tensile</b>	27.3 lbs/in
<b>Adhesion</b>	64.8 oz/in
<b>Application Temperature</b>	-4°F to 104°F (-20°C to 48°C)
<b>Service Temperature</b>	-31°F to 248°F / -35°C to 120°C
<b>UL Classification (Fire Rating)</b>	UL 723 General Use Tape Surface Burning Characteristics 38MP / Applied to Inorganic Reinforced cement board
<b>Elongation</b>	1%
<b>Flame Spread / Smoke Developed</b>	0
<b>Color</b>	Silver
<b>Sizes</b>	1.89 in x 50 yd   48mm x 45,72m / 2.83 in x 50 yd   72mm x 45,72m 3.78 in x 50 yd   96mm x 45,72m / 4.72 in x 50 yd   120mm x 45,72m

**STORAGE & USAGE CONDITIONS:** Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application, and the user must, by test or otherwise, determine suitability for purpose; ECHOtape makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for ECHOtape to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.