

DESCRIPTION

OV-G5254 is an overlamine film (.95 mil thick) with a matte finish. The self-wound overlamine film is coated with a high-grade, water-clear, emulsion acrylic system. The film is resistant to acids, chemicals, and oils and conforms to FDA regulations 21 CFR 175.105 and 21 CFR 177.1520. The film has a water-based, acrylic adhesive, and it can improve label strength while offering enhanced gloss and clarity. Available in transparent (with a matte finish), this overlamine film is often used for food and beverage containers, decals, electronics, appliances, toys, and screen printing.

APPLICATIONS

- Beverage and food containers
- Computer printable decals
- Electronics and appliances
- Insurance cards
- Pharmaceutical applications
- Screen printing
- Toys
- Reinforcement

FEATURES & BENEFITS

- Self-wound
- Improves label strength while offering enhanced gloss and clarity
- Resistant to acids, chemicals, and oils
- Resistant to moisture
- Resistant to abrasion
- Resistant to UV light
- Conforms to FDA regulations 21 CFR 175.105 and 21 CFR 177.1520
- Glossy finish

PRODUCT CONSTRUCTION

Backing	BOPP 0.75 mils
Adhesive	Water-Based Acrylic

TECHNICAL DATA

Thickness	.95 mils
Tensile	14 lbs/in
Adhesion	12 oz/in
Application Temperature	-10°F to 200°F (-23° to 93°C)
Service Temperature	-32°F to 140°F (0°C to 60°C)
Elongation	140%
Color	Transparent
Sizes	Custom Slitting

STORAGE & USAGE CONDITIONS: Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOTape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application, and the user must, by test or otherwise, determine suitability for purpose; ECHOTape makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOTape product is proved to be defective, the exclusive remedy, shall be for ECHOTape to replace the defective product. ECHOTape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.